

2N IP Verso Security Intercom Owner's Manual

Home » 2N » 2N IP Verso Security Intercom Owner's Manual

2N IP Verso Security Intercom Owner's Manual



2N® IP Verso

The 2N® IP Verso security intercom is configurable to your needs thanks to its modularity. It provides reliable

access control and allows you to easily interface with other systems. Now also in black, with a fingerprint reader, Bluetooth module, or touch display.

Offices and office buildings
Residential complexes
Family houses
Schools and campuses
State administration public buildings
Home Automation Hotels



Bluetooth technology

Get the latest technology in access systems. The Bluetooth module lets you eliminate access codes, entry cards, and key distribution.

Touchscreen

Create an intuitive and structured contact list similar to that in your mobile phone. It is water resistant vandal resistant and easy to read even in direct sunlight.

Camera with night vision

See who is standing in front of your door, even in total darkness. Moreover, the camera is hidden from normal view. The intruder has no clue they're being monitored.

Contents

- **1 FEATURES & BENEFITS**
- 2 DIAGRAM
- **3 TECHNICAL**
- **PARAMETERS**
- **4 SOFTWARE**
- **5 MODULARITY CLARIFIED**
- **6 MODULES**
- 7 FRAMES
- **8 ACCESSORIES**
- 9 Documents / Resources
 - 9.1 References

FEATURES & BENEFITS


Adjustable door security levels Make use of different security modes with the 2N® Mobile Key application, which allows you to adjust the functioning distance from the Bluetooth module.

Intuitive controls and search The touchscreen has all the functions of a mechanical keyboard. Discover its luxury design and intuitive controls and search.

Access control Achieve a greater level of security for all those at its location. 2N® IP Verso makes it easy to prevent the entry of unauthorized persons.

Modularity The modularity of this IP Intercom allows you to configure it to your requirements. Select the specific module, accessories and configurable functions.

DIAGRAM



TECHNICAL PARAMETERS


Signalling protocol —		Video stream	
SIP 2.0 (RFC - 3261)		Codecs	H.263+, H.263, H.264, MJPEG, MPEG-4
Buttons		RFID card reader	
Buttons	Transparent buttons with white backlight	RFID card reader	13.56MHz and 125kHz
	and easily removable label	Support for NFC	Yes, HCE and the 2N® Mobile Key
Number of buttons	1 to 146		application needed
Numeric keypad	Optional	Interfaces	
		Power supply	12V ± 15%/ 2A DC, or PoE
Audio	*	PoE	PoE 802.3af (Class 0 - 12.95W)
Microphone	1 built-in microphone	LAN	10/100BASE-TX with Auto-MDIX, RJ-45
Speaker	2W	Switch output	NC/NO contacts, max 30 V/1 A AC/DC
Sound pressure at 1 kHz		Active switch output	8 to 12 V DC depending on Power supply
at 1 m distance	78 dB		(PoE: 10 V; adapter: source voltage minus 2 V), max 400mA
Audio stream		Supported protocols	SIP2.0, DHCP opt. 66, ONVIF, SMTP,
Codecs	G.711, G.729, G.722, L16/16kHz		802.1x, RTSP, RTP, TFTP, HTTP, HTTPS, Syslog
Camera (optional) —	<u> </u>	Mechanical properties	
Resolution - JPEG	1280 x 960 px		-40°C - 60°C, touch display -30°C - 60°C
Resolution - video call	640 x 480 px	Operating temperature Storage temperature	-40°C - 70°C
Viewing angle	120° (H), 90° (V), 145° (D)	Operating relative	-40-0 - 70-0
Night vision	Yes	humidity	10%-95% (non-condensing)
		Coverage level	IP 54, IK08, touch display IK07
Bluetooth module (opti	onal)	Coverage level	ir 34, ixoo, toddii display ixo
Bluetooth Smart techno	logy	Dimensions	
Security	RSA-1024 and AES-128		configuration of the modules and
		installation type - see w	
Touchscreen (optional)			
Buttons and keyboard for	unctions		

SOFTWARE


2N® Mobile Video – mobile application providing video calls from the intercom to your mobile device 2N® Access Commander – software to manage 2N IP Intercoms and access units 2N® IP Eye – an application that enriches your desk phone with video from the intercom camera 2N® Network Scanner – application for detecting 2N IP Intercoms and access control units on the network 2N® Mobile Key – an application that turns your mobile phone into an access card

MODULARITY CLARIFIED


2N® IP Verso can be tailored to your requirements. Select the specific modules, frame and mounting box.



MODULES



FRAMES



Nickel version

ACCESSORIES

Boxes

Flush-mounting box for 1 module 9155014 Flush-mounting box for 2 modules 9155015 Flush-mounting box for 3 modules 9155016

Other

Extension cable - 1 m long 9155050

Blind button 9155051 Nametag foil 9155052

Backplates

Backplate - 1 module 9155061

Backplate - 2 modules 9155062

Backplate – 3 modules 9155063

Backplate - 2(w) x 2(h) modules 9155064

Backplate – 3(w) x 2(h) modules 9155065

Backplate $-2(w) \times 3(h)$ modules 9155066

ACCESSORIES

Backplate - 3(w) x 3(h) modules 9155067

2N TELEKOMUNIKACE a.s., Modřanská 621, 143 01 Prague 4, CZ, +420 261 301 500, sales@2n.cz, www.2n.cz

Documents / Resources



2N IP Verso Security Intercom [pdf] Owner's Manual

2 Modules, 3 Modules Recommended with 9155063, IP Verso, IP Verso Security Intercom, Security Intercom, Intercom



2N IP Verso Security Intercom [pdf] Instruction Manual 9155062, IP Verso, IP Verso Security Intercom, Security Intercom, Intercom

References

- Group Publishing
- 2N a Global Leader in IP Intercoms and Access Control 2N
- CIE award winning UK distributor for professional Audio Visual, Door Intercom & Access Control equipment

Manuals+,