



3M N95 9205+ Aura Particulate Respirator Instructions

[Home](#) » [3M](#) » 3M N95 9205+ Aura Particulate Respirator Instructions 

Contents

- [1 3M N95 9205+ Aura Particulate Respirator](#)
- [2 Use For](#)
- [3 Use Instructions](#)
- [4 Storage Conditions and Shelf Life](#)
- [5 Fitting Instructions](#)
- [6 FOR MORE INFORMATION](#)
- [7 Documents / Resources](#)
 - [7.1 References](#)



3M N95 9205+ Aura Particulate Respirator



IMPORTANT: Keep User Instructions for reference.

WARNING



This respirator helps protect against certain particles. Misuse may result in sickness or death. For correct use, consult the supervisor, and User Instructions, or call 3M in the U.S.A., 1-800-247-3941. In Canada, call Technical Service at 1-800-267-4414.

Use For

Helping to reduce exposure to certain airborne particulates such as coal, silica, iron ore, metal, wood, biological and certain other particles, and liquid or non-oil based particles from sprays that do not also emit oil aerosols or vapors. Follow all applicable local regulations. For additional information on 3M use recommendations for this class of respirator please consult the 3M Respirator Selection Guide found at www.3M.com/respiratorselector or call 1-800-247-3941 in U.S.A. In Canada, call 1-800 267-4414.

Do Not Use For

Do not use for gases and vapors, oil aerosols, or sandblasting, unless nozzle and blast are physically separated from the operator in an exhaust-ventilated enclosure; particulate concentrations that exceed either 10 times the occupational exposure limit or applicable government regulations, whichever is lower. This respirator does not supply oxygen. In the U.S., do not use when OSHA substance-specific standards, such as those for asbestos,

arsenic, cadmium, lead in the construction industry, or 4,4'-methylene dianiline (MDA), specify other types of respiratory protection.

Use Instructions

1. Failure to follow all instructions and limitations on the use of this respirator and/or failure to wear this respirator during all times of exposure can reduce respirator effectiveness and may result in sickness or death.
2. Before occupational use of this respirator, in the U.S. a written respiratory protection program must be implemented meeting all the requirements of OSHA 29 CFR 1910.134 such as training, fit testing, medical evaluation, and applicable OSHA substance-specific standards. In Canada, CSA standard Z94.4 requirements must be met and/or requirements of the applicable jurisdiction, as appropriate.
3. The particles which can be dangerous to your health include those so small that you cannot see them.
4. Leave the contaminated area immediately and contact supervisor if dizziness, irritation, or other distress occurs.
5. Store the respirator away from contaminated areas when not in use.
6. Inspect the respirator before each use to ensure that it is in good operating condition. Examine all the respirator parts for signs of damage including the two headbands, nose clip, and if applicable: nose foam, valve, and face seal. Ensure two headbands are securely fastened to the respirator. For respirators with nosefoam, inspect nosefoam to ensure it is fully adhered to the respirator, not torn, not degraded, and is centered under nose clip. Inspect nose clip to ensure it is fully adhered to the respirator and there are no sharp edges protruding from the respirator. Inspect the respirator for holes, tears or separated seams. For valved respirators, ensure respirator valve diaphragm is present and functioning properly. For respirators with adjustable straps, ensure straps maintain tension when donned. For respirators with a faceseal, ensure face seal is fully adhered to the respirator and not torn or degraded. The respirator should be disposed of immediately upon observation of damaged or missing parts. Filtering facepiece respirators are to be inspected prior to each use to ensure there are no holes in the breathing zone other than the punctures around staples and no damage has occurred. Enlarged holes resulting from ripped or torn filter material around staple punctures are considered damage. Immediately replace the respirator if damaged. Small punctures around the staples are normal and do not interfere with the respirator's compliance with NIOSH approval requirements.
7. Dispose of used product in accordance with applicable regulations.

Use Limitations

1. This respirator does not supply oxygen. Do not use in atmospheres containing less than 19.5% oxygen.
2. Do not use when concentrations of contaminants are immediately dangerous to life or health, are unknown or when concentrations exceed 10 times the permissible exposure limit (PEL) or according to specific OSHA standards or applicable government regulations, whichever is lower.
3. Do not alter, abuse, wash or misuse this respirator.
4. Do not use with beards or other facial hair or other conditions that prevent a good seal between the face and the sealing surface of the respirator.
5. Respirators can help protect your lungs against certain airborne contaminants; however, they will not prevent entry through other routes such as the skin, which would require additional personal protective equipment (PPE).
6. This respirator is designed for occupational/professional use by adults who are properly trained in their use and

limitations. This respirator is not designed to be used by children.


7. Individuals with a compromised respiratory system, such as asthma or emphysema, should consult a physician and complete a medical evaluation prior to use.
8. When stored in accordance with temperature and humidity conditions specified below, the product may be used until the “use by” date specified on packaging.

Storage Conditions and Shelf Life

Before use, store respirators in the original packaging, away from contaminated areas, dust, sunlight, extreme temperatures, excessive moisture and damaging chemicals. When stored in accordance with temperature and humidity conditions specified below, the product may be used until the “use by” date specified on packaging. Always inspect product and conduct a user seal check before use as specified in User Instructions. If you cannot achieve a proper seal, do not use the respirator.



- End of Shelf Life
 - Use respirators before the “use by” date specified on packaging.



- Storage Temperature Range
 - -20°C (-4°F) to +30°C (+86°F).
- Storage Maximum Relative Humidity
 - <80% RH.




Time Use Limitations


- If respirator becomes damaged, soiled, or breathing becomes difficult, leave the contaminated area immediately and replace the respirator.

Fitting Instructions


Must be followed each time respirator is worn.



1. Remove respirator from packaging and hold with straps facing upward (1a). Place bottom strap under center flaps next to WARNING statement as shown (1b).
2. Fully open top and bottom panels, bending nosepiece around thumb at center of foam. Straps should separate when panels are opened. Make certain bottom panel is unfolded and completely opened.



3. Place respirator on your face so that the foam rests on your nose and the bottom panel is open under chin. Hold the bottom panel securely under your chin. Pull the top strap over your head and position it high on the back of the head (3a). Then pull the bottom strap over your head and position it around the neck and below the ears (3b). Adjust for a comfortable fit by pulling top panel toward the bridge of the nose and bottom panel under chin.



4. Place your fingertips from both hands at the top of the metal nosepiece. Using two hands, mold the nose area to the shape of your nose by pushing inward while moving your fingertips down both sides of the nosepiece.
- **Warning:** Pinching the nosepiece using one hand may result in improper fit and less effective respirator performance. Use two hands.
5. Perform a User Seal Check prior to each wearing. To check the respirator-to-face seal, cover the middle panel with one or both hands. For the 9205+ and 9210+ respirator, inhale and exhale sharply. For the 9211+ respirator, inhale sharply. Be careful not to disturb the position of the respirator. If air leaks around the nose, readjust the nosepiece as described in step 4. If air leaks around respirator edges, adjust panels and straps. If you CANNOT achieve a proper fit, DO NOT enter the contaminated area. See your supervisor.

NIOSH Approved: N95

- At least 95% filtration efficiency against solid and liquid aerosols that do not contain oil.

THESE RESPIRATORS ARE APPROVED ONLY IN THE FOLLOWING CONFIGURATIONS:

		RESPIRATOR COMPONENTS			CAUTIONS AND LIMITATIONS ²
		FILTERING FACEPIECE			
TC-	PROTECTION ¹	9210+	9211+	9205+	
84A-5668	N95	X			ABCJMNOP
84A-5669	N95		X		ABCJMNOP
84A-8590	N95			X	ABCJMNOP

PROTECTION

- N95 -Particulate Filter (95% filter efficiency level) effective against particulate aerosols free of oil; time use restrictions may apply.

CAUTIONS AND LIMITATIONS

- **A:** Not for use in atmospheres containing less than 19.5 percent oxygen.
- **B:** Not for use in atmospheres immediately dangerous to life or health.
- **C:** Do not exceed maximum use concentrations established by regulatory standards.
- **J:** Failure to properly use and maintain this product could result in injury or death.
- **M:** All approved respirators shall be selected, fitted, used and maintained in accordance with MSHA, OSHA and other applicable regulations.
- **N:** never substitute, modify, add, or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
- **O:** Refer to User's Instructions, and / or maintenance manuals for information on use and maintenance of these respirators.
- **P:** NIOSH does not evaluate respirators for use as surgical masks.

This respirator contains no components made from natural rubber latex.

FOR MORE INFORMATION

In United States, contact:

- **Website:** www.3M.com/PPESafety
- **Technical Assistance:** 1-800-243-4630
- **For other 3M products:** 1-800-3M-HELPS or 1-651-737-6501

3M Personal Safety Division

- 3M Center, Building 0235-02-W-70
- St. Paul, MN 55144-1000

© 3M 2022. All rights reserved.

3M is a trademark of 3M Company, used under license in Canada.

Patented. See 3M.com/patent

<http://innovation.3m.co.kr/safety>

Documents / Resources



[3M N95 9205+ Aura Particulate Respirator](#) [pdf] Instructions

N95 9205 Aura Particulate Respirator, N95, 9205 Aura Particulate Respirator, Aura Particulate Respirator, Particulate Respirator, Respirator

References

- [3M 3M Patent Marking | Search for 3M Patent Information](#)
- [3M 3M](#)
- [Worker Health and Safety | PPE | 3M Canada](#)
- [3M EPP Soluciones de Seguridad | Salud y Seguridad Ocupacional | 3M](#)
- [3M PPE Safety Solutions | Worker Health & Safety | 3M US](#)
- [3M 3M.com/respiratorselector](#)