



ABB NS71E-26 Contactor Relay User Manual

[Home](#) » [ABB](#) » ABB NS71E-26 Contactor Relay User Manual 

ABB NS71E-26 Contactor Relay



Contents

- [1 General Information](#)
- [2 Ordering](#)
- [3 Popular Downloads](#)
- [4 Dimensions](#)
- [5 Technical](#)
- [6 Technical UL/CSA](#)
- [7 Environmental](#)
- [8 Certificates and Declarations](#)
- [9 Container Information](#)
- [10 Classifications](#)
- [11 Categories](#)
- [12 Documents / Resources](#)
- [13 Related Posts](#)

General Information

Extended Product Type	NS71E-26
Product ID	1SBH101001R2671
EAN	NS71E-26 230V50/60HZ Contactor Relay
Long Description	NS... contactor relays are used for switching auxiliary circuits and control circuits. – Poles: 8- pole contactor relays (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1 including the “Mechanically Linked” symbol on the contactor relay side) – Control circuit: AC operated with laminated magnet circuit – Accessories: a wide range of accessories is available

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Instructions and Manuals	1SBC101020M9701
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	100.2 mm
Product Net Height	68 mm
Product Net Weight	0.26 kg

Technical

Number of Auxiliary Contacts NO	7
Number of Auxiliary Contacts NC	1
Contacts NC	IEC 60947-5-1 and EN 60947-5-1, UL 508, CSA C22.2 N°14
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Frequency (f)	Main Circuit 690 V
Conventional Free-air	Auxiliary Circuit 50 / 60 Hz

Thermal Current (I _{th})	acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 10 A
Rated Operational Current AC-15 (I _e)	(500 V) NC 2 (500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Maximum Electrical Switching Frequency	(AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour
Rated Operational Current DC-13 (I _e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/C SA 600 V
Rated Impulse Withstand Voltage (U _{imp})	Auxiliary Circuit 6 Kv
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit	50 Hz 230 V
Voltage (U _c)	60 Hz 230 V
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 22 ms Between Coil De-energization and NO Contact Opening 5 ... 19 ms Between Coil Energization and NC Contact Opening 6 ... 18 ms Between Coil Energization and NO Contact Closing 9 ... 24 ms
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Wire Stripping Length	Auxiliary Circuit 9 mm Control Circuit 9 mm
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals I P20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals I P20
Terminal Type	Screw Terminals

Technical UL/CSA

Tightening Torque UL/CSA	Auxiliary Circuit 9 in-lb Control Circuit 9 in-lb
--------------------------	---

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... 70 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Vibrations acc. to IEC 60068-2-6	5 ... 300 Hz 3 g Closed position / 2 g Open position
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: C1 19 g Closed, Shock Direction: C2 16 g Open, Shock Direction: C1 8 g Open, Shock Direction: C2 13 g Shock Direction: A 20 g Shock Direction: B1 5 g Shock Direction: B2 15 g
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificates and Declarations

CB Certificate	CB_CN_32453
CCC Certificate	CCC_2007010305248106
CQC Certificate	CQC2007010305248106
Declaration of Conformity- CCC	2020980304001219
Declaration of Conformity – CE	1SBD250016U1000
Declaration of Conformity – UKCA	1SBD250051U1000
GOST Certificate	GOST_POCCCNME77B07821.pdf
UL Certificate	UL_220108-E312527A
UL Listing Card	NOA_E312527.pdf

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	72 mm
Package Level 1 Depth / Length	115 mm
Package Level 1 Height	48 mm
Package Level 1 Gross Weight	0.26 kg
Package Level 1 EAN	3471523004269
Package Level 2 Units	32 piece
Package Level 2 Width	250 mm
Package Level 2 Depth / Length	315 mm
Package Level 2 Height	195 mm
Package Level 2 Gross Weight	8.32 kg
Package Level 3 Units	768 piece

Classifications

Object Classification Code	K
ETIM 4	EC000196 – Contactor relay
ETIM 5	EC000196 – Contactor relay
ETIM 6	EC000196 – Contactor rel
ETIM 7	EC000196 – Contactor relay
ETIM 8	EC000196 – Contactor relay
eClass	V11.0 : 27371001
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4761 >> Magnet contactor, AC-switching

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors



© 2023 ABB. All rights reserved. 2023/08/10 Subject to change without notice



Documents / Resources



[ABB NS71E-26 Contactor Relay](#) [pdf] User Manual
NS71E-26 Contactor Relay, NS71E-26, Contactor Relay, Relay

[Manuals+](#)