

AEOTEC MultiSensor 7 User Guide

Home » Aeotec » AEOTEC MultiSensor 7 User Guide 🖫

Contents

- 1 AEOTEC MultiSensor 7
- **2 Package Contents**
- **3 Button Functions**
- 4 Important safety information
- **5 Advanced Functions**
- **6 Manual Hard Resetting MultiSensor**
- 7 Documents / Resources
 - 7.1 References
- **8 Related Posts**



AEOTEC MultiSensor 7




Aeotec MultiSensor 7 was developed to detect ambient values and movement and to transmit them with Z-Wave Plus (https://aeotec.com/z-wave-home-automation/zwave-gen7.html) technology. You can find out more about MultiSensor 7 (https://aeotec.com/z-wav To see whether MultiSensor 7 is known to be compatible with your Z-Wave system or not, please reference our Z-Wave gateway comparison technical specifications of MultiSensor (https://help.aeotec.com/a/solutions/articles/6000246153) can be viewed at that link.

Get to Know your MultiSensor

Your MultiSensor comes packaged with a number of accessories that will help with its installation and operation.

Package Contents

- 1. MultiSensor
- 2. Battery Cover
- 3. USB Cable
- 4. Double-Sided Tape
- 5. Screws (x2)
- 6. Back Arm Mount



Button Functions

Action button press	LED Status		Function
1x Tap (when factory reset)	S oli d	Yellow	Pair Mode Enters Z-Wave pair mode, flashes white/green 4
			Sends NIF / Excludes device
1x Tap (when already paired)	S oli d	Purple	if Z-Wave controller is in unpair mode, starts blue reset s uccessfully.
Press and hold [1, 2 seconds)	No LED		N/A

			Quick Wakeup
Press and hold [2, 5 seconds)	Solid Red		LED will disappear as soon as you release its but wakeu p report to your Z-Wave Controller to take i waiting in you r controller.
			Long Wakeup Mode
Press and hold [5, 9 seconds)	Solid Orange		LED will remain solid Orange upon release of its told to s leep by user or z-wave controller). This w device while the sensor is used with battery powe does not queue the command.
			Communication Health Test (Direct gateway co repeat ers).
			This will test your MultiSensor 7 direct communic remain Cyan while it is testing.
			Once finished it will become a solid color for 2 se indicat e health:
Press and hold [9, 15 seconds)	S oli d	Cyan	Red = Bad health, can't communicate at all. Yellow = Mo derate health, could use improvemen Green = Great hea lth
Press and hold [15, 20 second s)	Blinking Red		Release here to cancel Factory Reset.
Press and hold [20+ seconds)	Blue fade in/out for 2 seconds.		Factory Reset.

Important safety information

1. Remove the battery cover by sliding the Unlock button LEFT, then pull the cover off.




- 2. Insert the micro USB of the provided USB cable into your sensor's micro USB port.
- 3. Insert the larger end of the USB cable into a computer or any 5V adapter which will immediately power your MultiSensor 7.

4. Make sure to seat the Battery Cover back onto the MultiSensor 7 and lock it in by sliding the Unlock button RIGHT.




For a battery-powered installation (acts as a sleeping device upon initial pair):


1. Remove the battery cover by sliding the Unlock button LEFT, then pull the cover off.



2. Insert two CR123A lithium batteries orientated according to the diagram within your sensor. Try inserting the batteries flat rather than at an angle.



Action Button



Note: MultiSensor 7 can be powered by a single CR123A (doesn't matter which port), though batteries will require changing

WARNING: Not compatible to rechargeable CR123A batteries (3.6V).

- 3. Make sure to seat the Battery Cover back onto the MultiSensor 7 and lock it in by sliding the Unlock button RIGHT.
- 4. It will be solid yellow during inclusion, and flash white/green 3 times if paired successfully. If it fails, it will flash white/red instead.

Advanced Functions

Z-Wave Resetting MultiSensor 7.


Your MultiSensor can be removed from your Z-Wave network at any time. You'll need to use your Z-Wave

network's main controller t this. If you are using other products as your main Z-Wave controller, please refer to the part of their respective manuals that tells you how remove

Using an existing gateway:

You may need to refer to your gateway's method of including devices if you do not know how to pair a Z-Wave device. You may use MultiSensor 7 even if they are not paired together to factory reset MultiSensor 7.

- 1. Set your Z-Wave gateway into Z-Wave unpair (exclusion) mode.
- 2. Tap the action button once; the purple led will light up.




3. If removed successfully, the blue led will fade in and out to indicate it is ready to be paired to a new hub.

Manual Hard Resetting MultiSensor 7

This method is not fully advised unless your gateway has failed, if paired to your network, performing these steps will factory reset yo phantom/ghost device in your working Z-Wave network.

- 1. Make sure the device has been powered.
- 2. Press and hold the button for 20 seconds. When the red led flashes, the device will enter the factory reset mode.



- 1. Press and hold the Multisensor 7 Action button
- 2. Wait until the LED turns into a solid orange color (2 5 seconds)
- 3. Release Multisensor 7 Action Button, the LED should remain solid orange while it is awake. Send any configurations from your h
 - If the MultiSensor 7 LED orange LED turns off right away, this would indicate that your hub is putting your device to sleep. T 1-3 again, then power up your hub again.
- 4. Tap the Action Button on Multisensor 7 to put Multisensor 7 back to sleep, or wait 5 minutes. (recommended to manually put it ba

There are further advanced parameter settings and group association settings not listed in this guide. You can find the attachment of the which will give you all possible functions of the MultiSensor 7 that may be missing in this guide. The PDF guide will feature these missing advanced settings:

- Parameter settings (Configuration Command Class)
- Group Association (Association Command Class)

You may download the engineering sheet below:

Documents / Resources



References

- ◆ Support Aeotec
- A <u>Support Aeotec</u>
- ◆ Support Aeotec
- A Smart Sensors Aeotec
- aws

s3.amazonaws.com/cdn.freshdesk.com/data/helpdesk/attachments/production/6124869921/original/5GicG 1618442008

- aws
 - s3.amazonaws.com/cdn.freshdesk.com/data/helpdesk/attachments/production/6124870013/original/eQ75L 1618442124
- aws

s3.amazonaws.com/cdn.freshdesk.com/data/helpdesk/attachments/production/6124870018/original/yjM98/1618442145

- aws
 - s3.amazonaws.com/cdn.freshdesk.com/data/helpdesk/attachments/production/6124870451/original/394qc 1618442963
- aws

s3.amazonaws.com/cdn.freshdesk.com/data/helpdesk/attachments/production/6124870901/original/8BrqV/7iWxslquVF6eP6_ucg.png?1618443742

- aws
 - s3.amazonaws.com/cdn.freshdesk.com/data/helpdesk/attachments/production/6124871129/original/matan 1618444192
- aws

s3.amazonaws.com/cdn.freshdesk.com/data/helpdesk/attachments/production/6124871219/original/Uw_S iGb65GDr6AQ.PNG?1618444342

- aws
 - s3.amazonaws.com/cdn.freshdesk.com/data/helpdesk/attachments/production/6124871447/original/qWOI1 1618444713
- aws

 $\underline{s3.amazonaws.com/cdn.freshdesk.com/data/helpdesk/attachments/production/6124871852/original/Rk_Gl}\\ \underline{4ELUVV3KA.png?1618445686}$

Manuals+,