

AJAX
StreetSiren Wireless
Siren with LED Frame



AJAX StreetSiren Wireless Siren with LED Frame Instructions

[Home](#) » [ajax](#) » AJAX StreetSiren Wireless Siren with LED Frame Instructions 

Contents

- [1 AJAX StreetSiren Wireless Siren with LED Frame](#)
- [2 Technical specifications](#)
- [3 Documents / Resources](#)
 - [3.1 References](#)

AJAX

AJAX StreetSiren Wireless Siren with LED Frame



Wireless siren with LED frame and piezoelectric buzzer. The device is designed for both outdoor and indoor installation.

Technical specifications

Classification	Siren with light alarms
Type of siren	Wireless
Installation method	Indoors and outdoors
Compatibility	All Ajax hubs and radio signal range extenders
Type of notification	Acoustic and LED
Alarm volume	From 85 to 113 dB at a distance of 1 m <i>Adjusted in the Ajax app</i>
Alarm duration	From 3 s to 3 min ¹ <i>Adjusted in the Ajax app</i>
Indication of arming mode	Yes
Indication of entry/exit delays	Yes <i>With firmware version 3.50 and higher</i> Learn more
Chimes	Yes <i>With firmware version 3.73.1.0 and higher</i> Learn more


Power supply	<p>Batteries</p> <p>4 × CR123A, 3 V</p> <p>Up to 5 years of battery life</p> <p>External power supply</p> <p>12 V , 1.5 A</p>
Jeweller communication technology	<p>Frequency bands</p> <p>866.0 – 866.5 MHz</p> <p>868.0 – 868.6 MHz</p> <p>868.7 – 869.2 MHz</p> <p>905.0 – 926.5 MHz</p> <p>915.85 – 926.5 MHz</p> <p>921.0 – 922.0 MHz</p> <p>depends on the region of sales</p> <p>Maximum effective radiated power (ERP)</p> <p>≤ 20 mW</p>

	Radio signal modulation GFSK Communication range up to 1,700 m in an open space Polling interval 12–300 s Adjusted by PRO or user with system configuration rights Learn more
Operating temperature range	From -25°C to +50°C
Permissible humidity	Up to 95%
Protection class	IP54
Anti-sabotage	Protection against forgery Jamming detection Tamper against enclosure opening Accelerometer against detachment
Dimensions	200 x 200 x 51 mm
Weight	528 g
Warranty	24 months from the date of sale Learn more
Complete set	StreetSiren SmartBracket mounting panel 4 × CR123A battery (pre-installed) Installation kit Quick Start Guide

Compliance with standards

¹ Alarm duration of 3 to 15 minutes is available only for sirens with firmware version 5.60.4.14 or higher. The function is available in the USA and Canada only when the siren is connected to the hub with NA X.X.X firmware version.

Documents / Resources

	AJAX StreetSiren Wireless Siren with LED Frame [pdf] Instructions 38330.07.BL1, StreetSiren Wireless Siren with LED Frame, StreetSiren, Wireless Siren with LED Frame, Siren with LED Frame, LED Frame, Frame
---	--

References

- [User Manual](#)

Manuals+. Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.