




AMBIENTECH TECH-WSx-SA Wall Switch Instruction Manual

[Home](#) » [AMBIENTECH](#) » AMBIENTECH TECH-WSx-SA Wall Switch Instruction Manual 

AMBIENTECH TECH-WSx-SA Wall Switch



Contents

1 Wall Switch Installation

1.1 Wall Box

1.2 Maximum Load

1.3 Before You Begin

2 Item Identification

3 Pairing

3.1 Connect to the SmartAir App

4 Operation – Dimmer Wall Switch

5 Customer Assistance

5.1 Caution

5.2 FCC/IC Information

6 Troubleshooting

7 Documents / Resources

8 Related Posts

Wall Switch Installation

Wall Box

1. A standard single-gang wall box sized 3 x 2 x 2 ½ cm will service Dimmer
2. Not compatible with multi or double Mud Rings.
3. When using a retrofit gang box (cut in box) you might need to recess the ears.


Maximum Load

Input Voltage	Max Load
120VAC	700W

Note: A maximum of 7 Drivers can be controlled with each Wall Switch


Before You Begin

To avoid fire, shock, or death, turn the power Off at circuit breaker and test to ensure the power is Off before wiring.



Step I: Prepare Wall Box Wires


1. Make sure that the ends of the wires from the wall box are straight (cut if needed).
2. Strip the wire insulator for each wire inside the wall box as shown here:



Strip 5/8"(1.6 cm)

Step 2: Wire Wall Switch

Connect wires according to the wiring diagram below.



Wiring Description (Using wire connectors)


1. Connect the green (or bare copper) wire from the wall box to the green Wall Switch wire.
2. Connect the line/hot wire from the wall box to the black Wall Switch wire.
3. Connect the black LED Driver wire to the red Wall Switch wire.
4. Connect the white wire from the wall box to the white LED Driver wire and the white Wall Switch wire.

Step 3: Mount the Wall Switch

Mount the Wall Switch into the wall box using the screws provided.


Step 4: Restore Power

1. Turn the power On at the circuit breaker.
2. Verify 120V with a Voltmeter




Item Identification


- Mounting Screws




- Wire Connectors



- Cover Plate



- Wall Switch




Pairing

If you are installing more than one Wall Switch unit, all others must be switched Off while pairing.

1. Make sure both sliders are set to the top and the Wall Switch is switched Off.
2. Switch the power On at the circuit breaker.
3. Turn On the Wall Switch, the green LED Indicator will blink while pairing.

4. After up to 15 seconds, your LED fixture will be paired with the Wall Switch.
5. To verify pairing is successful, move the sliders and ensure that the LEDs respond accordingly.
6. If you're installing a smart wall switch, scan the QR code to download the app. Follow the instructions to connect to the SmartAir App.

* If pairing is not successful, press the Wall Switch pairing/ reset button.




Connect to the SmartAir App

- Scan the QR code to download the App. Follow the instructions to connect to the SmartAir App



Operation – Dimmer Wall Switch



Customer Assistance

For technical questions regarding the installation or operation of this product, please contact our customer support team:



347-334-6368 ext 3



www.ambientechinc.com



Caution

To reduce the risk of overheating and possible damage to other equipment, do not install to control a receptacle, A motor-operated appliance, or a transformer-supplied appliance.

“GRADATEURS COMMANDANT UN BALLAST – AFIN DE REDUIRE LE RISQUE DE SURCHAUFFE ET LA POSSIBILITE D’ENDOMMAGEMENT A D’AUTRES MATERIELS, NE PAS INSTALLER POUR COMMANDER UNE PRISE, UN APPAREIL A MOTEUR,”

FCC/IC Information

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:


1. This device may not cause harmful interference.
2. This device must accept any interference received, including interference that may cause undesired operation.

Troubleshooting

Symptoms	Cause	Possible Solution
Wall Switch LED Indicator blinking RED	The pairing/ reset button is pressed while the wall switch is off	Turn ON the Wall Switch and press the Pairing button again
Wall Switch LED Indicator steady RED	The Wall Switch is trying to perform pairing	Turn On the Wall Switch until pairing is completed
Lights do not respond to Wall Switch	The Breaker is Off, or tripped Improper pairing	Turn power On at the Circuit breaker Perform “Pairing”
	Improper wiring	Make sure all wires are connected according to the wiring diagram
	Short circuit at the LED Driver output	Check LED Driver output for short circuits
The wall switch is	The Wall Switch was	Perform “Pairing”.
controlling	paired with the	Make sure all the other
the wrong lights	wrong LED Driver	Wall Switches are turned
(Only if multiple		Off while pairing
Wall Switches units are		
installed in the		
same location)		
Wall Switch/ LED Driver	Any reason	Perform “Pairing”.
Replacement		Make sure all the other
		Wall Switches are
		turned Off while
		pairing

AMBIENTECH

Documents / Resources



[AMBIENTECH TECH-WSx-SA Wall Switch](#) [pdf] Instruction Manual
TECH-WSx-SA Wall Switch, TECH-WSx-SA, Wall Switch, Switch

Manuals+