



ANPVIZ IPC-D3083WD-S 8MP Smart Dual Light Fixed Turret Network Camera User Manual

[Home](#) » [ANPVIZ](#) » ANPVIZ IPC-D3083WD-S 8MP Smart Dual Light Fixed Turret Network Camera User Manual 

ANPVIZ IPC-D3083WD-S 8MP Smart Dual Light Fixed Turret Network Camera User Manual



- High quality imaging with BMP resolution
- Support Human and Vehicle Detection
- Smart Dual-Light: advanced technology with long range
- Built-in microphone for real-time audio security
- Water and dust resistant (IP67)
- Efficient H.265+ compression technology
- Support on-board storage up to 256 GB (SD card slot)

Contents

- [1 Specification](#)
- [2 Dimension](#)
- [3 Accessory – Optional](#)
- [4 Documents / Resources](#)
- [4.1 References](#)


Specification

Camera	
Image Sensor	1/2.4" Progressive Scan CMOS
Max. Resolution	3840×2160
Shutter Time	1/3 s to 1/100,000 s
Min. Illumination.	Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Day & Night	IR cut filter
Angle Adjustment	Pan: 0°to 360°, tilt: 0°to 75°, rotate: 0° to 360°
Lens	
Lens Type	2.8 mm Fixed focal lens.
Focal Length & FOV	2.8 mm, horizontal FOV 98°, vertical FOV 54°, diagonal FOV 114°
Lens Mount	M12
Iris Type	Fixed
Aperture	F1.6
DORI	
DORI	2.8 mm, D: 63 m, O: 25 m, R: 12 m, I: 6 m
Illuminator	
Supplement Light Type	IR, White Light IR: up to 30 m
Supplement Light Range	White Light: up to 20 m
Smart Supplement Light	Yes
IR Wavelength	850 nm
Video	
Main Stream	50 Hz: 12.5fps(3840×2160)20 fps (3200 x 1800, 2688 × 1520, 1920 x 1080, 1280 × 720) 60 Hz: 15fps(3840×2160)20 fps (3200 x 1800, 2688 × 1520, 1920 x 1080, 1280 x 720)
Sub-Stream	50 Hz: 20 fps (1280 x 720, 640 x 480, 640 x 360) 60 Hz: 20 fps (1280 x 720, 640 x 480, 640 x 360)

Video Compression	Main stream: H.265+/H.265/H.264+/H.264, Sub-stream: H.265/H.264/MJPEG
Video Bit Rate	32 Kbps to 16 Mbps
H.264 Type	Baseline Profile, Main Profile, High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR, VBR
Region of Interest (ROI)	1 fixed region for main stream
Audio	
Audio Type	Mono sound
Environment Noise Filtering	Yes
Audio Sampling Rate	8 kHz/16 kHz
Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC-LC
Audio Bit Rate	64 Kbps (G.711 ulaw)/64 Kbps (G.711 alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/16 to 64 Kbps (AAC-LC)
Network	
Security	Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address)
Simultaneous Live View	Up to 6 channels
API	Open Network Video Interface (Profile S, Profile T, Profile G (only -F model supports)), I SAPI, SDK
Protocols	TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP
User/Host	Up to 32 users 3 user levels: administrator, operator, and user
Client	iVMS-4200, Hik-Connect /Guarding Vision
Web Browser	Plug-in required live view: IE 10, IE 11,Local service: Chrome 57.0+, Firefox 52.0+
Image	
Wide Dynamic Range (WDR)	120 dB
SNR	≥ 52 dB
Day/Night Switch	Day, Night, Auto, Schedule
Image Enhancement	BLC, HLC, 3D DNR
Image Settings	Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance, adjustable by client software or web browser

Privacy Mask	4 programmable polygon privacy masks
Interface	
Ethernet Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
On-Board Storage	Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 256 GB
Built-in Microphone	Yes
Reset Key	Yes
Event	
Basic Event	Motion detection, video tampering alarm, exception
Linkage	Upload to FTP/memory card, send email, notify surveillance center, trigger recording, trigger capture
General	
Power	12 VDC $\pm$ 25%, 0.4 A, max. 5 W, Ø5.5 mm coaxial power plug reverse polarity protection, PoE: IEEE 802.3af, Class 3, max. 6.5 W
Material	Metal & Plastic
Dimension	Ø110 mm x 89.2 mm (Ø 4.3" x 3.5")
Package Dimension	150 mm x 150 mm x 141 mm (5.9" x 5.9" x 5.6")
With Package Weight	Approx. 340 g (0.7 lb.)
Storage Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Startup and Operating Conditions	°C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Language	English etc
General Function	Heartbeat, anti-banding, mirror, password protection, password reset via email
Approval	
EMC	FCC: 47 CFR Part 15, Subpart B, CE-EMC: EN 55032: 2015, EN 61000-3-2:2019, EN 61000-3-3: 2013+A1:2019, EN50130-4: 2011 +A1: 2014, RCM: AS/NZS CISPR 32: 2015, IC: ICES-003: Issue 7
Safety	UL: UL 62368-1, CB: IEC 62368-1: 2014+A11, CE-LVD: EN 62368-1: 2014/A11: 2017, BIS: IS 13252 (Part 1): 2010/IEC 60950-1:2005
Environment	CE-RoHS: 2011/65/EU, WEEE: 2012/19/EU, Reach: Regulation (EC) No 1907/2006
Protection	IP67: IEC 60529-2013

Dimension



Accessory – Optional

JB1280ZJ-DM8 Junction Box	WM1273ZJ-130-TRL Wall Mount
	



Documents / Resources



[ANPVIZ IPC-D3083WD-S 8MP Smart Dual Light Fixed Turret Network Camera](#) [pdf] User Manual

IPC-D3083WD-S 8MP Smart Dual Light Fixed Turret Network Camera, IPC-D3083WD-S, 8MP Smart Dual Light Fixed Turret Network Camera, Light Fixed Turret Network Camera, Fixed Turret Network Camera, Turret Network Camera, Network Camera, Camera

References

- [User Manual](#)