



anslut 018829 Work Lamp LED Instruction Manual

[Home](#) » [anslut](#) » anslut 018829 Work Lamp LED Instruction Manual

Contents [[hide](#)]

- 1 [anslut 018829 Work Lamp LED](#)
- 2 [OPERATING INSTRUCTIONS](#)
- 3 [SAFETY INSTRUCTIONS](#)
 - 3.1 [RISK GROUP 2](#)
 - 3.2 [SYMBOLS](#)
 - 3.3 [TECHNICAL DATA](#)
- 4 [USE](#)
 - 4.1 [CHARGING](#)
 - 4.2 [POWER SWITCH FUNCTION](#)
 - 4.3 [DIMMING FUNCTION](#)
- 5 [MAINTENANCE](#)
- 6 [Documents / Resources](#)
 - 6.1 [References](#)
- 7 [Related Posts](#)



anslut 018829 Work Lamp LED



OPERATING INSTRUCTIONS

Important! Read the user instructions carefully before use. Save them for future reference. Julia reserves the right to make changes. For latest version of operating instructions, see www.jula.com

JULA AB, BOX 363, SE-532 24 SKARA
2022-02-02
© Julia AB

SAFETY INSTRUCTIONS

- Do not use the product near flammable materials or gas.
- The LEDs must not be covered during use.
- Only use the supplied charger.
- Keep this product out of the reach of children.
- Always check the charger cord before use. Replace the charger if the cord is damaged.
- Recycle used batteries in accordance with local regulations.
- Never shine the light in the eyes of people or animals.

RISK GROUP 2

WARNING!

The product emits optic radiation that can result in a risk of personal injury. Do not look at the light source when it is switched on. Risk of eye damage.

SYMBOLS


TECHNICAL DATA

- Rechargeable lithium battery 3.7 V / 2500 mAh
- Protection rating IP67
- Output main spotlight COB LED 10 W
- Output secondary spotlight LED 2 W
- Luminous flux main spotlight approx. 800 lm
- Luminous flux secondary spotlight approx. 160 lm
- Ambient temperature –10 to 45°C
- Run time main spotlight 2.5 to 12 h
- Run time secondary spotlight 12 h
- Dimming function 10 to 100%
- Charging time Approx. 3 h
- Safety class III
- Charging 5 V, 1000 mA

DESCRIPTION

1. Car spotlight
2. Main spotlight
3. Power switch
4. Dimmer button
5. Battery indicator
6. Charger connection micro USB
7. Swivel magnetic mount 360°
8. Heavy-duty pivoting metal hang

FIG. 1



USE

CHARGING

1. Connect USB charger to the power supply.
2. Connect charger cord to micro USB port.
3. The battery charge status is shown on the battery indicator. When all 4 status lights go on the battery is fully charged.

NOTE: Fully charge the batteries before using for the first time.

POWER SWITCH FUNCTION

First press	Main spotlight COB LED goes on
Second press	Secondary spotlight LED goes on
Third press	Spotlights go off
If the switch is not touched for 3 seconds the next time it is pressed will switch it off.	

DIMMING FUNCTION

Main spotlight COB LED	10 to 100%
Secondary spotlight LED	10 to 100%

MAINTENANCE

The product should be recharged every 3 months for best battery life span.

Documents / Resources



[anslut 018829 Work Lamp LED](#) [pdf] Instruction Manual

References

-  [Jula à products for home and garden](#)
-  [Jula - mikään ei voi pysäyttää sinua nyt!](#)
-  [HTML](#)
-  [Jula – ingenting kan stoppe deg!](#)
-  [Jula – Teraz nic Cię nie powstrzyma!](#)
-  [Jula – inget kan stoppa dig nu!](#)