



APOLLO AP1004 Multigym Installation Guide

[Home](#) » [APOLLO](#) » APOLLO AP1004 Multigym Installation Guide 

Contents

- [1 APOLLO AP1004 Multigym](#)
- [2 Product Information](#)
- [3 Installation Guide](#)
- [4 Product Important Installation Safety Instructions](#)
- [5 IMPORTANT INSTALLATION SAFETY INSTRUCTIONS](#)
- [6 TOOLS REQUIRED](#)
- [7 CONCRETE BASE](#)
- [8 Documents / Resources](#)
 - [8.1 References](#)



APOLLO AP1004 Multigym



Product Information

The product being referred to is the APOLLO Multigym. It is a fitness equipment that is shipped partially assembled on a 4' x 6' pallet. The installation instructions are provided at the time of purchase. The APOLLO Multigym can be installed by two people in under four (4) hours assuming that the concrete base is already in place.

Installation Guide

Before starting the installation process, it is important to follow the safety instructions and have the necessary tools and equipment listed below.

Product Important Installation Safety Instructions

- Two people are required to install the APOLLO Multigym.
- Each person must wear steel-toed and steel-shank footwear.
- The person using the hammer drill must wear safety glasses.

Tools Required

- Hammer drill
- Four concrete anchors with a minimum pull-out or tension strength of 3400lbs per anchor
- Nylock nuts and oversized washers (mounting holes are 1" diameter) to fit anchors

- Ratcheting socket wrench set, pliers, Loctite & level
(Loctite is optional)
- Dolly or hand truck (optional)
- Shims (only needed if the concrete base is not level)

If you have any questions regarding the installation procedure, you can contact Outdoor-Fit at 1-877-760-6337 or email them at info@outdoor-fit.com. You can also visit their website at www.outdoor-fit.com for more information.

Complete Installation Instructions will be provided at time of purchase

- The APOLLO ships partially assembled on one 4' x 6' pallet.
- It is recommended to bring palletized unit as close to the installation site as possible.
- Assuming concrete is already in place, the APOLLO can be installed by two people in under four (4) hours.

IMPORTANT INSTALLATION SAFETY INSTRUCTIONS

- Two people are required to install the APOLLO Multigym
- Each person must wear steel toed and steel shank foot wear
- The person using the hammer drill must wear safety glasses

TOOLS REQUIRED


- Hammer drill
- Four concrete anchors with minimum "pull out" or "tension" strength of 3400lbs per anchor
- Nylock nuts and oversized washers (mounting holes are 1" diameter) to fit anchors
- Ratcheting socket wrench set, Pliers, Loctite & level (Loctite is optional)
- Dolly or hand truck (optional)
- Shims (only needed if concrete base is not level)

CONCRETE BASE

- The APOLLO needs to be anchored into concrete for safe operation.
- It is recommended that the unit be anchored to a concrete pad or footing that is level and structurally sound with a minimum "pull out" or "tension" strength of 3400lbs per anchor.
- Always consult with a local concrete expert if pouring a new pad or footing for your installation.
- If you have existing concrete in place, and you know the dimensions and specs of concrete, contact a local concrete anchoring expert (HILTI, HD Supply, etc) to determine if existing pad will work for the APOLLO.

Please call Outdoor-Fit if you have questions on installation procedure: 1-877-760-6337 info@outdoor-fit.com · www.outdoor-fit.com.

Documents / Resources

	<p>APOLLO AP1004 Multigym [pdf] Installation Guide AP1004 Multigym, AP1004, Multigym</p>
--	--

References

-  [fit.com](#)
-  [Outdoor Fitness Equipment | Outdoor Gym Equipment](#)