

Culligan FM-15A

Culligan FM-15A Faucet Mount Filter

INSTRUCTION MANUAL

Introduction

The Culligan FM-15A Faucet Mount Filter provides advanced water filtration directly from your faucet. This system is designed to reduce various contaminants and improve water taste and odor for drinking and cooking. It features a simple diverter tab to switch between unfiltered tap water and filtered water.

Setup

No tools are required for the installation of the Culligan FM-15A faucet mount filter.

- 1. Prepare Faucet:** Remove the existing aerator from your sink faucet. Retain the gasket for potential use with adapters.
- 2. Determine Adapter Needs:**
 - If your faucet has external threads, no adapter is typically needed. Proceed to step 3.
 - If your faucet has internal threads, select the appropriate adapter from the included set. Screw the chosen adapter into your faucet.
- 3. Attach Filter:** Attach the Culligan FM-15A faucet filter to the faucet. Turn the swivel collar to tighten it securely under the faucet threads. Avoid using pliers to prevent overtightening.
- 4. Flush Filter:** Slowly turn on the cold water to about halfway open. Pull out the valve stem to direct water through the filter. It is essential to flush each new filter cartridge for 10 minutes to remove any carbon fines. These fines are not harmful but should be flushed out before consuming the filtered water.
- 5. Initial Use:** The valve stem will automatically return to the unfiltered position when the water is turned off. Allow the system to flush for approximately three seconds before each use. After the initial 10-minute flush, water can be run through the cartridge at full pressure.

You are now ready to enjoy fresh filtered Culligan water.




Image: The Culligan FM-15A Faucet Mount Filter shown installed on a kitchen faucet, with filtered water flowing into the sink.

Video: A demonstration of the Culligan FM-15A Faucet Mount Filter installation and operation, showing how to switch between filtered and unfiltered water.

Operating Instructions

The Culligan FM-15A Faucet Mount Filter allows for easy switching between filtered and unfiltered water:

- **Filtered Water:** To obtain filtered water, turn on the cold water and pull out the diverter tab. Water will flow through the filter.
- **Unfiltered Water:** To obtain unfiltered tap water, push the diverter tab in.

Note that the filtered water stream may have a reduced flow rate compared to unfiltered tap water. This is normal for filtration systems.

Culligan

Self-installed home solutions



Image: A child enjoying a glass of clean, filtered water, highlighting the benefit of the filtration system.

Maintenance

- **Filter Replacement:** The filter cartridge should be replaced approximately every 2 months or after filtering 200 gallons of water, whichever comes first. Actual filter life may vary depending on water quality and usage.
- **Replacement Cartridges:** Replacement cartridges are available for purchase.

Troubleshooting

- **Reduced Water Flow:** If the filtered water flow significantly decreases before the recommended replacement period, the filter cartridge may be clogged due to high sediment levels in your water. Replace the filter cartridge.
- **Leaking:** Ensure all connections are tight but not overtightened. Check that gaskets are properly seated.
- **Unusual Taste/Odor:** If filtered water develops an unusual taste or odor, the filter cartridge may be exhausted. Replace the filter cartridge.
- **Divertor Tab Issues:** If the diverter tab does not switch properly, check for any obstructions or wear.

Specifications

Brand	Culligan
Model Name	Faucet-Mount Advanced
Part Number	FM-15A
Product Dimensions	5.5" L x 3.5" W x 6.75" H

Item Weight	14.4 ounces
Installation Type	Faucet Mount
Purification Method	Carbon Block, Sedimentation
Maximum Flow Rate	0.5 Gallons Per Minute
Operating Pressure Range	30-100 PSI
Temperature Range	40-100°F
Filter Capacity	200 Gallons
Filter Life	Up to 2 months or 200 gallons
Certifications	Tested and certified by IAPMO against ANSI Standard 42 and 53
Included Components	Culligan FM-15A Advanced Faucet Filter, Two Aerator Adaptors



Image: The Culligan FM-15A Faucet Mount Filter in its white finish, ready for installation.



Off-the-grid goodness



Image: A person in a lab coat holding a beaker of water, representing the commitment to water quality.

Warranty Information

This product comes with a 2-year limited warranty. Refer to the warranty documentation included with your product for full details.

Customer Support

For questions regarding fit and installation, or for technical support, please contact Culligan by calling TOLL FREE [800-721-9243](tel:8007219243), then Press "1", and then Press "3". Support is available 8 a.m. – 5 p.m. Central Time.