

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [FIA](#) /

› [FIA GS907 Custom Fit Grille Bug Screen Instruction Manual](#)

## FIA GS907

# FIA GS907 Custom Fit Grille Bug Screen Instruction Manual

Model: GS907

## INTRODUCTION

This manual provides detailed instructions for the installation, operation, and maintenance of your FIA GS907 Custom Fit Grille Bug Screen. Designed for vehicle-specific applications, this product helps protect your vehicle's grille and radiator from insects, road debris, and small rocks. Please read these instructions thoroughly before beginning installation to ensure proper fit and function.

## PRODUCT OVERVIEW

The FIA GS907 Grille Bug Screen is a custom-fit accessory designed to shield your vehicle's front grille and radiator. It features a durable mesh construction and is engineered for easy, drill-free installation using the included Stick-A-Stud 3M adhesive-backed studs.

## Key Features:

- Custom Fit: Vehicle-specific design ensures precise fitment.
- Easy Installation: Utilizes Stick-A-Stud 3M adhesive-backed studs, eliminating the need for drilling.
- Protection: Guards the grille and radiator against bugs, rocks, and other road debris.



Image: A red pickup truck with the FIA grille bug screen installed on its front grille. The screen is black and fits snugly over the grille, providing a protective barrier.

## PACKAGE CONTENTS

Verify that all components are present before beginning installation:

- FIA GS907 Grille Bug Screen
- Hardware Kit (including Stick-A-Stud 3M adhesive-backed studs)



Image: A close-up of the "Stick-A-Stud" packaging, showing replacement fasteners. This kit contains the adhesive-backed studs used for installation.

## SETUP AND INSTALLATION

Follow these steps carefully for proper installation of your FIA GS907 Grille Bug Screen. No drilling is required.

### Tools Required:

- Cleaning cloth
- Rubbing alcohol or automotive surface cleaner

## Installation Steps:

- Prepare the Surface:** Thoroughly clean the area on your vehicle's grille where the bug screen will be attached. Use rubbing alcohol or an automotive surface cleaner to remove any dirt, wax, or grease. Allow the surface to dry completely.
- Position the Screen:** Carefully hold the FIA GS907 bug screen against your vehicle's grille to determine the optimal placement. Ensure it covers the desired area and aligns with the grille's contours.
- Apply Stick-A-Studs:** The bug screen attaches using Stick-A-Stud 3M adhesive-backed studs. Peel the backing from each stud and firmly press them onto the clean, dry surface of your grille at the designated attachment points on the bug screen. Apply firm pressure for at least 30 seconds to ensure proper adhesion.
- Attach the Screen:** Once all studs are securely in place, align the bug screen with the studs and press it firmly onto them. The screen should snap or secure onto the studs.
- Verify Security:** Gently tug on the edges of the installed bug screen to ensure it is securely fastened and will not dislodge during vehicle operation.



Image: A close-up view of the FIA logo badge on a black grille bug screen, indicating the product's branding and fitment.

## OPERATING INSTRUCTIONS

Once installed, the FIA GS907 Grille Bug Screen operates passively by providing continuous protection to your vehicle's grille and radiator. No active operation is required.

- The screen remains in place during vehicle operation, deflecting bugs, small rocks, and other road debris.
- Regularly inspect the screen for any damage or signs of loosening.

## MAINTENANCE

Proper maintenance will extend the life and effectiveness of your FIA GS907 Grille Bug Screen.

- **Cleaning:** Periodically clean the bug screen to remove accumulated insects and debris. This can be done with a soft brush, a damp cloth, or by rinsing with water. Avoid harsh chemicals or abrasive cleaners that could damage the screen material or the adhesive studs.
- **Inspection:** Regularly inspect the screen for any tears, holes, or signs of wear. Check the adhesive studs to ensure they remain firmly attached to the grille. If a stud becomes loose, it may need to be re-adhered or replaced.
- **Removal (Optional):** If temporary removal is desired (e.g., for deep cleaning of the grille or during winter months if not needed), carefully detach the screen from the studs. Store the screen in a clean, dry place.

## TROUBLESHOOTING

Problem	Possible Cause	Solution
Screen not adhering properly.	Surface not clean or dry; insufficient pressure during stud application; cold temperatures during installation.	Ensure grille surface is thoroughly cleaned and dry. Apply firm, sustained pressure to studs. Install in temperatures above 50°F (10°C) for optimal adhesive performance.
Screen appears loose or sags.	Studs are not properly aligned or secured; screen material stretched.	Re-check stud placement and adhesion. Ensure the screen is correctly attached to all studs. If material is stretched, contact FIA support.
Damage to screen material.	Impact from large debris; improper cleaning.	The screen is designed to protect, but severe impacts can cause damage. Replace if significantly damaged. Use only soft cleaning methods.

## SPECIFICATIONS

- Model:** GS907
- Series:** GS900 Series
- Brand:** FIA
- Manufacturer:** Fia
- Item Weight:** 1 pound
- Product Dimensions:** 18.5 x 4 x 4 inches (packaging dimensions)
- Special Features:** Custom fit bug screen, no-drill installation with Stick-A-Stud 3M adhesive.

## WARRANTY AND SUPPORT

For warranty information or technical support regarding your FIA GS907 Grille Bug Screen, please refer to the manufacturer's official website or contact their customer service department. Keep your purchase receipt as proof of purchase.

*Note: Specific warranty terms and conditions may vary.*

© 2023 FIA. All rights reserved.

For more information, visit [FIA Store on Amazon](#)