

[Manuals.plus](#) /

> [Lund](#) /

> Lund 426512 Catch-All Xtreme Tan 2nd Seat Floor Mat Instruction Manual

## Lund 426512

# Lund 426512 Catch-All Xtreme Tan 2nd Seat Floor Mat Instruction Manual

## INTRODUCTION

This manual provides essential information for the proper installation, use, and maintenance of your Lund 426512 Catch-All Xtreme Tan 2nd Seat Floor Mat. Designed for specific vehicle models with a 2nd seat tool tray, this custom-molded floor mat offers superior protection against dirt, moisture, and spills, while providing a slip-resistant surface for enhanced safety.

## SETUP AND INSTALLATION

The Lund Catch-All Xtreme floor mat is custom-molded for a precise fit in your vehicle's second-row seating area. Follow these steps for proper installation:

- 1. Prepare the Vehicle Floor:** Ensure the vehicle's second-row floor carpeting is clean and dry before placing the mat. Remove any existing floor mats or debris.
- 2. Position the Mat:** Carefully place the Lund Catch-All Xtreme mat into the second-row footwell. Align it with the contours of the vehicle's floor, paying attention to areas around the seat bases and any existing floor anchors. The mat is specifically designed to accommodate vehicles with a 2nd seat tool tray.
- 3. Secure the Mat:** The mat features a patented snap fastener system. Press firmly on the designated fastener points to engage them with the vehicle's floor anchors, if present. This ensures the mat remains securely in place during vehicle operation.
- 4. Verify Fitment:** After installation, confirm that the mat lies flat and does not interfere with the operation of pedals, seats, or doors. Adjust as necessary.



*This image displays the Lund Catch-All Xtreme Tan 2nd Seat Floor Mat. Observe its custom-molded design, which ensures a precise fit for the second-row floor area, particularly in vehicles equipped with a second-seat tool tray. The mat features integrated fastener points for secure placement.*

## OPERATING INSTRUCTIONS

---

Once installed, the Lund Catch-All Xtreme floor mat functions passively to protect your vehicle's interior. Its primary operational benefits include:

- **Floor Protection:** The heavy-duty thermoplastic material creates a barrier against dirt, snow, water, grease, and various chemicals, preserving the original carpeting.
- **Slip Resistance:** The textured surface is designed to provide a secure footing, aiding in safer entry and exit from the vehicle.
- **Durability:** Engineered to resist cracking, splitting, and breaking under normal use conditions.

## MAINTENANCE AND CARE

---

To ensure the longevity and continued effectiveness of your Lund Catch-All Xtreme floor mat, regular cleaning is recommended:

- **Routine Cleaning:** For light dirt and dust, simply shake out the mat or use a vacuum cleaner.
- **Deep Cleaning:** For heavier soiling, spills, or stains, remove the mat from the vehicle. Wash with mild soap and water using a soft brush or cloth. Rinse thoroughly with clean water.
- **Drying:** Allow the mat to air dry completely before reinstalling it in the vehicle. Do not use harsh chemicals or abrasive cleaners, as these may damage the thermoplastic material.
- **Avoid Extreme Temperatures:** While durable, prolonged exposure to extreme heat or cold can affect the material. Store in a moderate environment if removed for extended periods.

## TROUBLESHOOTING

---

The Lund Catch-All Xtreme floor mat is designed for straightforward use. Should you encounter any issues, consider the following:

- **Improper Fit:** If the mat does not sit flat or appears misaligned, remove it and re-position carefully, ensuring all fastener points are engaged. Verify that no obstructions are beneath the mat.
- **Slipping:** If the mat moves during use, ensure it is properly secured with its snap fasteners. Clean the underside of the mat and the vehicle's carpet to remove any debris that might prevent proper grip.
- **Stains:** Most stains can be removed with mild soap and water. For stubborn stains, a specialized automotive interior cleaner suitable for thermoplastic materials may be used, following the product's instructions.

## SPECIFICATIONS

---

<b>Brand</b>	Lund
<b>Model Number</b>	426512
<b>Material</b>	Heavy-duty Thermoplastic
<b>Color</b>	Tan
<b>Item Weight</b>	4.3 pounds
<b>Package Dimensions</b>	30.5 x 18.25 x 4.25 inches
<b>UPC</b>	612959265128

## WARRANTY INFORMATION

---

The Lund 426512 Catch-All Xtreme Tan 2nd Seat Floor Mat comes with a **Limited Lifetime Warranty**. This warranty covers defects in material and workmanship, specifically protecting against cracking, splitting, or breaking under normal use conditions. For detailed terms and conditions, please refer to the official warranty documentation provided with your purchase or contact Lund customer support.

## SUPPORT

---

For further assistance, questions, or warranty claims regarding your Lund Catch-All Xtreme floor mat, please contact Lund customer support. Refer to the packaging or the official Lund website for the most current contact information.