

Chief PDRUB

Chief PDRUB Universal Flat Panel Dual Swing Arm Wall Mount Instruction Manual

Model: PDRUB

1. PRODUCT OVERVIEW

The Chief PDRUB Universal Flat Panel Dual Swing Arm Wall Mount is designed to provide flexible and secure mounting for flat panel displays. Its robust construction allows for optimal viewing angles from various positions within a room. This mount features advanced mechanisms for smooth adjustments and integrated cable management for a clean installation.

Key Features:

- **Centris Technology Tilt Mechanism:** Allows for fingertip tilt adjustment for most flat panels.
- **Q-Latch Mounting System:** Securely attaches the flat panel to the mount with a latching flag.
- **CableTrac System:** Provides built-in cable management channels within the arms for a tidy setup.
- **Dual Swing Arm Design:** Offers extensive extension and swivel capabilities.
- **High Load Capacity:** Supports displays up to 200 lbs (90.72 kg).
- **Wide Compatibility:** Suitable for flat panel displays ranging from 42 to 63 inches.

2. IMPORTANT SAFETY INFORMATION

Read all instructions carefully before installation and use. Failure to follow these instructions may result in property damage, serious injury, or death.

- **Professional Installation Recommended:** Due to the complexity and weight involved, professional installation is highly recommended.
- **Wall Structure Verification:** Ensure the mounting surface can safely support the combined weight of the mount and the display. Consult a structural engineer if unsure.
- **Weight Capacity:** Do not exceed the maximum load capacity of 200 lbs (90.72 kg).
- **Proper Tools:** Use appropriate tools for installation as specified in the detailed installation guide (not included in this general manual).
- **Cable Management:** Route all cables carefully to prevent pinching or damage, which could lead to electrical

hazards or equipment failure.

- **Children and Pets:** Keep children and pets away from the installation area during setup.

3. PACKAGE CONTENTS

Verify that all components are present before beginning installation. If any parts are missing or damaged, contact Chief customer support.

- Chief PDRUB Wall Mount Assembly
- Mounting Hardware Kit (various screws, washers, spacers)
- Installation Template
- User Manual (this document)

4. SETUP AND INSTALLATION

This section provides a general overview of the installation process. Refer to the detailed installation guide provided with your product for specific step-by-step instructions and safety warnings.

4.1 Preparing the Wall Mount

The Chief PDRUB mount is designed for secure attachment to wall studs. Proper stud location and secure fastening are critical for stability.



Figure 1: The Chief PDRUB wall mount, showing its dual swing arm design.



Figure 2: Another view of the Chief PDRUB mount, illustrating the robust mounting plate.



Figure 3: Detailed view of the mount's articulation points and the Q-Latch system for display attachment.

4.2 Attaching to the Display

The Q-Latch mounting system simplifies attaching the display to the mount. Ensure the display's VESA mounting pattern aligns with the mount's plate. Use the appropriate screws and spacers from the hardware kit.

4.3 Cable Management

Utilize the integrated CableTrac system to route all display cables (power, HDMI, etc.) through the arms of the mount. This helps maintain a clean appearance and prevents cable damage.

5. OPERATING INSTRUCTIONS

The Chief PDRUB mount offers various adjustment capabilities for optimal viewing.

5.1 Adjusting Position

- **Extension:** Gently pull or push the display to extend or retract the arm. The mount offers up to 37 inches (940 mm) of extension.
- **Swivel:** Rotate the display left or right up to 90 degrees in either direction to achieve the desired viewing angle.
- **Lateral Shift:** The mount allows for up to 9 inches (229 mm) of lateral shift for fine-tuning horizontal positioning.



Figure 4: Display mounted flush against the wall, showcasing minimal depth.

5.2 Tilt and Roll Adjustments

The Centris Technology tilt mechanism allows for easy tilt and roll adjustments:

- **Tilt:** Adjust the vertical angle of the display from $+5^{\circ}$ to -17° for glare reduction and optimal viewing height.
- **Roll:** Fine-tune the horizontal level of the display with a $\pm 2.5^{\circ}$ roll adjustment.



Figure 5: Display extended and angled, demonstrating the mount's flexibility.



Figure 6: Display extended and tilted downwards, illustrating tilt adjustment.

6. MAINTENANCE

Regular maintenance ensures the longevity and safe operation of your Chief PDRUB wall mount.

- **Cleaning:** Wipe the mount with a soft, dry cloth. Avoid abrasive cleaners or solvents.
- **Periodic Inspection:** Annually inspect all mounting hardware and connections to ensure they are secure. Tighten any loose screws.
- **Lubrication:** The moving parts of the mount are designed for smooth operation and generally do not require lubrication. If movement becomes stiff, consult Chief customer support.

7. TROUBLESHOOTING

If you encounter issues with your Chief PDRUB wall mount, refer to the following common solutions:

- **Mount feels loose or unstable:**

- Verify all wall mounting bolts are securely tightened into the wall studs.
- Ensure the display is properly seated and latched onto the mount's plate.
- Confirm the combined weight of the display and mount does not exceed the maximum load capacity.

- **Difficulty adjusting tilt or swivel:**

- Check for any obstructions preventing movement.
- Ensure no cables are pinched or interfering with the articulation points.
- The Centris Technology is designed for fingertip adjustment; excessive force should not be required. If persistent, contact support.

- **Cables are visible or messy:**

- Re-route cables through the CableTrac system channels within the mount arms.
- Use cable ties or clips (not included) to secure loose cables along the mount or behind the display.

For issues not covered here, please contact Chief customer support.

8. SPECIFICATIONS

Feature	Specification
Model Number	PDRUB
Mounting Type	Wall Mount
Movement Type	Swivel, Tilt
Maximum Load Capacity	200.00 lb (90.72 kg)
Minimum Supported Screen Size	42 Inches
Maximum Supported Screen Size	63 Inches
Depth from Wall	3.4 inches (86 mm)
Extension	37 inches (940 mm)
Tilt Range	+5° to -17°
Roll Adjustment	±2.5°
Swivel	Up to 90° left/right
Lateral Shift	Up to 9 inches (229 mm)
Mounts on Studs	16 inches channel size width each arm
Item Weight	65 Pounds (29.48 kg)
Compatible Devices	Television

9. WARRANTY INFORMATION

The Chief PDRUB Wall Mount comes with a **Year** warranty. For specific terms and conditions, please refer to the warranty documentation included with your purchase or visit the manufacturer's website.

10. CUSTOMER SUPPORT

For technical assistance, missing parts, or warranty claims, please contact Chief customer support.

Manufacturer Website: chiefmfg.com

Please have your product model number (PDRUB) and purchase information ready when contacting support.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question