

Wix 33244

WIX 33244 Fuel Pump Filter Instruction Manual

Model: 33244

1. PRODUCT OVERVIEW

The WIX 33244 Fuel Pump Filter is designed to provide superior fuel cleansing performance for your vehicle's fuel system. This spin-on filter features built-in gaskets for a secure and reliable seal, simplifying the installation process and reducing the risk of mis-installation. Its robust construction ensures high durability and reliability, contributing to the longevity and efficient operation of your engine.

Key Features:

- **Built-in gaskets:** Ensures a proper seal and simplifies installation.
- **Unmatched fuel cleansing performance:** Effectively removes contaminants from fuel.
- **Quick, easy filter replacement:** Designed for straightforward servicing.
- **Highly durable and reliable:** Constructed for long-lasting performance.
- **Reduces mis-installation of gaskets:** Integrated design minimizes errors during setup.

2. SAFETY INFORMATION

Always prioritize safety when working with fuel systems. Fuel is highly flammable. Ensure you are working in a well-ventilated area, away from open flames or sparks. Wear appropriate personal protective equipment, including safety glasses and gloves. Disconnect the vehicle's battery before beginning any work on the fuel system to prevent accidental ignition or electrical hazards. Refer to your vehicle's service manual for specific safety precautions and procedures.

3. INSTALLATION (SETUP)

Proper installation is crucial for the effective operation of the WIX 33244 Fuel Pump Filter. Follow these general steps, but always consult your vehicle's specific service manual for detailed instructions.

1. **Prepare the Vehicle:** Park the vehicle on a level surface and engage the parking brake. Allow the engine to cool down. Disconnect the negative terminal of the vehicle's battery.

2. **Relieve Fuel System Pressure:** Consult your vehicle's service manual for the correct procedure to relieve fuel system pressure. This is a critical safety step.
3. **Locate the Old Filter:** Identify the existing fuel pump filter. It is typically located along the fuel line, often near the fuel tank or engine compartment.
4. **Remove the Old Filter:** Place a drain pan beneath the filter to catch any residual fuel. Carefully disconnect the fuel lines from the old filter. Be prepared for some fuel spillage. Remove the old filter from its mounting bracket.
5. **Inspect and Clean:** Inspect the fuel lines and mounting area for any damage or debris. Clean the area as necessary.
6. **Install the New Filter:** Orient the new WIX 33244 filter correctly, noting any flow direction arrows. The built-in gaskets simplify this step. Attach the fuel lines securely to the new filter. Ensure all connections are tight to prevent leaks.
7. **Secure the Filter:** Mount the new filter firmly in its bracket.
8. **Reconnect and Test:** Reconnect the negative battery terminal. Turn the ignition key to the 'ON' position (without starting the engine) for a few seconds to allow the fuel pump to prime the system. Check for any fuel leaks around the new filter. Start the engine and re-check for leaks.




Image 1: WIX 33244 Fuel Pump Filter. This image shows the cylindrical filter with the WIX logo and model number clearly visible, along with the spin-on base and a separate gasket.

4. OPERATING PRINCIPLES

The WIX 33244 Fuel Pump Filter operates as a critical component within your vehicle's fuel delivery system. Its primary function is to remove contaminants such as dirt, rust, and other particles from the fuel before it reaches the fuel pump and engine. By filtering the fuel, it protects sensitive fuel system components from damage and ensures a clean, consistent fuel supply for optimal engine performance and efficiency. The spin-on design allows for a sealed filtration process, preventing unfiltered fuel from bypassing the filter media.

5. MAINTENANCE

Regular maintenance, specifically timely replacement, is essential for the continued effectiveness of your WIX 33244 Fuel Pump Filter. A clogged or dirty fuel filter can restrict fuel flow, leading to reduced engine performance, poor fuel economy, and potential damage to the fuel pump or injectors.

Replacement Schedule:

- Consult your vehicle manufacturer's recommendations for the specific fuel filter replacement interval. This can vary significantly based on vehicle type, driving conditions, and fuel quality.
- As a general guideline, fuel filters are often recommended for replacement every 15,000 to 30,000 miles, or every 1 to 2 years.
- If you frequently use low-quality fuel or drive in dusty environments, more frequent replacement may be necessary.

Replacement Procedure:

Follow the installation steps outlined in Section 3, treating the removal of the old filter and installation of the new filter as the replacement procedure. Always ensure safety precautions are followed.

6. TROUBLESHOOTING

If you experience issues with your vehicle's fuel system, a clogged or faulty fuel filter could be a contributing factor. Here are some common symptoms and troubleshooting steps:

Common Symptoms of a Clogged Fuel Filter:

- **Engine Misfires or Stalls:** Insufficient fuel delivery can cause the engine to run rough, misfire, or stall, especially under acceleration.
- **Reduced Engine Performance:** A restricted fuel flow can lead to a noticeable decrease in power and acceleration.
- **Difficulty Starting:** The engine may crank for an extended period before starting, or may not start at all, due to inadequate fuel pressure.
- **Poor Fuel Economy:** While less common, a severely clogged filter can sometimes cause the engine to work harder, leading to decreased fuel efficiency.
- **Check Engine Light:** In some modern vehicles, a severely restricted fuel filter can trigger a 'Check Engine' light.

Troubleshooting Steps:

1. **Verify Symptoms:** Confirm that the symptoms align with those of a fuel delivery issue.
2. **Check Fuel Pressure:** If you have the necessary tools and expertise, check the fuel pressure at the fuel rail. Low fuel pressure can indicate a clogged filter or a failing fuel pump.
3. **Inspect Filter:** While difficult to visually inspect the internal condition, if the filter is old and the symptoms are present, it is a strong candidate for replacement.
4. **Replace Filter:** If the filter is due for replacement or suspected to be clogged, replace it following the instructions in Section 3.
5. **Consult a Professional:** If symptoms persist after replacing the fuel filter, or if you are uncomfortable performing these checks, consult a qualified automotive technician.

7. SPECIFICATIONS

The following table details the key specifications for the WIX 33244 Fuel Pump Filter:

Specification	Detail
Brand	Wix
Model	33244
Item Weight	1.1 Pounds (approx. 0.5 kg)
Product Dimensions	4.29 x 4.41 x 6.57 inches (approx. 10.9 x 11.2 x 16.7 cm)
Outer Material	Metal
Style	Spin-On
OEM Part Number	33244
UPC	765809332447
Vehicle Service Type	Pump

8. WARRANTY AND SUPPORT

For information regarding warranty coverage, claims, or technical support for your WIX 33244 Fuel Pump Filter, please contact Wix Filters directly through their official website or customer service channels. Keep your purchase receipt and product information handy when contacting support.

© 2025 Wix Filters. All rights reserved.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question