

[Manuals.plus](#) /

› [Permatex](#) /

› Permatex 80062 High Tack Gasket Sealant Instruction Manual

Permatex 80062

Permatex 80062 High Tack Gasket Sealant Instruction Manual

Model: 80062

Brand: Permatex

PRODUCT OVERVIEW

The Permatex 80062 High Tack Gasket Sealant is a reliable general adhesive designed for sealing gaskets. It is formulated to be fast-drying and sensor-safe, providing a secure and durable seal for various applications.

Image: A can of Permatex High Tack Gasket Sealant, model #80062. The label clearly shows the brand name "Permatex", product name "HIGH TACK Gasket Sealant", and warnings regarding flammability and irritation. The can is silver with a white label, indicating a net content of 4 fl. oz. / 118 mL.

SAFETY INFORMATION

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE AND RESPIRATORY IRRITANT.

Read carefully other cautions on the back panel of the product container before use. Ensure adequate ventilation during application. Avoid contact with skin, eyes, and clothing. In case of contact, rinse immediately with plenty of water. If swallowed, do not induce vomiting; seek immediate medical attention. Keep out of reach of children.

SETUP AND PREPARATION

- Surface Cleaning:** Ensure all surfaces to be sealed are clean, dry, and free of oil, grease, old gasket material, and other contaminants. Use a suitable solvent if necessary, and allow to dry completely.
- Ventilation:** Work in a well-ventilated area to minimize exposure to vapors.
- Personal Protective Equipment:** Wear appropriate gloves and eye protection to prevent skin and eye contact.

OPERATING INSTRUCTIONS (APPLICATION)

Permatex High Tack Gasket Sealant is designed to hold gaskets in place during assembly and improve sealing. It is a quick-drying and very tacky formula.

- Shake Well:** Shake the can thoroughly before use to ensure proper mixing of the sealant.
- Apply to Gasket:** Apply a thin, even coat of sealant to one or both sides of the gasket.
- Position Gasket:** Carefully position the gasket onto the component. The high tack formula will help hold the gasket in place during assembly.
- Assemble Components:** Assemble the components immediately after positioning the gasket.
- Curing:** The sealant is fast-drying. Allow sufficient time for the sealant to set before subjecting the assembly to pressure or fluids, as specified by the vehicle or equipment manufacturer.

MAINTENANCE AND CLEANUP

- Excess Sealant:** Wipe away any excess sealant immediately after assembly using a suitable solvent or rag.
- Tool Cleaning:** Clean tools and application brushes with a solvent such as mineral spirits or lacquer thinner before the sealant dries.
- Storage:** Store the product in a cool, dry place, away from direct sunlight and sources of ignition. Ensure the lid is tightly sealed to prevent drying.

TROUBLESHOOTING

- Poor Adhesion:** If the sealant does not adhere properly, ensure surfaces were thoroughly cleaned and dry before application. Surface contamination (oil, grease, old material) is a common cause.

- **Incomplete Seal:** An incomplete seal may result from insufficient application, improper surface preparation, or incorrect assembly. Re-evaluate the application process and ensure proper torque specifications are met for fasteners.
- **Slow Drying:** Ensure adequate ventilation. High humidity or low temperatures can extend drying times.

SPECIFICATIONS

Attribute	Value
Brand	Permatex
Item Form	Liquid
Color	Black
Item Package Quantity	1
Package Information	Bottle
Item Volume	4 Fluid Ounces (118 mL)
Viscosity	Low to Moderate
Water Resistance Level	Water Resistant
Unit Count	1.0 Count
UPC	686226800626
Manufacturer	Permatex
Item Weight	5 ounces
Model Number	80062

WARRANTY AND SUPPORT

For specific warranty information regarding the Permatex 80062 High Tack Gasket Sealant, please refer to the manufacturer's official website or contact Permatex customer support directly.

Permatex Official Website: www.permatex.com

For further assistance or technical inquiries, please contact Permatex customer service.

© 2025 Permatex. All rights reserved.

This manual is for informational purposes only. Always refer to the product packaging for the most current safety and application instructions.