

[Manuals.plus](#) /

> [SONAX](#) /

> SONAX Xtreme Polish+Wax 3 Hybrid NPT 250 ml Instruction Manual

**SONAX 02021000**

# SONAX Xtreme Polish+Wax 3 Hybrid NPT 250 ml Instruction Manual

Brand: SONAX

## PRODUCT OVERVIEW

The SONAX Xtreme Polish+Wax 3 Hybrid NPT is a high-performance car polish and wax designed to restore and protect vehicle paintwork. This product effectively removes light scratches, rust spots, swirls, and holograms, leaving a brilliant, refreshed finish. It can be applied either by hand or with a polishing machine, making it versatile for various users.

Key features include:

- Removes light scratches, rust spots, swirls, and holograms from car paint.
- Suitable for both manual and machine application.
- Restores dull paint to a brilliant shine.



Image: SONAX Xtreme Polish+Wax 3 Hybrid NPT 250 ml product bottle.

## SETUP AND PREPARATION

Proper preparation is crucial for achieving optimal results with SONAX Xtreme Polish+Wax 3 Hybrid NPT. Follow these steps before application:

1. **Clean the Vehicle:** Thoroughly wash and dry the vehicle to remove all dirt, dust, and contaminants. Use a high-

quality car shampoo and rinse thoroughly.

2. **Inspect Paintwork:** Examine the paint surface for any deep scratches or imperfections that may require professional attention. This product is designed for light scratches and swirls.
3. **Work in a Shaded Area:** Always apply the product in a cool, shaded environment. Avoid direct sunlight or hot surfaces, as this can cause the product to dry too quickly and become difficult to remove.
4. **Shake Well:** Before use, shake the product bottle vigorously to ensure the ingredients are well mixed.
5. **Gather Supplies:** Have clean microfiber cloths, applicator pads (foam or microfiber), and a polishing machine (if using) ready.

## OPERATING INSTRUCTIONS

---

The SONAX Xtreme Polish+Wax 3 Hybrid NPT can be applied manually or with a polishing machine. Choose the method that best suits your needs and experience level.

### Manual Application

1. Apply a small amount of polish onto an applicator pad.
2. Work on a small section of the paintwork at a time (e.g., 50x50 cm).
3. Apply the polish evenly with moderate pressure in a circular or cross-hatch motion until a slight haze appears.
4. Allow the polish to dry for approximately 30 seconds to 1 minute until a dry film forms.
5. Using a clean, soft microfiber cloth, wipe off the residue with light pressure. Turn the cloth frequently to use a clean side.
6. Repeat the process for all sections of the vehicle.

### Machine Application

1. Attach a suitable polishing pad (e.g., medium-cut foam pad) to your polishing machine.
2. Apply a few drops of polish directly onto the pad.
3. Place the pad flat on the paint surface before starting the machine to prevent sling.
4. Work on a small section at a time, using a low to medium speed setting. Move the machine slowly and evenly in a cross-hatch pattern, applying light to moderate pressure.
5. Continue polishing until the desired correction is achieved and the polish begins to clear.
6. Wipe off any remaining residue with a clean, soft microfiber cloth.
7. Repeat the process for all sections of the vehicle.

  
Video: A 360-degree view of the SONAX Xtreme Polish+Wax 3 Hybrid NPT product bottle, demonstrating its packaging and design.

## MAINTENANCE

---

To maintain the brilliant finish achieved with SONAX Xtreme Polish+Wax 3 Hybrid NPT, follow these recommendations:

- **Regular Washing:** Wash your vehicle regularly using a pH-neutral car shampoo to preserve the wax layer.
- **Avoid Abrasives:** Do not use abrasive cleaners or harsh brushes that can damage the polished surface.
- **Reapplication:** Depending on environmental conditions and washing frequency, reapply the polish and wax every few months to maintain optimal protection and shine.
- **Product Storage:** Store the product in a cool, dry place, away from direct sunlight and extreme temperatures. Ensure the cap is tightly sealed after each use. Keep out of reach of children.

## TROUBLESHOOTING

Problem	Possible Cause	Solution
Streaks or uneven finish	Applied too much product; product dried too quickly; insufficient buffing.	Apply a thinner layer of product. Work in smaller sections. Ensure application in a cool, shaded area. Buff thoroughly with a clean microfiber cloth.
Product difficult to remove	Product dried on the surface for too long; applied in direct sunlight or on a hot surface.	Work in a cool, shaded area. Do not let the product dry completely. If dried, reapply a small amount of polish to reactivate it, then immediately wipe off.
Holograms or swirl marks visible after polishing	Improper application technique; dirty applicator pad/microfiber cloth; product not fully broken down.	Ensure applicator pads and cloths are clean. Use consistent pressure and motion. For machine application, ensure proper pad selection and speed. This product is designed to remove holograms, so re-evaluate technique.

## SPECIFICATIONS

Attribute	Value
Brand	SONAX
Model Number	02021000
Volume	250 ml
Item Dimensions (LxWxH)	37 x 69 x 170 mm
Material	Aluminum Oxide
Grain Material	Wax
Grain Type	Very Fine
Grain Number	800
Compatible Material	Aluminum
UPC	642310273738

## WARRANTY AND SUPPORT

Information regarding product warranty and customer support was not available in the provided product data. For specific warranty details or technical assistance, please refer to the product packaging or contact SONAX customer service directly through their official website or contact channels.

You can visit the official SONAX store for more information: [SONAX Store](#)



