



Manuals.plus /

- › Ushio /
- › Ushio BC8852 CFL Bulb Instruction Manual

## Ushio BC8852

# Ushio BC8852 CFL Bulb Instruction Manual

Model: BC8852 | Part Number: 3000056

## INTRODUCTION

---

This manual provides essential information for the safe and effective use of your Ushio BC8852 Compact Fluorescent Lamp (CFL). Please read these instructions carefully before installation and operation. Retain this manual for future reference.



Image: Ushio BC8852 CFL Bulb. This image displays the compact fluorescent lamp, highlighting its spiral design and G24q-2 base.

## SAFETY INFORMATION

---

Always follow basic safety precautions when using electrical products to reduce the risk of fire, electric shock, and personal injury.

- Ensure power is turned off at the circuit breaker before installation, removal, or inspection.
- Do not use in fully enclosed fixtures unless specified for CFL use, as this can shorten bulb life.
- Avoid touching the bulb with bare hands during operation or immediately after turning off, as it may be hot.
- Do not use with standard dimmer switches unless the bulb and fixture are specifically rated for dimmable CFLs. This bulb is dimmable.
- Dispose of broken bulbs according to local regulations, as they contain small amounts of mercury.

## SETUP AND INSTALLATION

---



Problem	Possible Cause	Solution
Bulb does not light up.	No power to the fixture. Bulb not properly seated. Bulb has reached end of life. Faulty fixture or switch.	Check circuit breaker and wall switch. Ensure bulb is firmly pushed into the socket. Replace the bulb. Consult a qualified electrician.
Bulb flickers.	Incompatible dimmer switch. Loose connection. Bulb nearing end of life.	Ensure dimmer is rated for dimmable CFLs. Turn off power, re-seat the bulb. Replace the bulb.
Bulb is dim or takes long to brighten.	Normal warm-up period for CFLs. Cold ambient temperature.	Allow a few minutes for full brightness. This is expected behavior in colder conditions.

## SPECIFICATIONS

Feature	Detail
Model Number	BC8852
Part Number	3000056
Wattage	18 Watts
Base Type	G24q-2 (4-Pin)
Color Temperature	2700 Kelvin (Warm White)
Color Rendering Index (CRI)	82
Initial Lumens	1200 Lumens
Average Lifetime	10,000 Hours
Voltage	100 Volts
Special Feature	Dimmable
Dimensions (L x W x H)	1.5 x 1.5 x 6 inches
Item Weight	2.11 ounces
Material	Copper

## WARRANTY AND SUPPORT

The manufacturer's warranty information for the Ushio BC8852 CFL Bulb is indicated as "Not applicable." For any product inquiries or support, please refer to the retailer or the original point of purchase.

