

[Manuals.plus](#) /

› [Rust-Oleum](#) /

› Rust-Oleum Stops Rust Bright Coat Metallic Spray Paint, Chrome - Instruction Manual

Rust-Oleum 7718830

Rust-Oleum Stops Rust Bright Coat Metallic Spray Paint, Chrome - Instruction Manual

INTRODUCTION

The Rust-Oleum Stops Rust Bright Coat Metallic Finish Spray in Chrome is designed to create a decorative, shiny metallic look on various interior surfaces. This fast-drying acrylic lacquer is suitable for use on metal, wood, concrete, and masonry. It features a comfort tip for ease of use during continuous spraying and an any-angle spray feature, allowing application in any direction, including upside-down.

Key product attributes include excellent chip resistance and color retention, ensuring your projects maintain their appearance over time. The finish will not fade or dull when used indoors, providing a classic and elegant look ideal for accent pieces.



Image: Rust-Oleum Bright Coat Metallic Spray Paint can in Chrome.

SAFETY INFORMATION

WARNING: This product is extremely flammable. Read all warnings on the can label before use. Failure to follow instructions may result in serious injury or property damage.

- Use in a well-ventilated area. Ensure adequate airflow to prevent vapor accumulation.
- Wear appropriate personal protective equipment, including safety glasses, gloves, and a respirator if ventilation is insufficient.
- Keep away from heat, sparks, open flames, and other ignition sources. Do not smoke while using.
- Keep out of reach of children and pets.
- Avoid prolonged breathing of vapors. If experiencing dizziness or headache, move to fresh air immediately.
- In case of eye contact, flush immediately with plenty of water for at least 15 minutes and seek medical attention.
- Dispose of empty cans and unused product according to local regulations. Do not puncture or incinerate cans.

PREPARATION

Surface Preparation

Proper surface preparation is crucial for optimal adhesion and finish quality. Ensure the surface is clean, dry, and free of loose rust, dirt, grease, oil, or old paint. For best results:

- **Cleaning:** Wash the surface with soap and water, then rinse thoroughly and allow to dry completely.
- **Sanding:** Lightly sand glossy surfaces or areas with minor imperfections to create a profile for better paint adhesion. For rusted metal, remove all loose rust with a wire brush or sandpaper.
- **Priming:** While not always required, applying a suitable primer (e.g., Rust-Oleum 2X Flat White for plastics/ceramics) can enhance adhesion and coverage, especially on challenging surfaces or when a uniform base color is desired. Allow primer to dry according to its instructions before applying metallic spray paint.

ADHERES TO



Image: Rust-Oleum Bright Coat Metallic Spray Paint adheres to wood and metal.

Can Preparation

Before spraying, shake the can vigorously for one minute after the mixing ball begins to rattle. Continue to shake occasionally during use.

CAP MATCHES COLOR

spray with confidence



Image: The can cap matches the paint color for confidence in selection.

APPLICATION (OPERATING INSTRUCTIONS)

Apply paint in a well-ventilated area when temperatures are between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying.

1. **Hold Can Correctly:** Hold the can upright approximately 10-16 inches from the surface.
2. **Apply Light Coats:** Press the spray button firmly and apply several thin, even coats with a steady, back-and-forth motion. Overlap each stroke slightly. Avoid applying a single heavy coat, as this can lead to drips and an uneven finish.
3. **Any-Angle Spray:** The comfort tip and any-angle spray feature allow for easy application, even when spraying upside-down or in hard-to-reach areas.
4. **Recoat Time:** Allow approximately 20 minutes between coats for optimal adhesion and finish.



Image: Demonstrating proper spray technique onto a vase.

spray at any angle with **COMFORT TIP**



Image: The comfort tip allows for spraying at any angle.

Video: Official Rust-Oleum demonstration of Stops Rust Bright Coat Spray application.

DRYING AND CURING

Drying times can vary based on temperature, humidity, and film thickness.

- **Dry to Touch:** Approximately 60 minutes.
- **Dry to Handle:** Approximately 60 minutes.
- **Full Cure:** For maximum durability and to prevent damage, allow the paint to fully cure for 3-4 days before heavy handling or exposure to moisture.
- **Top Coat:** For items that will be handled frequently or exposed to wear, consider applying a clear protective top coat after the metallic finish has dried for at least 24 hours.

MAINTENANCE

Cleaning the Nozzle

To prevent clogging and ensure future use, clean the spray nozzle immediately after each use:

1. Invert the can (turn it upside-down).
2. Press the spray button for 5 seconds or until only clear propellant comes out.
3. Wipe the nozzle opening clean with a cloth.

Storage

Store the can in a cool, dry, well-ventilated area away from direct sunlight, heat sources, and open flames. Do not store at temperatures above 120°F (49°C).

TROUBLESHOOTING

Problem	Possible Cause	Solution
Drips or Runs	Applying paint too heavily or holding the can too close to the surface.	Apply several thin, even coats instead of one thick coat. If drips occur, allow the paint to fully cure (3-4 days), then lightly sand the affected area and reapply thin coats.
Uneven Coverage	Insufficient shaking of the can, inconsistent spray distance, or improper surface preparation.	Shake the can vigorously for one minute before use and occasionally during application. Maintain a consistent spray distance (10-16 inches). Ensure the surface is properly cleaned and prepared.
Nozzle Clogging	Paint drying in the nozzle.	Clean the nozzle immediately after each use by inverting the can and spraying until clear propellant emerges. If clogged, remove the nozzle and soak it in mineral spirits or paint thinner, then rinse and reattach.

SPECIFICATIONS

Feature	Detail
Brand	Rust-Oleum
Model Number	7718830
Color	Chrome
Finish Type	Metallic
Size	11 Ounce (Pack of 1)
Item Volume	11 fluid ounces
Special Features	Any Angle Feature, Chip Resistant, Fast-Drying, Rust Resistant
Paint Type	Acrylic, Spray
Specific Uses For Product	Interior
Surface Recommendation	Metal, Wood, Concrete, Masonry
Indoor Outdoor Usage	Indoor
Dry Time (to touch/handle)	1 hour

Feature	Detail
Coverage	6 sq ft
Item Weight	14.4 ounces
UPC	020066771881

WARRANTY AND SUPPORT

Warranty Information

This Rust-Oleum product comes with a **1-year manufacturer's warranty**. Please retain your proof of purchase for any warranty claims.

Customer Support

For further assistance, technical advice, or to report any issues with the product, please contact Rust-Oleum customer service directly. Refer to the contact information provided on the product label or visit the official Rust-Oleum website for support resources.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question