

COMETIC C7269

COMETIC C7269 Hi-Performance Off-Road Gasket/Seal Instruction Manual

Model: C7269

1. INTRODUCTION

1.1 Product Overview

The COMETIC C7269 Gasket/Seal set is engineered for high-performance off-road applications and serves as an original equipment (OE) replacement. Manufactured in the U.S.A., this kit provides the necessary gaskets and seals for one complete application, ensuring a precise fit and reliable sealing for your engine's top end.


1.2 Intended Use

This gasket set is designed for use in specific high-performance off-road engines, primarily for top-end rebuilds or maintenance. It includes components such as base gaskets, head gaskets, cylinder O-rings, and other specific O-rings or seals required for the top end of the engine.

2. PACKAGE CONTENTS

Carefully unpack the box and verify that all components are present and undamaged.

- Complete gasket set for top end (e.g., for KX250 applications)



This image displays the various gaskets and seals included in the COMETIC C7269 kit, designed for a complete top-end engine application.

3. INSTALLATION INSTRUCTIONS

Proper installation is crucial for the performance and longevity of your COMETIC C7269 gasket set. It is recommended that installation be performed by a qualified technician.

3.1 Required Tools and Materials

- Torque wrench
- Socket set
- Gasket scraper or razor blade
- Cleaning solvent (e.g., brake cleaner, acetone)
- Lint-free cloths
- Manufacturer's service manual for specific torque specifications and procedures

3.2 Preparation

1. Ensure the engine is cool and disconnected from power sources (if applicable).
2. Drain any fluids that may interfere with the installation (e.g., coolant, oil).
3. Carefully disassemble the engine components to access the old gaskets. Refer to your vehicle's service manual for detailed disassembly steps.
4. Thoroughly clean all mating surfaces. Remove all traces of old gasket material, carbon deposits, and oil

residue. Use a gasket scraper and cleaning solvent. Ensure surfaces are smooth and free of nicks or scratches.

5. Inspect all engine components for wear or damage. Replace any worn parts before installing new gaskets.

3.3 Gasket Installation

1. Identify the correct gasket for each mating surface from the COMETIC C7269 set.
2. Place the new gaskets onto the clean mating surfaces. Ensure correct orientation and alignment with bolt holes and passages.
3. Reassemble engine components according to the manufacturer's service manual.
4. Apply thread locker to bolts as specified by the manufacturer.
5. Tighten all fasteners to the specified torque values in the correct sequence. Use a torque wrench for accuracy. Overtightening or undertightening can lead to gasket failure.

3.4 Post-Installation

1. Refill any drained fluids.
2. Perform a leak check after initial startup. Monitor for any signs of fluid leaks or unusual engine operation.
3. Follow any break-in procedures recommended by the engine manufacturer.

4. OPERATING PRINCIPLES

Gaskets are critical components designed to seal the interface between two mating surfaces, preventing leakage of fluids or gases and maintaining proper compression. The COMETIC C7269 gaskets are manufactured to withstand the high temperatures, pressures, and dynamic forces present in off-road engine environments.

Proper installation ensures that the gasket material compresses evenly, creating a tight seal. Incorrect installation or damaged gaskets can lead to:

- Fluid leaks (oil, coolant)
- Loss of engine compression
- Reduced engine performance
- Potential engine damage

5. MAINTENANCE

While gaskets themselves do not typically require routine maintenance, their performance is directly linked to the overall health of the engine.

- **Regular Inspection:** Periodically inspect the areas where gaskets are installed for any signs of leaks (e.g., oil stains, coolant drips).
- **Fluid Levels:** Maintain correct engine fluid levels (oil, coolant) as per your vehicle's service manual. Low fluid levels can indicate a leak.
- **Engine Temperature:** Monitor engine temperature. Overheating can compromise gasket integrity.
- **Replacement:** Gaskets are generally designed for single use. If engine components are disassembled, it is highly recommended to replace all affected gaskets with new ones, such as the COMETIC C7269 set, to ensure a reliable seal.

6. TROUBLESHOOTING COMMON ISSUES

Problem	Possible Cause	Solution
Fluid Leakage (Oil/Coolant)	Improper gasket installation; Damaged gasket; Uneven mating surfaces; Incorrect torque on fasteners.	Re-check torque specifications. If leak persists, disassemble, inspect gaskets and mating surfaces for damage, clean thoroughly, and reinstall with new gaskets.
Loss of Engine Compression	Head gasket failure; Improper head gasket installation.	Perform a compression test to confirm. If head gasket is suspected, disassemble and replace with a new COMETIC C7269 head gasket, ensuring proper surface preparation and torque.
Engine Overheating	Coolant leak from gasket; Air trapped in cooling system due to gasket issue.	Check for external coolant leaks. If none, internal head gasket failure might be allowing combustion gases into the cooling system. Replace head gasket.

7. PRODUCT SPECIFICATIONS

Brand	COMETIC
Model	C7269
Item Weight	1.92 ounces
Product Dimensions	7 x 6 x 0.3 inches
Manufacturer Part Number	C7269
OEM Part Number	C7269
Application	Hi-Performance Off-Road (Top End Gasket Set)
Origin	Made in the U.S.A.

8. WARRANTY AND SUPPORT

For specific warranty information regarding your COMETIC C7269 gasket set, please refer to the official COMETIC website or contact your authorized dealer. For technical assistance or support, please reach out to COMETIC customer service.

Note: Improper installation or use outside of intended application may void warranty.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question