

## GE UNFCTBL

# GE Single-Handle Water Filtration Faucet

Model: UNFCTBL | OEM Part #: WB01X10132

## 1. INTRODUCTION

This instruction manual provides essential information for the proper installation, operation, and maintenance of your GE Single-Handle Water Filtration Faucet. This faucet is designed to dispense filtered water from a compatible GE under-sink water filtration system. Please read this manual thoroughly before installation and retain it for future reference.

## 2. SAFETY INFORMATION

Observe all local plumbing and building codes. If you are unsure about any part of the installation, consult a qualified plumber. Always turn off the main water supply before beginning any plumbing work. Wear appropriate personal protective equipment, such as safety glasses, during installation.

## 3. PACKAGE CONTENTS

Verify that all components are present before beginning installation. The package should contain the following items:

- Single-Handle Water Filtration Faucet (Gooseneck Spout)
- Mounting Hardware (washers, nuts, compression fitting)
- Installation Instructions



Figure 3.1: Exploded view of the GE Single-Handle Water Filtration Faucet components, including the faucet body, handle, spout, mounting hardware, and connection fittings.

## 4. SETUP AND INSTALLATION

This faucet is designed for single-hole deck mount installation and is compatible with GE under-sink water filtration systems. The installation process is straightforward, but attention to detail is crucial for a leak-free setup.

1. **Prepare the Mounting Hole:** If a hole is not already present, drill a 1/2-inch diameter hole in your sink or

countertop at the desired location. Ensure the area is clean and free of debris.

2. **Mount the Faucet:** Insert the threaded stem of the faucet through the drilled hole. From underneath the sink, place the rubber washer, metal washer, and mounting nut onto the threaded stem. Tighten the mounting nut securely to prevent movement.
3. **Connect to Water Filtration System:** The faucet is designed to connect to your water filtration system's tubing. This faucet typically requires 3/8-inch tubing. If your filtration system uses 1/4-inch tubing, you will need a 3/8-inch O.D. x 1/4-inch Plastic FIP Quick Connect Adapter (not included) to ensure proper connection. Securely attach the tubing to the faucet's inlet using the provided compression fitting.
4. **Check for Leaks:** Once all connections are made, slowly turn on the main water supply and the water supply to your filtration system. Inspect all connections for any signs of leaks. Tighten connections as necessary.



## SECONDARY FAUCET

### Compatible with GE under sink systems

Figure 4.1: The GE Single-Handle Water Filtration Faucet installed on a kitchen sink, demonstrating its compact design and function for dispensing filtered water.

## 5. OPERATING INSTRUCTIONS

The GE Single-Handle Water Filtration Faucet features a simple lever operation for dispensing filtered water.

- To dispense water, lift the handle upwards.
- To stop the water flow, push the handle downwards.
- The spout can be rotated to position it conveniently over your sink or to move it out of the way when not in use.

## 6. MAINTENANCE

Regular maintenance ensures optimal performance and longevity of your faucet.

- **Cleaning:** Clean the faucet regularly with a soft cloth and mild soap. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the finish.
- **Leak Checks:** Periodically inspect all connections under the sink for any signs of leaks. Tighten fittings if necessary.
- **Filter Replacement:** Refer to your GE under-sink water filtration system's manual for instructions on filter replacement schedules and procedures. A clogged filter can reduce water flow from the faucet.

## 7. TROUBLESHOOTING

If you encounter issues with your faucet, refer to the following common problems and solutions:

| Problem                      | Possible Cause  | Solution  |
|------------------------------|---|---|
| Low Water Flow               | Clogged water filter; kinked tubing; partially closed shut-off valve. | Replace water filter; check and straighten tubing; ensure shut-off valve is fully open. |
| Water Leaks from Connections | Loose connections; damaged O-rings or washers.                        | Tighten connections; inspect and replace O-rings or washers if damaged.                 |
| Spout is Wobbly              | Mounting nut is loose.  | Tighten the mounting nut from underneath the sink.                                      |

## 8. SPECIFICATIONS

- **Model Number:** UNFCTBL
- **OEM Part Number:** WB01X10132
- **Product Dimensions:** 6 x 1.3 x 1.5 inches
- **Item Weight:** 9.2 ounces
- **Material:** Metal (likely Brass)
- **Finish:** Black (Sleek Chrome and Black Design)
- **Installation Method:** Single Hole Deck Mount
- **Number of Handles:** 1

- **Spout Height:** 6 Inches
- **Compatibility:** Designed for use with GE Water Filtration Systems

## 9. WARRANTY INFORMATION

---

This GE product is covered by a manufacturer's warranty. For specific details regarding warranty coverage, duration, and claims procedures, please refer to the warranty card included with your product or visit the official GE Appliances website. Proof of purchase may be required for warranty service.

## 10. CUSTOMER SUPPORT

---

For technical assistance, replacement parts, or further inquiries, please contact GE Appliances customer support:

- **Website:** Visit the official GE Appliances website for support resources and contact information.
- **Phone:** Refer to your product packaging or the GE Appliances website for the most current customer service phone numbers.