

[manuals.plus](#) /› [HMF](#) /› [HMF 303-02 Key Safe with Combination Lock User Manual](#)

HMF 303-02

HMF 303-02 Key Safe with Combination Lock User Manual

Model: 303-02



1. PRODUCT OVERVIEW

The HMF 303-02 Key Safe is designed for the secure storage of keys, such as car keys, house keys, or other small valuables. It features a robust construction and a personally adjustable combination lock for enhanced security. The safe can be securely mounted to a wall or other suitable surface using the provided hardware.

- **Secure Storage:** Ideal for car keys, house keys, and other small valuables.
- **Personal Combination Lock:** Set your own numerical code for access.
- **Wall Mountable:** Equipped with 4 pre-drilled holes for stable wall fixation.
- **Includes Mounting Hardware:** Screws and dowels are provided for installation.
- **Compact Dimensions:** Measures approximately 14.5 x 10 x 5.7 cm.



Figure 1: HMF 303-02 Key Safe with combination lock, designed for secure storage of keys and small items.

2. SETUP AND INSTALLATION

2.1 Setting Your Personal Combination

The key safe comes with a factory-set combination, usually "0-0-0". It is crucial to change this to a personal combination immediately after unpacking. Please follow these steps:

1. Open the safe using the current combination (factory default is "0-0-0").
2. Locate the reset lever or button inside the safe, usually on the back of the door or near the locking mechanism. This is often a small lever that needs to be moved from position A to B (or similar, depending on the specific design).
3. While the lever is in the reset position, set your desired new 3-digit combination by rotating the number dials. Choose a memorable but secure combination.
4. Return the reset lever to its original position.
5. Close the safe and scramble the dials to lock it. Test your new combination to ensure it works correctly before

securing any valuables.

Important: Make a note of your new combination and store it in a safe place, separate from the key safe. There is no master key or override for the combination lock.

2.2 Wall Mounting

The key safe is designed for stable wall mounting. Choose a discreet and secure location for installation.

1. Open the key safe.
2. Hold the safe against the desired mounting surface and mark the positions of the four pre-drilled mounting holes.
3. Drill pilot holes at the marked positions. Ensure the drill bit size is appropriate for the included dowels.
4. Insert the dowels into the drilled holes.
5. Align the key safe with the dowels and secure it firmly using the provided screws.



Figure 2: Interior view of the HMF 303-02 Key Safe, highlighting the mounting holes and internal mechanism.



Figure 3: The HMF 303-02 Key Safe shown attached to a car window, illustrating a potential temporary use case.

3. OPERATING INSTRUCTIONS

3.1 Opening the Key Safe

1. Rotate the number dials to align with your personal 3-digit combination.
2. Once the correct combination is set, the safe can be opened by pulling the front cover.

3.2 Closing and Locking the Key Safe

1. Place your items inside the safe.
2. Close the front cover firmly.
3. Scramble the number dials to a random sequence. This will lock the safe and prevent unauthorized access.

4. MAINTENANCE

To ensure the longevity and proper functioning of your HMF 303-02 Key Safe, consider the following maintenance tips:

- **Cleaning:** Wipe the exterior with a soft, damp cloth. Avoid abrasive cleaners or solvents that could damage the finish or internal mechanisms.
- **Lubrication:** Periodically, a small amount of graphite powder or a silicone-based lubricant can be applied to the combination dials and locking mechanism to ensure smooth operation. Avoid oil-based lubricants as they can attract dust and grime.
- **Environmental Conditions:** While robust, avoid prolonged exposure to extreme weather conditions (e.g., heavy rain, direct sunlight, freezing temperatures) if not permanently mounted in a sheltered outdoor location, as this can affect the materials over time.

5. TROUBLESHOOTING

5.1 Safe Will Not Open with Combination

- **Verify Combination:** Double-check that you are entering the correct 3-digit combination. Ensure each number is precisely aligned with the indicator mark.
- **Dial Alignment:** Sometimes, dials can be slightly misaligned. Gently wiggle each dial to ensure it's fully seated in its position for the correct number.
- **Reset Lever Position:** If you recently changed the combination, ensure the reset lever inside was fully returned to its original position after setting the new code. If it wasn't, the combination might not have been set correctly.
- **Forgotten Combination:** If the combination is forgotten, there is no master key or override. The safe will need to be opened by a professional locksmith, which may damage the unit. Always keep a record of your combination in a secure, separate location.

5.2 Dials are Stiff or Hard to Turn

- **Clean Dials:** Dust or grime can accumulate. Clean the dials and surrounding area with a soft, dry cloth.
- **Lubrication:** Apply a small amount of graphite powder or silicone spray lubricant to the dials. Do not use oil-based lubricants.

6. SPECIFICATIONS

Feature	Detail
Brand	HMF
Model Number	303-02
Color	Black
Dimensions (L x W x H)	14.5 x 10 x 5.7 cm
Weight	750 g
Material	Alloy Steel

Feature	Detail
Lock Type	Combination Lock (3-digit)
Mounting Type	Wall Mount
Included Components	Key Safe, Screws, Dowels

© 2023 HMF. All rights reserved.