

Ubbink 1061913

Ubbink FoliColl Pond Liner Sealant

INSTRUCTION MANUAL - MODEL 1061913

1. Introduction

The Ubbink FoliColl Pond Liner Sealant is specifically designed for repairing and sealing leaks in Ubbink AquaLiner PVC pond liners. This high-quality glue provides a durable and waterproof bond, ensuring the longevity and integrity of your pond system.

This manual provides essential information for the safe and effective use of the FoliColl sealant, including preparation, application, and maintenance guidelines.



Image 1: Ubbink FoliColl Pond Liner Sealant 250 ml bottle.

2. Safety Information

Always read and understand all safety warnings and instructions before using this product. Keep out of reach of children and pets.

- **Ventilation:** Use in a well-ventilated area to avoid inhalation of fumes.
- **Skin and Eye Contact:** Avoid direct contact with skin and eyes. Wear appropriate protective gloves and eye protection (safety glasses/goggles). In case of contact, rinse immediately with plenty of water and seek medical advice.
- **Ingestion:** Do not ingest. If swallowed, do not induce vomiting. Seek immediate medical attention.
- **Flammability:** Keep away from open flames, sparks, and other ignition sources.
- **Storage:** Store in a cool, dry place, away from direct sunlight and extreme temperatures. Keep container tightly closed when not in use.

3. Setup and Preparation

Proper preparation of the surfaces is crucial for effective adhesion and a lasting repair.

1. **Identify Leak:** Locate the exact area of the leak or damage on the PVC pond liner.
2. **Clean Surface:** Thoroughly clean the area to be repaired. Remove any dirt, algae, debris, or loose material. Use a mild detergent if necessary, then rinse completely.
3. **Dry Surface:** Ensure the repair area is completely dry before applying the sealant. Moisture will prevent proper bonding.
4. **Cut Patch (if needed):** If repairing a hole or tear, cut a patch from a compatible PVC pond liner. The patch should overlap the damaged area by at least 5 cm (2 inches) on all sides. Clean and dry the patch as well.

4. Operating (Application)

Follow these steps for optimal application of the Ubbink FoliColl sealant:

1. **Open Container:** Carefully open the 250 ml container of FoliColl sealant.
2. **Apply Sealant:** Apply a thin, even layer of FoliColl sealant to both the damaged area of the pond liner and the underside of the PVC patch (if using one). Ensure complete coverage of the bonding surfaces.
3. **Join Surfaces:** If using a patch, carefully align and press the patch firmly onto the damaged area. Smooth out any air bubbles by working from the center outwards. For simple seam sealing, press the liner edges together firmly.
4. **Apply Pressure:** Apply firm, even pressure to the bonded area for several minutes to ensure good contact and adhesion. A roller or flat object can be used.
5. **Curing Time:** Allow the sealant to cure completely. The initial bond will form quickly, but full strength and waterproofing are typically achieved after 24-48 hours, depending on temperature and humidity. Avoid disturbing the repaired area during this time.
6. **Water Test:** After the curing period, carefully test the repaired area for leaks before fully refilling the pond.



Image 2: Example of pond liner application, similar to sealant use.

5. Maintenance

Once applied and cured, the FoliColl sealant requires minimal maintenance. Periodically inspect your pond liner for any new signs of wear or damage, especially around previously repaired areas.

- **Storage:** Store any unused sealant in its original tightly sealed container in a cool, dry place, away from direct sunlight and freezing temperatures.
- **Shelf Life:** Refer to the product packaging for specific shelf life information.

6. Troubleshooting

If you encounter issues with the sealant, consider the following common problems and solutions:

- **Poor Adhesion:**

- Ensure surfaces were thoroughly cleaned and completely dry before application.
- Verify that sufficient pressure was applied during bonding.
- Check if the sealant has expired or was stored improperly.

- **Leak Persists After Repair:**

- The leak might be larger than the repaired area, or there could be another leak nearby. Re-inspect the liner.
- The sealant may not have fully cured. Allow more time, especially in cooler or humid conditions.
- Insufficient sealant applied or uneven application. Reapply if necessary, ensuring full coverage.

7. Specifications

Attribute	Detail
Product Name	Ubbink FoliColl Pond Liner Sealant

Model Number	1061913
Material	Glue (Paste)
Compatible Material	Polyvinyl Chloride (PVC) liners
Contents Volume	250 ml
Coverage	Approximately 10 m ²
Special Feature	Waterproof
Colour	White
Package Dimensions	1 x 1 x 1 cm
Item Weight	1 kg

8. Disposal



Dispose of unused product and empty containers according to local regulations. Do not dispose of in drains or waterways.


9. Warranty and Support

For information regarding product warranty or technical support, please refer to the official Ubbink website or contact Ubbink customer service directly. Contact details are typically available on the product packaging or the manufacturer's official website.

© 2024 Ubbink. All rights reserved.

Related Documents - 1061913

	<p><u>Ubbink XTRA Pond Pumps: Installation, Operation, and Maintenance Guide</u></p> <p>Comprehensive guide for Ubbink XTRA pond pumps (models 400, 600, 900, 1600, 2300, 3900), covering installation, safety, operation, maintenance, and disposal. Includes detailed specifications and multilingual safety information.</p>
	<p><u>Ubbink Elimax Pond Pumps - User Manual</u></p> <p>This document provides user instructions and safety information for Ubbink Elimax pond pumps, covering installation, operation, maintenance, and warranty.</p>
	<p><u>Ubbink FiltraPure Pond Filters: Models 2000, 4000, 7000 - Product Overview</u></p> <p>Comprehensive overview of Ubbink FiltraPure pond filter systems, including models 2000, 4000, and 7000. Features, connections, and essential safety guidelines for pond maintenance.</p>

	<p><u>Ubbink UB8 to UB37 Plain Tile Vent Conversion Fixing Instructions</u></p> <p>Step-by-step fixing instructions from Ubbink for converting the UB8 Plain Tile Vent to a UB37 Plain Tile Terminal, suitable for soil, vent, and mechanical extract systems.</p>
	<p><u>Rolux Vent System Condensate Trap Kit Installation and Maintenance Guide</u></p> <p>Detailed installation instructions and maintenance guide for the Ubbink Rolux Vent System Condensate Trap Kit, compatible with male and female appliance tops. Includes parts list, assembly steps, cleaning procedures, and general requirements.</p>
	<p><u>UBBINK 300x300 H126 cm Wooden Swimming Pool Assembly and Safety Manual</u></p> <p>This manual provides comprehensive instructions for assembling, safely operating, and maintaining your UBBINK 300x300 H126 cm wooden swimming pool. Learn about installation, safety guidelines, water care, and warranty details.</p>