

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [Command](#) /

› [3M 17068 Wire Hooks With Strips \(2 Packs of 2 Hooks\)](#)

Command 17068

Instruction Manual

COMMAND 3M 17068 WIRE HOOKS WITH STRIPS

Model: 17068 | Brand: Command

PRODUCT OVERVIEW

The Command 3M 17068 Wire Hooks with Strips offer a damage-free solution for hanging items in your home or office. Designed to hold strongly on various surfaces, these hooks can be removed cleanly without leaving holes, marks, or sticky residue. Each pack contains two medium wire hooks and four medium adhesive strips, capable of holding up to 3 pounds (1.36 kg) per hook.



Image 1: Front view of the Command 3M 17068 Wire Hooks packaging. It displays two white wire hooks and the included adhesive strips, highlighting key features like strong hold and clean removal. The 3M logo is visible at the top right.

SETUP AND INSTALLATION

Proper installation ensures maximum holding power and clean removal. Follow these steps carefully:

1. **Clean the Surface:** Select a smooth, clean surface. Wipe the area with rubbing alcohol (isopropyl alcohol). Do not use household cleaners as they may leave a residue. Allow the surface to dry completely.
2. **Prepare the Strip:** Separate the Command Adhesive Strips. Remove the red liner from one side of the strip.
3. **Apply to Hook:** Press the adhesive strip firmly onto the back of the hook. Ensure the tab of the strip extends slightly below the hook for easy removal later.
4. **Apply to Wall:** Remove the black liner from the other side of the strip. Position the hook on the desired surface. Press the hook firmly against the wall for 30 seconds.
5. **Wait:** For maximum adhesion, wait 1 hour before hanging anything on the hook. This allows the adhesive to build strength.



Image 2: Packaging of Command Wire Hooks, illustrating the "Damage-Free Hanging" feature. The image shows the two hooks and highlights the 1 kg (3 lb) weight capacity. The reverse side of the packaging often contains visual installation instructions.

OPERATING AND USAGE

Once installed, your Command Wire Hooks are ready for use. They are designed for indoor use and can hold items up to 3 pounds (1.36 kg). Ensure the weight of the item you intend to hang does not exceed this limit.

- Do not hang valuable or irreplaceable items.
- Do not hang over beds.
- Do not use on wallpaper, vinyl surfaces, or other delicate surfaces.
- Ensure the hook is securely attached before hanging any item.

MAINTENANCE AND REMOVAL

Command Hooks require minimal maintenance. If you need to move or remove a hook, follow these steps for clean removal:

1. **Remove Item:** Take off any item hanging on the hook.
2. **Hold Hook:** Gently hold the top of the hook. Do not press the hook against the wall.
3. **Stretch Strip:** Slowly stretch the adhesive strip straight down along the wall, keeping your hand against the wall. Stretch the strip at least 6 inches (15 cm) until the hook releases from the wall. Do not pull the strip outwards or upwards.
4. **Re-application:** If you wish to re-use the hook, you will need a new Command Medium Adhesive Strip.

To clean the hooks, simply wipe them with a damp cloth. Do not use abrasive cleaners.

TROUBLESHOOTING

- **Hook fell off:**
 - Ensure the surface was cleaned with rubbing alcohol and allowed to dry completely before application.
 - Verify that the strip was pressed firmly against the hook and the wall for 30 seconds each.
 - Confirm that the 1-hour waiting period was observed before hanging items.
 - Check if the weight of the item exceeded the 3-pound limit.
- **Residue left on wall after removal:**
 - The strip might not have been stretched straight down or stretched enough (at least 6 inches).
 - Ensure the strip was not pulled outwards or upwards during removal.
- **Hook not sticking to surface:**
 - The surface might be textured, porous, or painted with a low-VOC paint, which can affect adhesion. Command hooks work best on smooth, solid surfaces.
 - Ensure the surface is not wallpaper or vinyl, as these are not recommended.

SPECIFICATIONS

Brand	Command
Model Number	17068
Color	White
Material	Plastic
Mounting Type	Wall Mount
Weight Limit	3 Pounds (1.36 kg)
Recommended Use	Indoor

Item Dimensions (L x W x H)	6.7 x 3.6 x 2 inches (17.02 x 9.14 x 5.08 cm)
Item Weight	1.6 ounces (45.36 grams)
Number of Hooks	2 per pack
UPC	051131921276
Date First Available	September 18, 2009




WARRANTY AND SUPPORT


Specific warranty information for the Command 3M 17068 Wire Hooks is typically provided on the product packaging or through the manufacturer's official website. For detailed warranty terms, product support, or to purchase replacement strips, please visit the official Command brand website or contact 3M customer service.

You can often find more information and support resources by visiting the [Command Store on Amazon](#).

© 2023 Command / 3M. All rights reserved. Information subject to change without notice.

Related Documents - 17068

	<p>Command 17006CLR-ES Clear Mini Hooks: Application and Removal Guide</p> <p>Step-by-step instructions for applying and removing Command Clear Mini Hooks (model 17006CLR-ES) using clear adhesive strips. Includes usage tips and warranty information.</p>
	<p>Command Hook Installation and Removal Instructions</p> <p>Step-by-step guide for applying and removing Command hooks, including product information and warranty details for model 17003ES.</p>
	<p>Dynojet Power Commander 6 Installation Guide for Kawasaki Z125 (PC6-17068)</p> <p>Detailed installation guide for the Dynojet Power Commander 6 (PC6-17068) on 2017-2020 Kawasaki Z125 motorcycles. Covers parts list, optional accessory inputs, wiring connections, and step-by-step installation procedures.</p>



[Regulus Ball Valve with Strainer: Installation and Maintenance Guide](#)

Comprehensive installation and maintenance instructions for the Regulus Ball Valve with Strainer, covering application, technical data, variants, installation procedures, and cleaning steps.