

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [DELTA](#) /

› [Delta Faucet RP53411 Dryden Bathroom Lift Rod, Knob and Set Screw Instruction Manual](#)

DELTA RP53411

DELTA Faucet RP53411 Dryden Bathroom Lift Rod, Knob and Set Screw Instruction Manual

Introduction	Product Overview	Components	Installation	Operation	Maintenance
	Troubleshooting	Specifications		Warranty & Support	

1. INTRODUCTION

This instruction manual provides detailed guidance for the installation, operation, and maintenance of your DELTA Faucet RP53411 Dryden Bathroom Lift Rod, Knob, and Set Screw. Please read these instructions carefully before beginning installation to ensure proper function and longevity of the product. Retain this manual for future reference.

2. PRODUCT OVERVIEW

The DELTA Faucet RP53411 is a genuine replacement part designed for Dryden series bathroom sink faucets. This component includes the lift rod, knob, and set screw, all finished in chrome. It is engineered to fit and function as the original part, ensuring reliable operation of your faucet's drain stopper mechanism.



Figure 1: The Delta Faucet RP53411 Dryden Bathroom Lift Rod, Knob, and Set Screw. This image displays the chrome-

finished lift rod with the attached knob and the small set screw, which secures the knob to the rod.

3. COMPONENTS LIST

Before beginning installation, ensure all components are present and undamaged. The package should contain the following items:

- **Lift Rod:** The main metal rod that connects to the drain stopper mechanism.
- **Knob:** The decorative handle attached to the top of the lift rod for manual operation.
- **Set Screw:** A small screw used to secure the knob to the lift rod.

4. INSTALLATION INSTRUCTIONS

This replacement part is designed for easy installation, typically requiring no specialized tools. Follow these steps to replace your existing lift rod assembly:

1. **Preparation:** If replacing an existing lift rod, carefully remove the old knob and lift rod from the faucet body. This may involve loosening a set screw on the old knob.
2. **Insert Lift Rod:** Insert the new lift rod into the designated opening on the faucet body. Ensure the bottom end of the lift rod engages correctly with the drain stopper mechanism beneath the sink.
3. **Attach Knob:** Place the new knob onto the top of the lift rod. Align the set screw hole on the knob with the flat surface or indentation on the lift rod, if present.
4. **Secure Knob:** Using a small screwdriver (not included), insert and tighten the provided set screw into the knob to firmly secure it to the lift rod. Do not overtighten.
5. **Test Functionality:** Operate the lift rod and knob to ensure the drain stopper opens and closes smoothly and completely. Adjust the lift rod's position if necessary to achieve proper drain operation.

5. OPERATION

The lift rod and knob assembly controls the drain stopper in your bathroom sink. To operate:

- **To Close the Drain:** Push the knob downwards. This action lowers the drain stopper, sealing the sink drain.
- **To Open the Drain:** Pull the knob upwards. This action raises the drain stopper, allowing water to flow out of the sink.

Ensure smooth movement and avoid excessive force when operating the lift rod.

6. MAINTENANCE

Proper care and maintenance will help preserve the finish and functionality of your DELTA Faucet RP53411 lift rod assembly.

- **Cleaning:** Clean the chrome finish regularly with a soft, damp cloth. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the finish.
- **Inspection:** Periodically check the set screw for tightness. If the knob feels loose, gently tighten the set screw.
- **Lubrication:** If the lift rod movement becomes stiff, a small amount of silicone-based lubricant can be applied to the pivot points of the drain stopper mechanism beneath the sink, ensuring it does not

come into contact with the visible chrome finish.

7. TROUBLESHOOTING

Problem	Possible Cause	Solution
Knob is loose or detached from the lift rod.	Set screw is loose or missing.	Tighten the set screw. If missing, contact DELTA Faucet for a replacement part.
Lift rod does not operate the drain stopper.	Lift rod not properly engaged with the drain stopper mechanism.	Ensure the lift rod is fully inserted and correctly connected to the pivot rod of the drain assembly beneath the sink.
Drain stopper does not seal completely or open fully.	Lift rod or pivot rod adjustment needed.	Adjust the position of the lift rod or the pivot rod nut beneath the sink to achieve proper stopper movement.

8. SPECIFICATIONS

Brand: DELTA

Model Number: RP53411

Material: Metal

Color/Finish: Chrome

Product Dimensions: 0.25" L x 0.25" W (Note: This dimension likely refers to the knob or a specific part, not the full rod length.)

Item Weight: Approximately 1.6 ounces (0.1 Pounds)

UPC: 034449585712

Included Components: Knob, Set Screw

Specific Uses: Bathroom Sink Faucet Replacement Part




9. WARRANTY AND SUPPORT

Warranty: This DELTA Faucet product is covered by a **Lifetime Faucet and Finish Limited Warranty**. For specific details regarding warranty coverage, limitations, and claims, please refer to the official DELTA Faucet warranty documentation or visit their official website.

Customer Support: If you require further assistance, have questions about installation, or need to obtain replacement parts, please contact DELTA Faucet customer service. Contact information can typically be found on the DELTA Faucet official website or on the original product packaging.

For more information, visit the [DELTA Store on Amazon](#).

Related Documents - RP53411

	<p><u>Delta Touch2O Technology Lavatory Faucets - Installation, Warranty, and Maintenance Guide</u></p> <p>Comprehensive guide for Delta Touch2O Technology Lavatory Faucets, including installation, cleaning, care, limited warranty, maintenance, and troubleshooting. Covers models like COMPEL, LAHARA, DRYDEN, ADDISON, TESLA, and TALBOTT with Touch2O technology.</p>
	<p><u>Delta Touch2O® Technology Lavatory Faucets Installation and Maintenance Manual</u></p> <p>Comprehensive guide for installing, maintaining, and troubleshooting Delta Touch2O® Technology Lavatory Faucets, covering various models like COMPEL®, LAHARA®, DRYDEN™, ADDISON™, TESLA®, TALBOTT™, and more. Includes warranty information and quick tips.</p>
	<p><u>Delta Touch2O Technology Lavatory Faucets Installation and Maintenance Guide</u></p> <p>Comprehensive guide for Delta Touch2O Technology Lavatory Faucets, covering installation, maintenance, troubleshooting, and warranty information for models like COMPEL, LAHARA, DRYDEN, ADDISON, TESLA, and TALBOTT.</p>
	<p><u>Delta Touch2O® Technology Lavatory Faucets Installation and Maintenance Guide</u></p> <p>Comprehensive guide for installing, maintaining, and troubleshooting Delta Touch2O® Technology Lavatory Faucets, covering models like Compel, Lahara, Dryden, Addison, Tesla, and Talbott. Includes warranty information and quick tips.</p>
	<p><u>Delta Trinsic Tub and Shower Faucet Trim Specifications</u></p> <p>Comprehensive product specifications, features, warranty, and compliance details for the Delta Trinsic Tub and Shower Faucet Trim collection, including model numbers T14058, T14158, T14258, and T14458.</p>
	<p><u>Delta Woodhurst 3532LF-AMPU Two Handle Widespread Bathroom Faucet Installation Guide</u></p> <p>Comprehensive installation guide for the Delta Woodhurst 3532LF-AMPU two-handle widespread bathroom faucet, including step-by-step instructions, maintenance tips, and warranty information.</p>

