

[Manuals.plus](#) /

› [LiftMaster](#) /

› LiftMaster 12V Impact Wrench User Manual

LiftMaster 607c

LiftMaster 12V Impact Wrench User Manual

Model: 607c | Brand: LiftMaster

INTRODUCTION

This user manual provides essential information for the safe and effective operation, maintenance, and troubleshooting of your LiftMaster 12V Impact Wrench. Please read this manual thoroughly before using the tool and retain it for future reference. This impact wrench is designed for the fast removal of stubborn wheel nuts and studs, powered by your vehicle's 12V power socket or battery connector.

SAFETY INFORMATION

WARNING: Always observe basic safety precautions when using electrical tools to reduce the risk of fire, electric shock, and personal injury.

- Ensure the power source is 12V DC only. Do not connect to higher voltage sources.
- Keep the work area clean and well-lit. Cluttered or dark areas invite accidents.
- Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases, or dust.
- Keep children and bystanders away while operating a power tool. Distractions can cause you to lose control.
- Wear appropriate personal protective equipment, including safety glasses, gloves, and hearing protection.
- Avoid accidental starting. Ensure the switch is in the off-position before connecting to power.
- Do not overreach. Keep proper footing and balance at all times.
- Disconnect the plug from the power source before making any adjustments, changing accessories, or storing power tools.
- Do not abuse the cord. Never use the cord for carrying, pulling, or unplugging the power tool. Keep cord away from heat, oil, sharp edges, or moving parts.
- Store idle power tools out of the reach of children and do not allow persons unfamiliar with the power tool or these instructions to operate the power tool.

PACKAGE CONTENTS

Carefully unpack your LiftMaster 12V Impact Wrench and check for the following items:

- LiftMaster 12V Impact Wrench
- Two double-ended sockets: 17mm-19mm and 21mm-23mm
- 12V cigarette lighter plug power cord (approximately 3.5M / 11FT)
- Battery connector clamps
- Storage case
- User Manual (this document)



Figure 1: Complete LiftMaster 12V Impact Wrench kit in its storage case.

PRODUCT OVERVIEW

The LiftMaster 12V Impact Wrench is a compact and powerful tool designed for automotive applications, specifically for

loosening and tightening wheel nuts. It features a robust motor and a standard 1/2-inch socket shaft for compatibility with various sockets.



Figure 2: All components of the LiftMaster 12V Impact Wrench kit.



Figure 3: The LiftMaster 12V Impact Wrench itself.

Key Components:

- **Impact Wrench Body:** Houses the motor and impact mechanism.
- **1/2" Square Drive:** For attaching sockets.
- **Power Cord:** Integrated cord with a 12V cigarette lighter plug.
- **Battery Connector Clamps:** Adapter for direct connection to a 12V car battery.
- **Sockets:** Included double-ended sockets (17mm/19mm and 21mm/23mm) for common wheel nut sizes.

SETUP

Before operating the impact wrench, ensure your vehicle's parking brake is engaged and the vehicle is stable.

1. Choose Power Source:

- **Cigarette Lighter Socket:** Insert the 12V plug firmly into your vehicle's cigarette lighter socket. Ensure the socket is clean and free of debris for a good connection.
- **Battery Connector:** If your vehicle's cigarette lighter socket is not accessible or provides insufficient power, use the included battery connector clamps. Connect the red clamp to the positive (+) terminal of your 12V car battery and the black clamp to the negative (-) terminal. Ensure a secure connection.

2. Attach Socket:

Select the appropriate double-ended socket (17mm-19mm or 21mm-23mm) for your wheel nuts.

Push the socket firmly onto the 1/2-inch square drive of the impact wrench until it clicks into place.

3. **Check Cord Length:** The power cord is approximately 3.5 meters (11 feet) long. Ensure it reaches the wheel you are working on without being stretched or creating a tripping hazard.

OPERATING INSTRUCTIONS

Follow these steps for safe and effective operation of your LiftMaster 12V Impact Wrench:

1. **Loosening Wheel Nuts:**
- With the correct socket attached, place the socket firmly onto the wheel nut.
 - Ensure the wrench is set to the "reverse" or "loosen" direction (usually indicated by an arrow or switch on the tool).
 - Press the trigger to activate the wrench. The impact mechanism will begin to loosen the nut. Hold the wrench firmly to counteract the torque.
 - Continue until the nut is loose enough to be removed by hand.
2. **Tightening Wheel Nuts:**
- Hand-tighten the wheel nuts onto the studs as much as possible before using the impact wrench.
 - Place the socket firmly onto the wheel nut.
 - Ensure the wrench is set to the "forward" or "tighten" direction.
 - Press the trigger to activate the wrench. The impact mechanism will tighten the nut.
 - **Torque Setting:** This wrench features a torque level preset. While the wrench will tighten nuts effectively, it is highly recommended to use a calibrated torque wrench to achieve the vehicle manufacturer's specified torque settings for wheel nuts. This ensures proper and safe fastening, preventing over-tightening or under-tightening.
3. **After Use:** Release the trigger, disconnect the power source, and remove the socket.

MAINTENANCE

Regular maintenance ensures the longevity and optimal performance of your impact wrench.

- **Cleaning:** After each use, wipe down the tool with a clean, dry cloth to remove dirt, dust, and grease. Do not use harsh chemicals or abrasive cleaners.
- **Storage:** Store the impact wrench and its accessories in the provided storage case in a dry, cool place, away from direct sunlight and moisture. Keep it out of reach of children.
- **Cord Inspection:** Periodically inspect the power cord for any signs of damage, cuts, or fraying. If damaged, do not use the tool and have the cord repaired by a qualified technician.
- **Lubrication:** For prolonged tool life, consider occasional lubrication of the internal planetary gearbox bushes and shafts. This should be performed by a qualified service professional.

TROUBLESHOOTING

If you encounter issues with your LiftMaster 12V Impact Wrench, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
---------	----------------	----------

Problem	Possible Cause	Solution
Wrench does not operate / No power.	No power from 12V socket/battery. Loose connection. Blown fuse in vehicle's circuit. Internal fault.	Check vehicle's 12V socket for power (e.g., by testing with another device). Ensure plug/clamps are securely connected. Check and replace vehicle's fuse if necessary. If problem persists, seek professional service.
Wrench operates but does not loosen/tighten nuts effectively.	Incorrect socket size. Nut is seized/rusted. Insufficient power supply.	Ensure the correct socket size is used and fully engaged. Apply penetrating oil to seized nuts and allow time to work. Ensure a strong 12V connection, consider using battery clamps for direct power.
Wrench stops working intermittently or after use.	Internal mechanism "locks out" or sticks. Overheating protection activated.	Disconnect power, allow tool to cool down. Gently tap the side of the wrench (as described in some user experiences) to reset the mechanism. If this becomes a frequent issue, professional inspection is recommended.

TECHNICAL SPECIFICATIONS

Feature	Specification
Model Number	607c
Power Source	12V DC (Vehicle cigarette lighter socket or battery connector)
Power Consumption	70W
Cord Length	3.5 meters (11 feet)
Socket Drive	1/2 inch square drive
Included Sockets	Double-ended 17mm-19mm, 21mm-23mm
Item Weight	2.7 kg
Package Dimensions	27.94 x 22.61 x 11.18 cm

WARRANTY AND SUPPORT

This LiftMaster 12V Impact Wrench is manufactured to high-quality standards. For information regarding warranty coverage, terms, and conditions, please refer to the warranty documentation provided with your purchase or contact LiftMaster customer support. Keep your proof of purchase for any warranty claims.

For technical assistance or service inquiries, please contact the retailer or manufacturer directly. Do not attempt to repair the tool yourself unless specifically instructed by a qualified service professional, as this may void your warranty and pose safety risks.