

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [HCC](#) /

› [HCC Marine Grade ATV Seat Cover Instruction Manual for Polaris Trail Boss 250 2x4 \(1991 Model\)](#)

## HCC HCC 57-600

# HCC Marine Grade ATV Seat Cover Instruction Manual

For 1991 Polaris Trail Boss 250 2x4 (Model: HCC 57-600)

## INTRODUCTION

This manual provides comprehensive instructions for the proper installation and maintenance of your new HCC Marine Grade ATV Seat Cover. This product is designed as a full replacement seat cover for the 1991 Polaris Trail Boss 250 2x4. Please read all instructions carefully before beginning installation to ensure correct fitment and longevity of the product.

## SAFETY INFORMATION

- Always wear appropriate safety gear, such as gloves and eye protection, during installation.
- Ensure the ATV is turned off and stable before beginning any work on the seat.
- Keep small parts and tools away from children.
- If you are unsure about any step, consult a qualified technician.

## PACKAGE CONTENTS

Please verify that all items are present before proceeding with installation:

- 1x HCC Marine Grade ATV Seat Cover (Black)
- 1x Detailed Installation Guide (this document)

## SETUP AND INSTALLATION

This seat cover is designed as a full replacement. The existing seat cover fabric must be completely removed from the seat pan before installing the new HCC cover.

### Tools Required:

- Staple gun (manual or pneumatic)

- Staples (stainless steel recommended for marine grade material)
- Flathead screwdriver or staple remover (for old staples)
- Pliers (optional, for removing stubborn staples)
- Heat gun or hairdryer (optional, to make material more pliable)

## Installation Steps:

1. **Remove Existing Seat Cover:** Carefully remove all staples holding the old seat cover to the seat pan. Peel off and discard the old cover. Ensure the seat foam is clean and dry.
2. **Position New Seat Cover:** Center the new HCC seat cover over the seat foam. Ensure the front and rear are correctly aligned. The cover is designed to fit the specific contours of your 1991 Polaris Trail Boss 250 2x4 seat.
3. **Initial Fastening (Front and Rear):** Start by stapling the front center of the cover to the underside of the seat pan. Then, pull the cover taut towards the rear center and staple it. This establishes the primary tension points.
4. **Work Towards Sides:** Working from the center outwards, pull the cover firmly and evenly around the sides of the seat pan. Staple approximately every 1-2 inches, ensuring the material is smooth and free of wrinkles. If the material is stiff, a heat gun or hairdryer can be used on a low setting to make it more pliable, but be careful not to overheat or damage the material.
5. **Corners and Curves:** Pay special attention to corners and curves. You may need to make small relief cuts in the excess material on the underside of the pan to allow it to lay flat, but avoid cutting into the visible portion of the cover. Pull and staple securely.
6. **Final Inspection:** Once all edges are stapled, inspect the seat cover for any loose areas, wrinkles, or uneven tension. Add more staples as needed to achieve a tight, professional finish.



*Image: The HCC Marine Grade ATV Seat Cover, showcasing its black finish and contoured design. This image illustrates the product's appearance once installed on a compatible seat pan.*

## OPERATION (GENERAL USE)

Once installed, your HCC Marine Grade ATV Seat Cover provides a durable and comfortable riding surface. The marine-grade material is designed to withstand various outdoor conditions.

- Ensure the seat is securely reattached to the ATV before operation.
- Avoid sharp objects that could puncture or tear the seat cover material.
- Periodically check the staples on the underside of the seat pan to ensure they remain secure.

## MAINTENANCE

---

Proper care will extend the life and appearance of your seat cover.

- **Cleaning:** Wipe the seat cover with a damp cloth and mild soap solution. Rinse thoroughly with clean water. Avoid harsh chemicals, abrasive cleaners, or stiff brushes, as these can damage the marine-grade material.
- **Drying:** Allow the seat cover to air dry completely before storage or prolonged exposure to direct sunlight after cleaning.
- **Protection:** For long-term storage or extreme weather conditions, consider using an ATV cover to protect the seat and the entire vehicle.

## TROUBLESHOOTING

---

Issue	Possible Cause	Solution
Wrinkles or loose areas after installation	Insufficient tension during stapling; material not pliable enough.	Carefully remove staples from affected area, re-stretch the material firmly, and re-staple. Use a heat gun on low to make material more flexible if needed.
Staples pulling out	Incorrect staple length; staples not fully seated; weak seat pan material.	Use longer staples or ensure staples are fully driven. Consider using a stronger staple gun or different staple type (e.g., stainless steel).
Difficulty fitting cover	Not properly centered; cold material; incorrect model year.	Re-center the cover. Warm the material with a heat gun or hairdryer on low. Verify the seat cover is for the correct 1991 Polaris Trail Boss 250 2x4 model.

## SPECIFICATIONS

---

**Product Type:** ATV Seat Cover (Full Replacement)

**Brand:** HCC

**Model Number:** HCC 57-600

**Compatibility:** 1991 Polaris Trail Boss 250 2x4

**Material:** Marine Grade Vinyl

**Color:** Black

**ASIN:** B003EM1W9O

## WARRANTY AND SUPPORT

---

For specific warranty information or technical support regarding your HCC Marine Grade ATV Seat Cover,

please refer to the seller's documentation or contact the manufacturer directly. General return policies may apply as per the point of purchase.

© 2023 HCC. All rights reserved.