

[manuals.plus](#) /

› [PhyIrich](#) /

› [PhyIrich K8200_014 Single Hole Bar Faucet Instruction Manual](#)

PhyIrich K8200014

PhyIrich K8200_014 Single Hole Bar Faucet Instruction Manual

Model: K8200014

1. PRODUCT OVERVIEW

The PhyIrich K8200_014 is a high-quality single-hole bar faucet designed for deck-mount installation. Featuring a polished nickel finish and a 5-inch spout, this faucet combines elegant design with functional performance for your bar or prep sink area.



Image 1.1: The PhyIrich K8200_014 Single Hole Bar Faucet, showcasing its polished nickel finish and single handle design.

2. SAFETY INFORMATION

Please read all instructions carefully before installation and use. Failure to follow these instructions may result in property damage or personal injury.

- Always turn off the main water supply before beginning any plumbing work.
- Wear appropriate personal protective equipment, such as safety glasses, during installation.
- If you are unsure about any part of the installation process, consult a qualified plumber.

- Do not overtighten connections, as this can damage the faucet or plumbing.
- Keep small parts away from children.

3. PACKAGE CONTENTS

Verify that all components are present before beginning installation:

- Phylrich K8200_014 Bar Faucet Assembly
- Mounting Hardware
- Bar Closure Hose
- Installation Instructions (this document)

4. SETUP AND INSTALLATION

This faucet is designed for single-hole deck-mount installation. Follow these general steps for proper setup.

4.1. Prepare the Installation Area

1. Turn off the main water supply to the sink area.
2. Clear the area under the sink for easy access.
3. If replacing an old faucet, remove it and clean the sink surface thoroughly.

4.2. Faucet Installation

1. Insert the faucet body into the single mounting hole on the sink or countertop.
2. From underneath the sink, secure the faucet using the provided mounting hardware (washer and nut). Ensure the faucet is properly aligned before tightening.
3. Connect the hot and cold water supply lines to the corresponding inlets on the faucet. Use thread sealant tape on threaded connections to prevent leaks.
4. Connect the bar closure hose as per the diagram (if applicable, specific diagram not provided in data).
5. Ensure all connections are hand-tight, then use a wrench for a final quarter-turn to secure, being careful not to overtighten.

4.3. Test for Leaks

1. Slowly turn on the main water supply.
2. Check all connections for leaks. If leaks are present, gently tighten the connection until the leak stops.
3. Operate the faucet to ensure proper water flow and temperature control.

5. OPERATING INSTRUCTIONS

The Phylrich K8200_014 bar faucet features a single handle for controlling both water flow and temperature.

- **To Turn On/Off:** Lift the handle to turn on the water. Push the handle down to turn off the water.
- **To Adjust Water Flow:** The height to which you lift the handle controls the water volume.
- **To Adjust Temperature:** Move the handle left for hot water and right for cold water. The further you move it, the hotter or colder the water will become.

6. MAINTENANCE

Proper care and maintenance will ensure the longevity and appearance of your Phylrich faucet.

- **Cleaning:** Clean the polished nickel finish regularly with a soft, damp cloth. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the finish.
- **Aerator Maintenance:** If water flow decreases, the aerator may be clogged. Unscrew the aerator from the spout, clean any debris, and rinse thoroughly before reattaching.
- **Leak Prevention:** Periodically check all connections under the sink for any signs of leaks. Tighten connections gently if necessary.

7. TROUBLESHOOTING

Refer to the following table for common issues and their solutions:

Problem	Possible Cause	Solution
Low Water Flow	Clogged aerator; partially closed shut-off valve; kinked supply line.	Clean aerator; ensure shut-off valves are fully open; check supply lines for kinks.
Leaking at Faucet Base	Loose mounting nut; worn O-rings.	Tighten mounting nut; inspect and replace O-rings if necessary (consult a plumber).
Leaking from Spout	Worn cartridge.	Replace the faucet cartridge (consult a plumber or manufacturer for parts).
No Hot/Cold Water	Supply valve closed; cross-connection issue.	Ensure hot/cold supply valves are open; consult a plumber for cross-connection issues.

8. SPECIFICATIONS

- **Brand:** Phylrich
- **Model Number:** K8200014
- **Mounting Type:** Deck Mount
- **Installation Type:** Single Hole
- **Finish Type:** Polished
- **Color:** Nickel
- **Included Components:** Bar Closure Hose
- **Handle Location:** Single-hole-deck-mount
- **UPC:** 883908361165

9. WARRANTY AND SUPPORT

For warranty information or technical support, please contact Phylrich customer service directly. Keep your purchase receipt as proof of purchase.

For further assistance, please visit the official Phylrich website or contact their customer support line.

