

Phylrich KES25/004

Phylrich KES25/004 Regent Wall Mounted Soap Dish User Manual

Model: KES25/004

INTRODUCTION

This manual provides comprehensive instructions for the installation, usage, and maintenance of your Phylrich KES25/004 Regent Wall Mounted Soap Dish. Please read this manual thoroughly before installation and retain it for future reference. Proper installation and care will ensure the longevity and optimal performance of your product.

SAFETY INFORMATION

- Always turn off the main water supply if working near plumbing lines.
- Wear appropriate personal protective equipment, such as safety glasses, during installation.
- Ensure the mounting surface is structurally sound and capable of supporting the fixture.
- Use caution when handling tools to prevent injury.
- Keep small parts away from children to prevent choking hazards.

PACKAGE CONTENTS

Verify that all components are present before beginning installation. If any parts are missing or damaged, contact your retailer or Phylrich customer service.

- Phylrich KES25/004 Regent Wall Mounted Soap Dish Assembly (Brass fixture with Glass dish)
- Mounting Hardware (screws, anchors, mounting plate)
- Installation Template (if included)

TOOLS REQUIRED

The following tools are typically required for installation:

- Pencil
- Measuring Tape

- Level
- Drill with appropriate drill bit for anchors
- Screwdriver (Phillips or Flathead, as required by screws)
- Stud Finder (recommended for optimal mounting)

SETUP AND INSTALLATION

Follow these steps carefully to install your wall-mounted soap dish:

1. **Choose Location:** Select a suitable location on the wall, ensuring it is at a convenient height and away from direct water spray if possible. Use a level to ensure the mounting area is straight.
2. **Mark Drilling Points:** Use the provided installation template (if available) or hold the mounting plate against the wall at the desired location. Mark the screw hole positions with a pencil.
3. **Drill Pilot Holes:** Using a drill with the appropriate drill bit size for the wall anchors, carefully drill pilot holes at the marked positions. If drilling into a wall stud, anchors may not be necessary, but ensure screws are suitable for wood.
4. **Insert Wall Anchors:** If drilling into drywall or tile, gently tap the wall anchors into the pilot holes until they are flush with the wall surface.
5. **Attach Mounting Plate:** Align the mounting plate with the drilled holes and secure it to the wall using the provided screws. Ensure the plate is firmly attached and level.
6. **Mount Soap Dish Fixture:** Carefully align the main soap dish fixture with the mounting plate. Secure the fixture to the plate using the set screw(s) typically located on the underside of the fixture. Tighten the set screw(s) with a screwdriver until the fixture is snug and does not wobble.
7. **Insert Glass Dish:** Place the glass soap dish into the brass holder. Ensure it sits securely.



Image: The Phylrich KES25/004 Regent Wall Mounted Soap Dish, featuring a clear glass dish set within a decorative brass fixture. The brass base is circular with a textured edge, designed for wall mounting.

USAGE

The Phylrich KES25/004 Regent Wall Mounted Soap Dish is designed to hold a bar of soap conveniently in your bathroom. Simply place your bar of soap onto the glass dish. The wall-mounted design helps keep your countertop clear and organized.

MAINTENANCE

Regular cleaning will help maintain the finish and appearance of your soap dish.

- **Cleaning the Brass Fixture:** Use a soft, damp cloth and a mild, non-abrasive cleaner specifically designed for brass or general bathroom fixtures. Avoid harsh chemicals, abrasive pads, or polishes that can damage the finish. Wipe dry immediately after cleaning to prevent water spots.
- **Cleaning the Glass Dish:** The glass dish can be removed for thorough cleaning. Wash with warm, soapy water and a soft sponge. Rinse thoroughly and dry with a lint-free cloth.
- **Avoid:** Do not use cleaners containing ammonia, bleach, or abrasive agents on any part of the soap dish.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Soap dish feels loose on the wall.	Mounting screws or set screw are not tight.	Gently tighten the mounting screws behind the fixture or the set screw(s) on the underside of the fixture. Do not overtighten.
Glass dish is wobbly.	Dish not seated correctly or debris in holder.	Remove the glass dish, inspect for debris, clean, and re-seat it firmly into the brass holder.
Finish appears dull or stained.	Hard water spots or improper cleaning agents.	Clean with a soft, damp cloth and a mild, non-abrasive cleaner. Avoid harsh chemicals. Dry immediately after cleaning.

SPECIFICATIONS







Model: KES25/004
Brand: Phylrich
Material: Brass, Glass
Mounting Type: Wall Mount
Item Package Quantity: 1
ASIN: B003I9RBNE
UPC: 883908627797

WARRANTY INFORMATION

Specific warranty details for the Phylrich KES25/004 Regent Wall Mounted Soap Dish are typically provided at the point of purchase or can be obtained directly from the manufacturer. Please refer to your purchase documentation or visit the official Phylrich website for the most current warranty policy.

CUSTOMER SUPPORT

For technical assistance, missing parts, or warranty inquiries, please contact your retailer or the manufacturer, Phylrich, directly. Contact information can usually be found on their official website or on your product packaging.

 <p>PHYLIRICH® Enriching Lavatory Since 1989</p> <p>INSTALLATION INSTRUCTIONS FOR WALL MOUNTED BIDET (1-124)</p>	<p>Phylrich 1-124 Wall Mounted Bidet Installation Instructions</p> <p>Comprehensive installation guide for the Phylrich 1-124 Wall Mounted Bidet, detailing valve specifications, parts breakdown, rough-in dimensions, installation procedures, and maintenance tips for optimal performance and longevity.</p>
 <p>PHYLIRICH® Enriching Lavatory Since 1989</p> <p>INSTALLATION INSTRUCTIONS FOR LAVATORY FAUCETS WITH DRY TEE FLUSH MOUNTED VALVE (TRANSITION SERIES)</p>	<p>Phylrich Transition Series Lavatory Faucet Installation Guide & Limited Warranty</p> <p>Comprehensive installation instructions and limited warranty details for the Phylrich Transition Series lavatory faucet with a dry tee flush mounted valve, covering setup, drain assembly, and product coverage.</p>
 <p>PHYLIRICH® Enriching Lavatory Since 1989</p> <p>INSTALLATION INSTRUCTIONS FOR LAVATORY FAUCETS WITH DRY TEE FLUSH MOUNTED VALVE (JAMESTOWN SERIES)</p>	<p>Phylrich Jamestown Series Lavatory Faucet Installation Guide & Limited Warranty</p> <p>Comprehensive installation instructions for the Phylrich Jamestown Series lavatory faucet with a dry tee flush mounted valve, including detailed steps, diagrams, and information on the limited lifetime warranty.</p>
 <p>PHYLIRICH® Enriching Lavatory Since 1989</p> <p>INSTALLATION INSTRUCTIONS FOR 1/2" PRESSURE BALANCE VALVE (DFPHY & DFPHYID SERIES)</p>	<p>Phylrich DFPHY & DFPHYID 1/2" Pressure Balance Valve Installation Instructions</p> <p>Comprehensive installation guide for the Phylrich DFPHY and DFPHYID 1/2 inch pressure balance valve, covering general characteristics, valve specifications, rough-in dimensions, temperature settings, and maintenance procedures.</p>
 <p>PHYLIRICH® Enriching Lavatory Since 1989</p> <p>INSTALLATION INSTRUCTIONS FOR SINGLE HANDLE WIDESPREAD FAUCET (JAMESTOWN SERIES)</p>	<p>Phylrich Jamestown Series Single Handle Widespread Faucet Installation Guide</p> <p>Comprehensive installation instructions for the Phylrich Jamestown Series single handle widespread faucet with high spout and lever handle. Covers spout, valve, and drain assembly with detailed steps and textual descriptions of diagrams.</p>
 <p>PHYLIRICH® Enriching Lavatory Since 1989</p> <p>INSTALLATION INSTRUCTIONS FOR JAMESTOWN SERIES WALL LAVATORY SET (165-11 CROSS HANDLE & 165-12 LEVER HANDLE)</p>	<p>Jamestown Series Wall Lavatory Set Installation Instructions</p> <p>Detailed installation guide for the Phylrich Jamestown Series Wall Lavatory Set, including models 165-11 (Cross Handle) and 165-12 (Lever Handle). Covers spout, escutcheon, handle installation, trim adjustments, and cartridge replacement with torque specifications.</p>