

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [WENKO](#) /

› [WENKO Stainless Steel Mounting Element for Toilet Seats \(Model: 290219100\) Instruction Manual](#)

WENKO 290219100

WENKO Stainless Steel Mounting Element for Toilet Seats (Model: 290219100)

Instruction Manual

INTRODUCTION

This manual provides detailed instructions for the installation and maintenance of your WENKO Stainless Steel Mounting Element for Toilet Seats. This 8-piece set is designed to securely fasten toilet seats to the toilet bowl, offering a reliable replacement for original WENKO fastening clips.

Please read these instructions carefully before beginning installation to ensure proper function and longevity of the product.

PACKAGE CONTENTS

The WENKO Stainless Steel Mounting Element set typically includes the following 8 pieces:

- 2 x Stainless Steel Mounting Bolts
- 2 x Plastic Expansion Plugs
- 2 x Plastic Washers (may include transparent rings with a rim)
- 2 x Stainless Steel Nuts

Note: Some sets may include additional components such as extra plastic flat washers, metal washers, or a small plastic wrench for tightening, as described in some user experiences. The core 8 pieces for mounting are listed above.



DIE BESSERE IDEE

Image: Components of the WENKO Stainless Steel Mounting Element for Toilet Seats. This image displays the individual components included in the 8-piece WENKO toilet seat mounting set, featuring various plastic and stainless steel parts.

INSTALLATION INSTRUCTIONS

Follow these steps to properly install the WENKO Stainless Steel Mounting Element for your toilet seat:

1. **Prepare the Toilet Bowl:** Ensure the mounting holes on your toilet bowl are clean and free from any debris or old mounting residue.
2. **Insert Plastic Expansion Plugs:** Place one plastic expansion plug into each mounting hole on the toilet bowl. These plugs provide a snug fit for the bolts.
3. **Position the Toilet Seat:** Align your toilet seat's mounting brackets over the holes where the plastic plugs have been inserted.
4. **Insert Mounting Bolts and Plastic Rings:** From the top, insert a stainless steel mounting bolt through each toilet seat bracket. If your set includes transparent plastic rings with a rim, place one onto the bolt before pushing the bolt down into the plastic expansion plug.
5. **Add Washers (from underneath):** From underneath the toilet bowl, slide any additional transparent plastic flat washers, followed by metal washers (if included in your set), onto each bolt.
6. **Attach Stainless Steel Nuts:** Thread a stainless steel nut onto each bolt from underneath.
7. **Hand-Tighten:** Hand-tighten the nuts until they are snug. Do not overtighten at this stage, as you may need to adjust the seat position.
8. **Adjust Seat Position:** Close the toilet seat and adjust its position to ensure it is centered and aligned with the toilet bowl.
9. **Final Tightening:** Once the seat is correctly positioned, fully tighten the stainless steel nuts using an appropriate wrench. A small plastic wrench may be included in your set for this purpose. Be careful not to overtighten, which could damage the toilet bowl or the mounting elements.

Note: This set is suitable as a replacement for WENKO fastening clips of toilet seats from models such as Beach, Java, Mare, Rhodes, Ruby, Sonata, and Tropic.

MAINTENANCE

To ensure the longevity and proper function of your WENKO mounting elements, follow these maintenance guidelines:

- **Cleaning:** Clean the stainless steel components regularly with a soft cloth and mild, non-abrasive cleaning agents. Avoid harsh chemicals or abrasive scrubbers, which can damage the finish.
- **Check Tightness:** Periodically check the tightness of the mounting nuts. Over time, vibrations or use may cause them to loosen. Retighten if necessary, but do not overtighten.
- **Inspect for Wear:** Occasionally inspect the plastic and stainless steel components for any signs of wear, corrosion, or damage. Replace the set if significant wear is observed to maintain secure fastening.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Toilet seat is loose or wobbly.	Mounting nuts are not sufficiently tightened.	Tighten the stainless steel nuts underneath the toilet bowl. Ensure the seat is aligned before final tightening.
Mounting bolts do not fit into toilet bowl holes.	Incorrect size of expansion plugs or toilet bowl holes.	Ensure the plastic expansion plugs are fully inserted. If the holes are unusually sized, this mounting set may not be compatible.
Difficulty in aligning the toilet seat.	Nuts are overtightened prematurely.	Loosen the nuts slightly, adjust the seat to the desired position, then retighten.

SPECIFICATIONS

Brand	WENKO
Model Number	290219100
Material	Stainless Steel (components also include plastic)
Color	Chrome
Product Dimensions	3.94"L x 3.94"W (approximate, for individual components)
Item Weight	127 Grams (4.5 ounces)
Set Contents	8-piece WC mounting set

SUPPORT

For further assistance or inquiries regarding your WENKO Stainless Steel Mounting Element, please refer to the official WENKO website or contact their customer support. You can visit the [WENKO Store on Amazon](#) for more product information.

