

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Rohl](#) /

› [ROHL U.4718X-EG-2 Bridge Kitchen Faucet with Sidespray User Manual](#)

Rohl U.4718X-EG-2

ROHL U.4718X-EG-2 Bridge Kitchen Faucet with Sidespray User Manual

Perrin & Rowe Georgian Era Series

1. INTRODUCTION

Thank you for choosing the ROHL U.4718X-EG-2 Bridge Kitchen Faucet with Sidespray. This manual provides essential information for the proper installation, operation, and maintenance of your new faucet. Please read these instructions thoroughly before beginning installation or use to ensure safe and efficient performance. Retain this manual for future reference.

2. PRODUCT OVERVIEW

The ROHL U.4718X-EG-2 is a high-quality bridge-style kitchen faucet designed for deck mounting. It features a classic Georgian Era aesthetic, durable brass construction, and includes a convenient sidespray for enhanced functionality in your kitchen.

Key Features:

- **Brass Construction:** Ensures durability and longevity.
- **Bridge Design:** Classic aesthetic with two handles for precise temperature control.
- **Sidespray Functionality:** Separate spray unit for targeted cleaning.
- **Deck Mount Installation:** Designed for installation directly onto the countertop or sink deck.
- **English Gold Finish:** A luxurious and durable surface treatment.

Product Illustration:



Figure 2.1: ROHL U.4718X-EG-2 Bridge Kitchen Faucet with Sidespray. This image displays the complete ROHL U.4718X-EG-2 Bridge Kitchen Faucet assembly. It features a high-arc C-spout, two cross-style handles for hot and cold water control, and a separate sidespray unit, all in a polished English Gold finish. The bridge design connects the two handle bases.

3. SAFETY INFORMATION

Please observe the following safety precautions during installation and use:

- Always turn off the main water supply before beginning any plumbing work.

- Wear appropriate personal protective equipment, such as safety glasses and gloves.
- If you are unsure about any part of the installation process, consult a qualified plumber.
- This product may expose you to chemicals known to the State of California to cause cancer or birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.
- Ensure all connections are secure and leak-free before restoring water supply.

4. SETUP AND INSTALLATION

Professional installation is recommended for optimal performance and to ensure compliance with local plumbing codes. The faucet is designed for deck-mounted installation requiring three holes.

Required Tools (Not Included):

- Adjustable wrench
- Plumber's putty or silicone sealant
- Screwdriver
- Flashlight
- Bucket and towels

Installation Steps:

1. **Prepare the Sink/Countertop:** Ensure the mounting surface has three holes, each with a maximum cutout of 1 inch, spaced appropriately for a bridge faucet and sidespray. Clean the area thoroughly.
2. **Install Faucet Body:** Apply plumber's putty or silicone sealant to the underside of the faucet bases. Insert the faucet shanks through the two main holes on the deck. Secure from underneath with washers and mounting nuts, tightening firmly but carefully.
3. **Install Sidespray:** Apply sealant to the base of the sidespray. Insert its shank through the third hole. Secure from underneath with its mounting nut.
4. **Connect Water Supply Lines:** Connect the hot and cold water supply lines to the corresponding 3/8" compression connections on the faucet. Use unions included for secure connections. Ensure connections are hand-tight, then tighten an additional quarter to half turn with a wrench. Do not overtighten.
5. **Connect Sidespray Hose:** Attach the sidespray hose to the designated outlet on the faucet body. Ensure a tight, leak-free connection.
6. **Test for Leaks:** Slowly turn on the main water supply. Check all connections for leaks. If leaks are detected, tighten connections slightly until they stop.

5. OPERATING INSTRUCTIONS

Your ROHL bridge kitchen faucet is designed for ease of use and precise control.

Faucet Operation:

- **Water Flow:** Turn the handles to control the water flow. Typically, the left handle controls hot water and the right handle controls cold water.
- **Temperature Control:** Adjust the hot and cold handles simultaneously to achieve the desired water temperature.
- **Shut-off:** Turn both handles fully to the off position to stop water flow.

Sidespray Operation:

- To activate the sidespray, ensure the main faucet is running, then press the button or lever on the sidespray head.
- Release the button or lever to return water flow to the main spout.

6. MAINTENANCE

Proper care and maintenance will preserve the beauty and functionality of your English Gold finish faucet.

Cleaning the Finish:

- Clean the faucet regularly with a soft, damp cloth and mild soap.
- Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the English Gold finish.
- Rinse thoroughly with clean water after cleaning and dry with a soft cloth to prevent water spots.

Aerator Maintenance:

- If water flow becomes restricted, the aerator may be clogged. Unscrew the aerator from the end of the spout.
- Rinse any debris from the aerator screen. For stubborn mineral deposits, soak the aerator in a 50/50 solution of white vinegar and water.
- Reattach the aerator, ensuring it is securely tightened.

7. TROUBLESHOOTING

Refer to the following table for common issues and their solutions.

Problem	Possible Cause	Solution
Low Water Flow	Clogged aerator; partially closed shut-off valve; kinked supply line.	Clean aerator (see Maintenance); ensure shut-off valves are fully open; check supply lines for obstructions.
Leaks from Faucet Base	Loose mounting nuts; improper sealant application.	Tighten mounting nuts; reapply plumber's putty or silicone sealant if necessary.
Leaks from Connections	Loose supply line connections; worn washers.	Tighten supply line connections; replace washers if damaged.
Sidespray Not Working	Main faucet not running; clogged spray head; kinked hose.	Ensure main faucet is on; clean spray head; check hose for kinks.

If you encounter issues not listed here or if the suggested solutions do not resolve the problem, please contact customer support.

8. SPECIFICATIONS

Brand	Rohl
Model Name	U.4718X-EG-2
Series ID	Georgian Era

Recommended Uses	Kitchen
Mounting Type	Deck Mount
Hole Count	3
Finish Type	English Gold
Material	Brass (Faucet Body), Metal (General)
Number of Handles	2 (for hot/cold water)
Spout Design	Curved spout (C-SPOUT)
Special Features	Bridge Design, Sidespray Functionality
Maximum Flow Rate	1.8 Gallons Per Minute
Product Dimensions	17 x 26.5 x 3.75 inches
Item Weight	7 pounds
UPC	685333705794

9. WARRANTY AND SUPPORT

Warranty Information:

This ROHL faucet is backed by a **5-year Limited Warranty**. Please refer to the official ROHL warranty documentation for full terms and conditions. The product data also indicates a "lifetime" warranty type, but the specific "Warranty Description" states "5-year Limited Warranty". For precise details, consult your purchase documentation or the manufacturer's website.




Customer Support:

For technical assistance, replacement parts, or warranty claims, please contact ROHL customer service. Visit the official ROHL website for current contact information and support resources.

Website: www.rohlhome.com (Example link, please verify actual manufacturer website)

© 2023 Rohl. All rights reserved. Information subject to change without notice.

Related Documents - U.4718X-EG-2

	<p>ROHL Bar/Food Prep Kitchen Faucet Installation Manual</p> <p>Official installation instructions and parts list for the ROHL Bar/Food Prep Kitchen Faucet. Includes helpful tools, step-by-step assembly, and contact information for warranty and support.</p>
	<p>Rohl Volume Control or Diverter Trim Installation Manual</p> <p>Detailed installation instructions for Rohl Volume Control or Diverter Trim (Model INS12615A, Rev. 10/22). Includes parts list, helpful tools, and contact information for Rohl, Riobel, Perrin & Rowe, Shaws, and Victoria + Albert brands in the US and Canada.</p>
	<p>ROHL R1040R & R1062BO Installation Guide, Care, and Warranty</p> <p>Comprehensive installation instructions, care and maintenance guidelines, and warranty details for ROHL R1040R rough-in valves and R1062BO three-way diverter valves. Includes product specifications, parts lists, and finish care advice.</p>
	<p>ROHL Edwardian™ Thermostatic & Pressure Balance Valve Trim - Installation, Specifications, and Product Catalog</p> <p>Comprehensive guide for ROHL plumbing fixtures, including the Edwardian™ U.TEW44W1 valve trim, 2-Way Type T/P Coaxial Valve Rough, handshowers, showerheads, and accessories. Features installation instructions, parts lists, product specifications, finishes, warranty information, and customer support.</p>
	<p>ROHL MD08D3XM Modelle™ Widespread Lavatory Faucet Illustrated Parts List</p> <p>Detailed illustrated parts list for the ROHL MD08D3XM Modelle™ Widespread Lavatory Faucet with C-Spout. Find part numbers, descriptions, and contact information for warranty and support. Includes exploded view diagram description.</p>
	<p>ROHL R2012D Pressure Balance Rough Without Diverter Installation Guide</p> <p>Explore the ROHL R2012D Pressure Balance Rough Without Diverter, a key component for luxurious showers. This guide details features, specifications, installation, and warranty information from ROHL.</p>