

DELTA FAUCET 9992-DST

Delta Faucet Addison Chrome Bar Faucet Instruction Manual

Model: 9992-DST

SAFETY INFORMATION

Please read all instructions carefully before installation and use to ensure safe operation and prevent damage.

- Always turn off the main water supply before beginning any installation or maintenance.
- Wear appropriate personal protective equipment, such as safety glasses, during installation.
- If you are unsure about any part of the installation process, consult a qualified plumber.
- Ensure all connections are secure and leak-free before restoring water supply.

PRODUCT OVERVIEW

The Delta Faucet Addison Chrome Bar Faucet with Pull Down Sprayer (Model 9992-DST) is designed for both kitchen and wet bar applications, offering convenience and durability with its innovative features.

Key Features

- **DIAMOND Seal Technology:** Reduces leak points and ensures long-lasting, leak-free operation.
- **MagnaTite Docking:** Utilizes a powerful integrated magnet to securely hold the pull-down sprayer in place.
- **Easy Installation:** Designed for single-hole or 3-hole configurations (deck plate RP63198 sold separately for 3-hole). Includes InnoFlex PEX supply lines.
- **Touch-Clean Spray Holes:** Allows for easy wiping away of calcium and lime build-up with a finger.
- **Multi-Flow Spray Wand:** Toggle between a water-efficient spray/stream and a high water flow for faster filling.

Included Components

- Faucet Assembly

- Handle
- Sprayer
- InnoFlex PEX Supply Lines



Figure 1: The Delta Faucet Addison Chrome Bar Faucet, showcasing its elegant design and pull-down sprayer.

SETUP AND INSTALLATION

The Delta Faucet Addison is designed for straightforward installation. For detailed, step-by-step instructions, please refer to the official Installation Manual PDF:

Key Installation Considerations:

- **Mounting:** This faucet is designed to fit single-hole or 3-hole, 8-inch configurations. For 3-hole installations, a deck plate (Delta part RP63198) must be purchased separately.
- **Supply Lines:** InnoFlex PEX supply lines are integrated into the faucet, simplifying the connection process and reducing potential leak points.
- **Tools Required:** Ensure you have the necessary tools as outlined in the installation manual before starting.



Figure 2: The Delta Faucet Addison in a kitchen setting, demonstrating the convenience of its pull-down sprayer for filling containers.

OPERATING INSTRUCTIONS

The Delta Faucet Addison features a single-handle design for easy control of water temperature and flow.

Water Flow and Temperature Control:

- **Handle Operation:** Lift the single lever handle to turn on the water. Move the handle left for hot water and right for cold water. Adjust the height of the handle to control the water flow intensity.

Pull-Down Sprayer Operation:

- **Detaching the Sprayer:** Gently pull the sprayer head down from the spout. The MagnaTite Docking system will release it smoothly.
- **Spray Modes:** The Multi-Flow Spray Wand allows you to switch between two spray patterns: a standard aerated stream for everyday tasks and a powerful spray for rinsing or filling large containers faster. Use the button on the sprayer head to toggle between these modes.

- **Re-docking:** When finished, guide the sprayer head back towards the spout. The integrated magnet will securely snap it back into place, preventing drooping.

MAINTENANCE

Regular maintenance will help keep your Delta Faucet Addison in optimal condition and extend its lifespan.

Cleaning:

- **Exterior Cleaning:** Clean the faucet's exterior with a soft, damp cloth and mild soap. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the chrome finish.
- **Touch-Clean Spray Holes:** If mineral deposits build up on the spray holes, simply wipe them with your finger to dislodge the residue. This feature makes cleaning quick and easy.

General Care:

- Periodically check for any leaks around the base of the faucet or connections under the sink. Address any leaks promptly.
- Avoid hanging heavy objects from the faucet or applying excessive force to the handle, which could cause damage.

TROUBLESHOOTING

If you encounter issues with your Delta Faucet Addison, consult the following common troubleshooting tips. For more complex problems, refer to the full installation manual or contact customer support.

| Problem | Possible Cause | Solution |
|--------------------------------|---|--|
| Low Water Flow | Clogged aerator or mineral buildup in spray holes. | Clean the aerator. Use the Touch-Clean feature to clear spray holes. Check water supply valves are fully open. |
| Leaking from Faucet Base | Loose mounting nut or worn O-rings/gaskets. | Tighten mounting nut. Inspect and replace O-rings/gaskets if necessary (refer to manual for part numbers). |
| Sprayer Does Not Dock Securely | Debris in docking mechanism or issue with MagnaTite magnet. | Ensure the sprayer head and spout are clean. Check for any obstructions. |
| Water Temperature Inconsistent | Issue with hot/cold supply lines or internal valve. | Verify hot and cold water supply. If problem persists, contact Delta Faucet customer support. |

SPECIFICATIONS

Detailed technical specifications for the Delta Faucet Addison Chrome Bar Faucet (Model 9992-DST).

| Attribute | Detail |
|------------|--------------|
| Brand | DELTA FAUCET |
| Model Name | 9992-DST |

| Attribute | Detail |
|--------------------|---------------------------------|
| Color | Chrome |
| Finish Type | Chrome |
| Material | Stainless Steel, Brass (Handle) |
| Mounting Type | Single-hole |
| Number of Handles | 1 |
| Handle Type | Lever |
| Hole Count | 1 |
| Special Feature | Pull Down Sprayer |
| Maximum Flow Rate | 1.5 Gallons Per Minute |
| Valve Type | DIAMOND Seal Valve |
| Spout Height | 14.5 Inches |
| Spout Reach | 6.38 Inches |
| Item Weight | 7 Pounds |
| Product Dimensions | 6.39 x 2.5 x 6.39 inches |
| UPC | 034449638135 |

WARRANTY AND SUPPORT

Warranty Information:

Delta Non-Electronic Lifetime Faucet and Finish Limited Warranty: All parts and finishes of the Delta faucet are warranted to the original consumer purchaser to be free from defects in material and workmanship for as long as the original consumer purchaser owns their home. Delta recommends using a professional plumber for all installation and repair. Delta will replace, FREE OF CHARGE, during the warranty period, any part or finish that proves defective in material and/or workmanship under normal installation, use and service. Replacement parts may be obtained by calling 1-800-345-DELTA (3358).

Customer Support:

For further assistance, technical support, or to order replacement parts, please contact Delta Faucet customer service:

- **Phone:** 1-800-345-DELTA (3358)
- **Online:** Visit the official Delta Faucet website for support resources and contact options.
- **Installation Manual:** For detailed installation and troubleshooting, refer to the [Installation Manual \(PDF\)](#).