

Battery Tender 081-0069-8

Battery Tender 081-0069-8 Female Cigarette Adapter Accessory Cable Instruction Manual

Brand: Battery Tender | Model: 081-0069-8

PRODUCT OVERVIEW

The Battery Tender 081-0069-8 Female Cigarette Adapter Accessory Cable is designed to provide a convenient 12 Volt power source for charging various DC electronic devices. This cable allows you to power items like cell phones, tablets, and GPS tools directly from your vehicle's battery, often while the battery is also being maintained by a compatible Battery Tender charger.

It features a quick-disconnect SAE connector for easy attachment to most Battery Tender battery chargers and a female cigarette lighter socket with a protective flap to prevent dust and debris from entering.

SETUP AND INSTALLATION

Follow these steps to properly set up your Battery Tender Female Cigarette Adapter Accessory Cable:

1. **Identify the SAE Connector:** Locate the black SAE quick-disconnect connector on your Battery Tender battery charger or existing battery harness.
2. **Connect the Adapter:** Plug the male end of the 081-0069-8 accessory cable into the female SAE connector of your Battery Tender system. Ensure a secure connection.
3. **Position the Cable:** Route the 5-foot (152 cm) cable to a convenient location where you intend to charge your devices. The cable is 16 gauge for reliable power transfer.
4. **Access the Lighter Socket:** Open the protective flap on the female cigarette lighter adapter to expose the socket.



Image: A hand connecting the Battery Tender adapter to an existing battery harness on a motorcycle, illustrating the quick-disconnect feature.

CIGARETTE ADAPTER FEMALE

QUICK DISCONNECT



081-0069-8

Image: An overhead view of the Battery Tender Female Cigarette Adapter, showing its overall length of 5 feet (152 cm) and the dimensions of the cigarette lighter socket and SAE connector.



QUICK DISCONNECT FEMALE CIGARETTE ADAPTOR CABLE



STAY
CHARGED



EXTEND
BATTERY LIFE



SIMPLE
& SAFE



START WITH
TRUST



Image: A close-up of the female cigarette adapter with its protective cap, highlighting its design for dust and water prevention.

OPERATING INSTRUCTIONS

Once the accessory cable is connected to your Battery Tender system, you can begin charging your 12V DC electronic devices:

1. **Plug in Your Device:** Insert the male cigarette lighter plug of your electronic device (e.g., phone charger, GPS, air compressor) into the female cigarette lighter socket of the adapter cable.
2. **Ensure Power:** Confirm that your Battery Tender charger is powered on and connected to your vehicle's 12V battery. The accessory cable is compatible with standard 12V automotive, marine, or powersport batteries, including Lithium, Lead Acid, AGM, and Gel types.
3. **Monitor Charging:** Your device should begin charging. The Battery Tender system often includes safety features like reverse polarity protection and spark-proof design to ensure safe operation.

BATTERY COMPATIBILITY

12V

LITHIUM | LEAD ACID | AGM | GEL

CHARGES & MAINTAINS



Image: An illustration detailing the Battery Tender adapter's compatibility with 12V Lithium, Lead Acid, AGM, and Gel batteries, along with icons for various vehicles it can charge/maintain.

Safety First FEATURES



**QUICK DISCONNECT
HARNESS**



**CONNECT IT AND
FORGET IT**



SPARK PROOF

Image: A graphic emphasizing the safety features of the Battery Tender adapter, including quick disconnect harness, "connect it and forget it" functionality, and spark-proof design.

Product Video: ELFCULB 12V Car Cigarette Lighter Cable

Your browser does not support the video tag.

Video: This video demonstrates the functionality and features of a 12V car cigarette lighter cable, similar to the Battery Tender adapter, showcasing its use with various car accessories and outdoor equipment.

MAINTENANCE

To ensure the longevity and optimal performance of your accessory cable:

- **Keep Clean:** Regularly inspect the connectors for dirt, dust, or corrosion. Clean with a dry cloth if necessary.
- **Protect the Socket:** Always keep the protective flap closed over the female cigarette lighter socket when not in use to prevent dust and moisture infiltration.
- **Store Properly:** When not connected to a battery, store the cable in a dry, cool place, away from direct sunlight and

extreme temperatures. Avoid kinking or sharply bending the cable.

TROUBLESHOOTING

If you encounter issues with your Battery Tender Female Cigarette Adapter Accessory Cable, consider the following:

- **No Power to Device:**
 - Ensure the SAE connection to your Battery Tender charger or battery harness is secure.
 - Verify that your Battery Tender charger is properly connected to a power source and the vehicle battery, and is operating correctly.
 - Check the male plug of your electronic device for proper insertion into the female socket.
 - Inspect the cable for any visible damage or breaks.
- **Loose Connection:** If your device's plug feels loose in the adapter's socket, ensure it is fully inserted. Some plugs may fit more snugly than others.

For further assistance, please refer to the main Battery Tender charger manual or contact customer support.

SPECIFICATIONS

Model Number	081-0069-8
Brand	Battery Tender
Input Voltage	12 Volt DC
Cable Length	5 feet (approximately 152 cm)
Wire Gauge	16 Gauge
Connector Type	SAE Quick Disconnect to Female Cigarette Lighter Socket
Item Weight	3.2 ounces
Product Dimensions	60 x 1 x 1 inches (approximate, referring to cable length)

WARRANTY INFORMATION

Specific warranty details for the Battery Tender 081-0069-8 accessory cable may vary. Please refer to the product packaging or the official Battery Tender website for the most current and detailed warranty information. Keep your proof of purchase for any warranty claims.

CUSTOMER SUPPORT

For technical assistance, product inquiries, or warranty support, please contact Battery Tender customer service. You can find contact information and additional resources on the official Battery Tender website. Visit the [Battery Tender Store on Amazon](#) for more products and information.

