Mercedes Benz A00098623509723

Mercedes-Benz Genuine Touch-Up Paint User Manual

Model: A00098623509723

1. Product Overview

This manual provides comprehensive instructions for the proper use and maintenance of your Mercedes-Benz Genuine Cabanite Silver Touch-Up Paint (Code 723). This product is designed for minor paint repairs on your vehicle's exterior, helping to maintain its appearance and protect against corrosion.



Image: Mercedes-Benz Genuine Cabanite Silver Touch-Up Paint kit, showing two small bottles (base coat and clear coat) in packaging.

2. Safety Information

Always prioritize safety when handling paint products. Read and understand all warnings before use.

- **Ventilation:** Use in a well-ventilated area to avoid inhaling fumes. If working indoors, ensure adequate airflow.

- **Skin and Eye Protection:** Wear appropriate protective gloves and eye protection (safety glasses or goggles) to prevent skin and eye contact.
- **Flammability:** Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
- **Ingestion:** Do not ingest. If swallowed, seek immediate medical attention.
- **Children and Pets:** Keep out of reach of children and pets.
- **Disposal:** Dispose of contents and container in accordance with local, regional, national, and international regulations.

3. Setup: Surface Preparation

Proper surface preparation is crucial for a successful and durable repair.

1. **Clean the Area:** Thoroughly clean the damaged area with automotive soap and water to remove dirt, wax, and grease. Rinse well and dry completely.
2. **Remove Loose Paint/Rust:** Gently remove any loose paint flakes or rust using fine-grit sandpaper (e.g., 2000-grit) or a specialized rust remover. Feather the edges of the existing paint.
3. **Degrease:** Wipe the area with a wax and grease remover or rubbing alcohol to ensure a clean, oil-free surface. Allow to dry completely.
4. **Masking (Optional):** For larger areas or to protect surrounding paint, use automotive masking tape to tape off the repair area.

4. Operating: Application Instructions

Follow these steps carefully for optimal results. Ensure the ambient temperature is suitable for painting (typically 60-80°F / 15-27°C).

1. **Shake Paint Thoroughly:** Before opening, shake the base coat paint bottle vigorously for at least 1-2 minutes to ensure the pigment is fully mixed. You should hear the mixing ball inside.
2. **Test Color (Optional but Recommended):** Apply a small amount of paint to an inconspicuous area or a test card to verify color match before applying to the vehicle.
3. **Apply Base Coat:**
    - Using the brush applicator attached to the cap, apply a thin, even layer of the base coat directly to the prepared scratch or chip.
    - Avoid applying too much paint at once; multiple thin coats are better than one thick coat.
    - Allow each coat to dry for approximately 10-15 minutes before applying the next. Apply 2-3 thin coats until the repair area is adequately covered and matches the surrounding paint.
4. **Apply Clear Coat:**
    - Once the final base coat is dry to the touch (typically after 30 minutes to 1 hour), shake the clear coat bottle thoroughly.
    - Apply 1-2 thin, even layers of the clear coat over the repaired area. The clear coat provides gloss and protection.
    - Allow each clear coat to dry for 15-20 minutes between applications.
5. **Final Drying:** Allow the repaired area to cure completely. This can take several hours to 24 hours, depending on temperature and humidity. Avoid washing the vehicle or exposing the repaired area to harsh conditions for at least 24-48 hours.

5. Maintenance: Storage and Care

Proper storage ensures the longevity and effectiveness of your touch-up paint.

- **Storage:** Store the bottles upright in a cool, dry place, away from direct sunlight and extreme temperatures. Ensure caps are tightly sealed to prevent drying out.
- **Shelf Life:** The date on the bottle is the manufacture date, not the expiration date. When stored correctly, the paint can remain usable for an extended period.
- **Cleaning Applicators:** If you use separate brushes or applicators, clean them immediately after use with appropriate paint thinner or mineral spirits.

6. Troubleshooting

Common issues and their potential solutions:

Issue	Possible Cause	Solution
Paint appears too dark/light	Insufficient shaking; incorrect color code; lighting conditions.	Ensure thorough shaking. Verify paint code with your vehicle's VIN. Check color in natural light.
Uneven application/streaks	Too much paint applied; improper brush technique; surface not clean.	Apply thinner coats. Use light, even strokes. Re-clean and prepare surface.
Paint not drying	Too thick application; low temperature/high humidity.	Ensure thin coats. Apply in recommended temperature range with good ventilation.
Bubbles in paint	Shaking too vigorously right before application; applying too thick.	Allow paint to settle after shaking. Apply thin coats.

7. Specifications

Key technical details for your Mercedes-Benz Genuine Touch-Up Paint.

Brand: Mercedes-Benz

Color: Cabanite Silver (Code 723)

Model Number: A00098623509723

Paint Type: Enamel

Item Form: Liquid (with brush applicator)

Specific Uses: Exterior (Automotive Touch Up)

Surface Recommendation: Metal

Indoor/Outdoor Usage: Outdoor

Item Weight: Approximately 5 ounces (total package)

Product Dimensions: Approximately 6.75 x 2.75 x 1 inches

Water Resistance Level: Not Water Resistant (after application, clear coat provides protection)

8. Warranty and Support

For specific warranty information regarding your genuine Mercedes-Benz parts, please refer to the documentation

provided with your vehicle or contact an authorized Mercedes-Benz dealership.

For further assistance or inquiries, you may visit the officialMercedes-Benz Store on Amazon or consult your local Mercedes-Benz service center.

Mercedes-Benz

Image: Close-up of the Mercedes-Benz Genuine Touch-Up Paint packaging, highlighting the brand and product details.

© 2024 Mercedes-Benz. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question