Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

Jaclo 529-BKN

Jaclo 529-BKN Toe Control Drain Strainer User Manual

Model: 529-BKN

Introduction

This manual provides comprehensive instructions for the installation, operation, and maintenance of your Jaclo 529-BKN Toe Control Drain Strainer. Please read these instructions carefully before beginning installation or use to ensure proper function and longevity of the product. Retain this manual for future reference.

Product Overview

The Jaclo 529-BKN is a 2-inch toe control drain strainer designed for use in various plumbing applications, including bathroom sinks and bathtubs. It features a durable construction with a Black Nickel finish and a convenient toe-operated stopper mechanism. The removable design facilitates easy cleaning and maintenance.



Figure 1: Jaclo 529-BKN Toe Control Drain Strainer. This image displays the top view of the drain strainer, highlighting its polished

surface, the "PUSH" inscription on the stopper, and the black rubber seals.

Safety Information

- Always turn off the water supply to the fixture before beginning any plumbing work.
- Wear appropriate personal protective equipment, such as safety glasses and gloves, during installation.
- If you are unsure about any step of the installation process, consult a qualified plumber.
- Ensure all connections are watertight to prevent leaks.

Package Contents

Verify that all components are present before proceeding with installation:

- 1 x Jaclo 529-BKN Toe Control Drain Strainer (complete assembly)

Setup and Installation

Tools Recommended: Plumber's putty or silicone sealant, adjustable wrench, pipe wrench, rags, bucket.

1. **Preparation:** Ensure the drain opening is clean and free of debris. If replacing an old drain, remove it completely and clean the area thoroughly.
2. **Apply Sealant:** Apply a bead of plumber's putty or silicone sealant around the underside of the drain strainer's flange (the top part that sits in the sink/tub).
3. **Insert Strainer:** Insert the drain strainer assembly into the drain opening from above the sink or tub.
4. **Secure from Below:** From underneath the sink or tub, slide the rubber washer, then the friction washer, and finally thread the locknut onto the drain body.
5. **Tighten Connections:** Hand-tighten the locknut, then use an adjustable wrench to tighten it further. Do not overtighten, as this can damage the fixture or drain. Wipe away any excess plumber's putty or sealant.
6. **Test for Leaks:** Once installed, fill the sink or tub with water and check for any leaks around the drain assembly. If leaks are present, tighten the locknut slightly or reapply sealant if necessary.

Operating Instructions

The Jaclo 529-BKN Toe Control Drain Strainer operates with a simple push mechanism:

- **To Close the Drain:** Gently push down on the top of the stopper until it clicks into the closed position. This will seal the drain, allowing the basin to fill with water.
- **To Open the Drain:** Gently push down on the top of the stopper again until it clicks into the open position. This will allow water to drain freely.

Maintenance

Regular cleaning and maintenance will help preserve the finish and functionality of your drain strainer.

- **Cleaning the Finish:** Clean the Black Nickel finish with a soft, damp cloth and mild soap. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the finish. Rinse thoroughly and dry with a soft cloth.
- **Cleaning the Stopper:** The stopper is removable for easy cleaning. To remove, simply pull the stopper straight up from the drain opening. Clean any hair or debris accumulated around the stopper and inside the drain pipe. Reinsert the stopper by aligning it and pushing it back into place.

Troubleshooting

Problem	Possible Cause	Solution
Drain leaks around the flange.	Improperly sealed or loose locknut.	Ensure plumber's putty or silicone sealant was applied correctly. Tighten the locknut from underneath the sink/tub.
Stopper does not seal properly.	Debris under the stopper or worn seals.	Remove the stopper and clean any debris. Inspect the rubber seals for wear and replace if necessary.
Slow draining.	Hair or debris accumulation in the drain.	Remove the stopper and clear any obstructions from the drain pipe.

Specifications

Brand: Jaclo

Model: 529-BKN

Color: Black Nickel

Finish Type: Brushed

Special Feature: Removable stopper

Style: Modern

Number of Items: 1

Item Weight: 2.08 ounces

Product Dimensions: 2 x 2 x 3 inches

UPC: 020111020223

Country of Origin: United States

Warranty and Support

For warranty information or technical support regarding your Jaclo 529-BKN Toe Control Drain Strainer, please contact Jaclo customer service directly. Refer to the product packaging or the official Jaclo website for current contact details.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B006Z3R3OC

More documents and user manuals: **https://manuals.plus/**