Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

Jaclo 253-SB

Jaclo 253-SB P-Trap with Round Box Escutcheon

MODEL: 253-SB - SATIN BRASS FINISH

Introduction

This manual provides detailed instructions for the installation, functionality, maintenance, and troubleshooting of the Jaclo 253-SB P-Trap with Round Box Escutcheon. This product is designed to create a water seal in your plumbing system, preventing sewer gases from entering your living space while providing a decorative finish.

Setup and Installation

Proper installation is crucial for the effective operation of the P-trap. Please follow these steps carefully.

Tools Required:

- Adjustable Wrench
- Plumber's Putty or Thread Sealant Tape
- Bucket (for catching water during removal of old trap)
- Clean Cloths

Installation Steps:

1. **Preparation:** Ensure the water supply to the sink is turned off. Place a bucket under the existing P-trap to catch any residual water.
2. **Remove Old P-Trap (if applicable):** Loosen the slip nuts connecting the old P-trap to the tailpiece and the drainpipe. Carefully remove the old trap.
3. **Inspect Components:** Unpack the Jaclo 253-SB P-trap and inspect all components for any damage. Ensure all washers and slip nuts are present.
4. **Install Escutcheon:** Slide the round box escutcheon onto the horizontal pipe extending from the wall drain. This will cover the wall opening for a finished look.
5. **Connect Tailpiece:** Attach the upper part of the P-trap (the J-bend) to the sink's tailpiece. Hand-tighten the slip nut, then use an adjustable wrench for a final quarter-turn to ensure a snug fit without overtightening.
6. **Connect to Wall Drain:** Connect the horizontal arm of the P-trap to the drainpipe extending from the wall. Ensure

the P-trap is properly aligned. Hand-tighten the slip nut, then use an adjustable wrench for a final quarter-turn.

7. **Test for Leaks:** Turn on the water supply to the sink and allow water to run for several minutes. Carefully inspect all connections for any signs of leaks. Tighten connections slightly if leaks are detected.



This image displays the Jaclo 253-SB P-trap assembly. It features a U-shaped pipe designed to hold water, preventing sewer gases from entering the living space. The pipe is connected to a horizontal section that extends towards the wall, covered by a decorative round box escutcheon. The entire unit has a satin brass finish, providing both functionality and aesthetic appeal for plumbing installations under a sink.

Functionality

The P-trap's primary function is to maintain a water seal that blocks sewer gases from rising through the drain and entering your home. The U-shaped bend in the pipe always retains a small amount of water, acting as a barrier. This design is essential for maintaining indoor air quality and preventing unpleasant odors.

Maintenance

Regular maintenance helps ensure the longevity and proper function of your P-trap.

- **Cleaning:** Periodically clean the exterior of the P-trap with a soft cloth and a mild, non-abrasive cleaner suitable for brass finishes. Avoid harsh chemicals that can damage the satin brass.
- **Leak Inspection:** Routinely check all connections for any signs of drips or leaks. Address any leaks promptly to prevent water damage.
- **Preventing Clogs:** Avoid pouring grease, coffee grounds, or other solid waste down the drain. Use a drain strainer to catch hair and debris.

Troubleshooting

Issue	Possible Cause	Solution
Leaks at Connections	Loose slip nuts, damaged washers, improper alignment.	Tighten slip nuts. Inspect and replace damaged washers. Ensure proper alignment during installation.

Issue	Possible Cause	Solution
Slow Drain	Partial clog in the P-trap or drainpipe.	Remove the P-trap and clear any debris. Use a plumbing snake if the clog is further down the drain. Avoid chemical drain cleaners as they can damage plumbing.
Sewer Odors	P-trap dry (water seal evaporated), loose connections, or vent pipe issue.	Run water into the sink to refill the P-trap. Check for loose connections. If odors persist, consult a plumber regarding your vent system.

Specifications

- **Model Number:** 253-SB
- **Material:** Brass
- **Finish:** Satin Brass
- **Product Dimensions:** Approximately 11.5" x 3.0" x 5.25"
- **Item Weight:** 1.6 ounces
- **Country of Origin:** United States

Warranty Information

Jaclo products are manufactured to high-quality standards. For specific warranty details regarding your 253-SB P-Trap, please refer to the warranty documentation included with your purchase or visit the official Jaclo website. Keep your proof of purchase for any warranty claims.

Customer Support

If you have any questions, require assistance with installation, or encounter issues not covered in this manual, please contact Jaclo customer support. Contact information can typically be found on the product packaging or the official Jaclo website.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B007492PCG

More documents and user manuals: **https://manuals.plus/**