

Cyber Acoustics CA-3908

Cyber Acoustics CA-3908 2.1 Multimedia Speaker System User Manual

Model: CA-3908

1. SETUP GUIDE

This section provides instructions for setting up your Cyber Acoustics CA-3908 2.1 Multimedia Speaker System.

Package Contents:

- CA-3908 2.1 Speaker System (Subwoofer, two Satellite Speakers, Control Pod)
- 120V AC Power Adapter
- User Guide (this manual)

Connection Steps:

1. **Position the Subwoofer:** Place the subwoofer on a flat, stable surface, ideally on the floor near your computer or audio source. Ensure the side-firing speaker is not obstructed.
2. **Connect Satellite Speakers:** Plug the cables from the two satellite speakers into the corresponding left and right speaker output jacks on the back of the subwoofer.
3. **Connect Control Pod:** Plug the control pod cable into the dedicated port on the back of the subwoofer.
4. **Connect to Audio Source:** Plug the 3.5mm audio cable from the control pod into the headphone jack or audio output port of your computer, laptop, gaming console, tablet, or smartphone.
5. **Connect Power:** Plug the AC power adapter into the power input on the subwoofer, then plug the adapter into a standard 120V AC wall outlet.



Image: The complete Cyber Acoustics CA-3908 2.1 Multimedia Speaker System, showing the subwoofer, two satellite speakers, and the control pod.

Satellite Speakers with Sub

A 2.1 computer speaker system designed to provide the best sound for the money



Image: A satellite speaker positioned next to the subwoofer, illustrating the connection point.

2. OPERATING INSTRUCTIONS

Learn how to operate your CA-3908 speaker system using the convenient control pod.

Control Pod Functions:

- **Power On/Off:** The control pod features an on/off toggle switch. A blue LED light indicates when the system is powered on.
- **Master Volume Control:** Rotate the large dial on the top of the control pod clockwise to increase volume and counter-clockwise to decrease volume.
- **Bass Volume Control:** Use the dedicated bass control knob on the side of the pod to adjust the subwoofer's bass level.
- **3.5mm AUX Input:** An easily accessible 3.5mm auxiliary input allows for quick connection of additional audio devices.

- **Headphone Jack:** Connect headphones to the headphone jack on the control pod for private listening. Plugging in headphones will mute the speakers.

Convenient Desktop Control Pod

- LED light on/off indicator
- Power on/off toggle
- Master volume control
- Bass volume control
- 3.5mm AUX input
- Headphone port



Image: A detailed view of the desktop control pod, highlighting the LED indicator, volume dial, AUX input, and headphone port.

3. MAINTENANCE

Proper care will ensure the longevity and optimal performance of your speaker system.

Cleaning:

- Disconnect the power adapter before cleaning.
- Use a soft, dry cloth to wipe down the surfaces of the speakers, subwoofer, and control pod.
- Do not use liquid cleaners, aerosols, or abrasive chemicals, as these may damage the finish or internal components.
- Gently dust the speaker grilles with a soft brush or vacuum cleaner with a brush attachment. The cloth grilles on the satellite speakers are removable for easier cleaning.

Triple Driver Cones

Dual 2" drivers + a passive radiator with removable acoustically transparent cloth grills



Image: A satellite speaker with its acoustically transparent cloth grille partially removed, showing the triple driver cones.

4. TROUBLESHOOTING

If you encounter issues with your speaker system, refer to the following common problems and solutions.

No Sound:

- Ensure the power adapter is securely plugged into both the subwoofer and a working wall outlet.
- Verify the control pod is switched on and the blue LED is illuminated.
- Check that the master volume on the control pod is turned up.
- Confirm the 3.5mm audio cable is securely connected to both the control pod and your audio source.
- Ensure the volume on your audio source (computer, phone, etc.) is not muted or set too low.
- If headphones are plugged into the control pod, unplug them to enable speaker output.

Distorted Sound or Static:

- Reduce the volume on both the control pod and your audio source. High volume levels can cause distortion.
- Check all cable connections for looseness or damage.
- Ensure the speaker cables are fully inserted into the subwoofer.
- Move the speakers away from other electronic devices that might cause interference.
- Test with a different audio source or cable to rule out issues with the source device or cable.

No Bass:

- Adjust the bass control knob on the control pod to increase the bass level.
- Ensure the subwoofer is properly connected to the power source and the satellite speakers.
- Check the audio settings on your computer or device to ensure bass enhancement is enabled if desired.

6.5" Subwoofer

Delivers the lower frequencies known as “bass”
for a richer computer audio experience



Image: A front view of the 6.5-inch subwoofer, responsible for delivering deep bass frequencies.

5. SPECIFICATIONS

Detailed technical specifications for the Cyber Acoustics CA-3908 2.1 Multimedia Speaker System.

Feature	Specification
Model Name	CA-3908
Speaker Type	2.1 Multimedia Speaker System (Subwoofer, Satellite, Computer)
Peak Power	92 Watts
RMS Power	46 Watts
Subwoofer Diameter	6.5 Inches
Satellite Drivers	Dual 2-inch drivers + passive radiator
Connectivity Technology	Wired (3.5mm Auxiliary)
Control Method	Control Pod (Volume, Bass, On/Off, Headphone, AUX)
Product Dimensions (Subwoofer)	Approximately 10.65"D x 15.25"W x 11"H
Item Weight	14 Pounds
Color	Black
Power Source	Corded Electric (120V AC)
Manufacturer	Cyber Acoustics

6. WARRANTY INFORMATION

Your Cyber Acoustics CA-3908 2.1 Multimedia Speaker System comes with a manufacturer's warranty.

Limited Warranty:

This product includes a **1-year manufacturer warranty** from the date of purchase. This warranty covers defects in materials and workmanship under normal use. Please retain your proof of purchase for warranty claims. For detailed warranty terms and conditions, please refer to the official Cyber Acoustics website or contact customer support.

7. SUPPORT

For further assistance or inquiries regarding your Cyber Acoustics CA-3908 speaker system, please use the following resources:

Customer Service:

Cyber Acoustics has a US-based customer service team available to assist you. You can typically contact them

through the platform where you purchased the product (e.g., Amazon's customer service portal).

Additional Resources:

- **Online User Manual (PDF):** A digital version of this user manual is available for download. [Download PDF Manual](#)
- **Manufacturer Website:** Visit the official Cyber Acoustics website for product registration, FAQs, and additional support information.