

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Nora Lighting](#) /

› [Nora Lighting NS-76W 4-inch Air Tight Lensless Baffle Shower Trim User Manual](#)

## Nora Lighting NS-76W

# Nora Lighting NS-76W 4-inch Air Tight Lensless Baffle Shower Trim

## USER MANUAL

### 1. Introduction

Thank you for choosing the Nora Lighting NS-76W 4-inch Air Tight Lensless Baffle Shower Trim. This product is designed for recessed lighting applications, offering a clean and functional aesthetic. This manual provides essential information for the safe installation, operation, and maintenance of your new trim.

Please read these instructions thoroughly before installation and retain them for future reference.

### 2. Safety Information

- **WARNING:** Risk of electric shock. Disconnect power at the fuse box or circuit breaker before installation or servicing.
- This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
- Ensure all electrical connections are made correctly and securely.
- Do not install this trim in a location where it may be exposed to direct water spray unless specifically rated for such conditions. This trim is CUL rated for wet locations.
- Use only bulbs that meet the specified wattage and base type.
- Do not attempt to modify the trim. Any modifications may void the warranty and create safety hazards.

### 3. Package Contents

Verify that all components are present before beginning installation:

- Nora Lighting NS-76W 4-inch Air Tight Lensless Baffle Shower Trim (1 unit)
- Pre-installed water-tight gasket

*Note: Recessed housing and light bulb are sold separately.*

## 4. Specifications

Feature	Specification
Brand	Nora Lighting
Model Number	NS-76W
Trim Size	4 inches
Outer Diameter (OD)	5 inches
Aperture	3-1/2 inches
Product Dimensions (L x W x H)	5 x 5 x 3.5 inches
Material	Copper
Color/Finish	White
Item Weight	1 lb
Bulb Compatibility	GU5.3 and Medium (E26)
Maximum Wattage	50 watts (PAR20 Maximum)
Voltage	120 Volts
Housing Compatibility	IC & Non-IC housings
Wet Location Rated	Yes (CUL rated)
Dimmable	No (Fixture is not capable of being dimmed)
Lens Required	No
Mounting Type	Trim Clips
Warranty	1 Year Limited

## 5. Setup and Installation

This trim is designed for easy installation into compatible 4-inch recessed housings (sold separately).

- 1. Prepare for Installation:** Ensure power to the recessed housing circuit is turned OFF at the circuit breaker or fuse box.
- 2. Install Bulb (if not already in housing):** If your recessed housing requires the bulb to be installed before the trim, insert the appropriate GU5.3 or Medium (E26) bulb, not exceeding 50 watts.
- 3. Position the Trim:** Align the Nora Lighting NS-76W trim with the opening of the recessed housing. The trim includes a pre-installed water-tight gasket for wet location listing, ensuring a secure seal.
- 4. Secure the Trim:** Gently push the trim upwards into the housing. The integrated trim clips will engage with the housing, holding the trim firmly in place. Ensure the trim sits flush with the ceiling surface.
- 5. Restore Power:** Once the trim is securely installed, restore power to the circuit.



This image shows the Nora Lighting NS-76W 4-inch Air Tight Lensless Baffle Shower Trim. It features a white outer ring and a ribbed white baffle interior, designed for recessed lighting applications. The center shows the opening for the light bulb.

## 6. Operating Instructions

---

Once installed and powered, the Nora Lighting NS-76W trim operates in conjunction with your recessed lighting fixture and wall switch. Simply use the wall switch connected to the circuit to turn the light ON or OFF.

- **Bulb Replacement:** To replace the bulb, turn off power at the circuit breaker. Carefully pull down the trim to access the bulb. Replace with a compatible GU5.3 or Medium (E26) bulb, not exceeding 50 watts. Re-install the trim by pushing it back into the housing until the clips engage.
- **Non-Dimmable:** Please note that this fixture is not capable of being dimmed.

## 7. Maintenance

---

The Nora Lighting NS-76W trim requires minimal maintenance.

- **Cleaning:** Ensure power is OFF before cleaning. Wipe the trim with a soft, damp cloth. Do not use abrasive cleaners or solvents, as these may damage the finish.
- **Inspection:** Periodically inspect the trim for any signs of damage or wear. If any damage is observed, discontinue use and consult a qualified electrician.

## 8. Troubleshooting

---

- **Light does not turn ON:**
  - Check if the power supply to the fixture is ON at the circuit breaker.
  - Ensure the light bulb is correctly installed and not burnt out.
  - Verify that the bulb wattage does not exceed the maximum rating of 50 watts.
- **Trim is loose:**
  - Ensure the trim clips are properly engaged with the recessed housing. Gently push the trim firmly into the housing until it is secure.

If you experience persistent issues, consult a qualified electrician.

## 9. Warranty Information

The Nora Lighting NS-76W 4-inch Air Tight Lensless Baffle Shower Trim is covered by a **1 Year Limited Warranty** from the date of purchase. This warranty covers defects in materials and workmanship under normal use. It does not cover damage resulting from improper installation, misuse, abuse, or unauthorized modifications.

For warranty claims or further details, please refer to the official Nora Lighting warranty policy or contact their customer support.

## 10. Support

For technical assistance, product inquiries, or support, please contact Nora Lighting customer service. Contact information can typically be found on the manufacturer's official website or product packaging.

**Manufacturer:** NOR

**Brand:** Nora Lighting

**Website:** [Visit the Nora Lighting Store on Amazon](#)