

[Manuals.plus](#) /

› [Green Valley](#) /

› Green Valley Original PRO 1 135 cm Steel Roof Bar Instruction Manual

Green Valley PRO 1 135 cm

Green Valley Original PRO 1 135 cm Steel Roof Bar

INSTRUCTION MANUAL

1. Introduction

This manual provides detailed instructions for the safe and correct installation, operation, and maintenance of your Green Valley Original PRO 1 135 cm Steel Roof Bar. Please read this manual thoroughly before attempting installation or use, and retain it for future reference. Incorrect installation or use can lead to product damage, vehicle damage, or personal injury.

Safety Information:

- Always ensure all components are securely fastened before driving.
- Do not exceed the maximum load capacity specified for your roof bars or your vehicle's roof. Refer to your vehicle's owner's manual for specific load limits.
- Distribute the load evenly across the roof bars.
- Check the security of the roof bars and any attached load frequently, especially during long journeys or after driving on rough terrain.
- Adjust driving speed to suit the load and road conditions. Crosswinds and sudden braking can affect vehicle stability.
- Be aware of increased vehicle height when roof bars are installed, especially when entering garages, car washes, or low-clearance areas.

2. Package Contents

Please verify that all the following components are present in your package. If any parts are missing or damaged, contact your retailer immediately.

- 2 x Green Valley Original PRO 1 135 cm Steel Roof Bars
- 4 x Roof Bar Feet (specific to vehicle model, if applicable)
- 1 x Fitting Kit (includes bolts, washers, and clamps)
- 2 x Keys (for locking mechanisms)
- 1 x Instruction Manual (this document)

3. Setup and Installation

Installation of the Green Valley Original PRO 1 roof bars requires careful attention to detail. It is recommended to have two people for installation to ensure proper alignment and safety. Refer to your vehicle's owner's manual for specific roof mounting points and load capacities.

1. **Prepare the Vehicle:** Ensure the vehicle roof is clean and free from debris where the roof bars will be mounted. Identify the designated mounting points on your vehicle's roof (e.g., integrated rails, fixed points, door frame mounts).
2. **Assemble the Feet:** Attach the roof bar feet to the steel bars according to the specific instructions provided with your fitting kit. Ensure all bolts are hand-tightened initially.
3. **Position the Bars:** Carefully place the assembled front roof bar onto the designated mounting points on your vehicle's roof. Ensure it is centered and aligned correctly. Repeat for the rear roof bar, maintaining the recommended distance between the bars as specified in your vehicle's manual or the fitting kit instructions.
4. **Secure the Bars:** Using the provided fitting kit, secure the roof bar feet to the vehicle's mounting points. Tighten all bolts evenly and firmly using the appropriate tools. Do not overtighten.
5. **Check Security:** After tightening, firmly grasp each roof bar and attempt to move it. There should be no significant movement. Re-check all fastenings.
6. **Install End Caps/Locks:** Attach any protective end caps or locking mechanisms to the roof bar feet. Use the provided keys to lock the bars in place for added security.



Image 1: Example of Green Valley Original PRO 1 135 cm Steel Roof Bar securely installed on a vehicle's roof. The image shows the robust steel construction and the mounting feet.

4. Operating Instructions

Once installed, your Green Valley Original PRO 1 roof bars are ready for use. Always adhere to the maximum load capacity and ensure loads are properly secured.

- **Loading:** Place items such as roof boxes, bike carriers, or other accessories onto the roof bars. Ensure the weight is distributed as evenly as possible.

- **Securing the Load:** Use appropriate straps, clamps, or locking mechanisms to secure your load to the roof bars. Ensure there is no movement of the load during transit. Periodically check the security of the load during your journey.
- **Driving with Load:** Be mindful that carrying a load on your roof will affect your vehicle's handling, fuel consumption, and overall height. Drive cautiously, especially in windy conditions or when cornering.
- **Unloading:** Carefully remove the load from the roof bars. If not in use for an extended period, consider removing the roof bars to reduce wind noise and improve fuel efficiency.

5. Maintenance

Regular maintenance will ensure the longevity and safe operation of your Green Valley roof bars.

- **Cleaning:** Clean the roof bars regularly with mild soap and water. Avoid abrasive cleaners or solvents that could damage the finish.
- **Inspection:** Periodically inspect all components for signs of wear, corrosion, or damage. Check bolts, clamps, and locking mechanisms for tightness and proper function. Replace any worn or damaged parts immediately.
- **Lubrication:** If applicable, lubricate locking mechanisms with a suitable lubricant to ensure smooth operation.
- **Storage:** When not in use, store the roof bars in a dry, protected area to prevent corrosion and damage.

6. Troubleshooting

If you encounter issues with your Green Valley roof bars, refer to the following common problems and solutions:

- **Problem:** Roof bars feel loose after installation.
Solution: Re-check all mounting bolts and clamps. Ensure they are tightened firmly and evenly according to the installation instructions. Verify that the correct fitting kit for your vehicle model has been used.
- **Problem:** Excessive wind noise during driving.
Solution: Ensure the roof bars are correctly positioned and that any rubber strips or aerodynamic covers are properly installed. Check for any gaps or loose components that could cause whistling. Consider removing the bars when not in use.
- **Problem:** Difficulty locking/unlocking the bars.
Solution: Ensure the key is fully inserted and turned correctly. Apply a small amount of graphite lubricant or a suitable lock spray to the locking mechanism if it feels stiff. Do not force the lock.
- **Problem:** Damage to vehicle paintwork.
Solution: This usually indicates incorrect installation or insufficient protection. Ensure all contact points between the roof bars and the vehicle are protected with the provided pads or protective film. Always clean the roof surface before installation.

If problems persist, contact Green Valley customer support or your retailer.

7. Specifications

Model	Original PRO 1 135 cm
Material	Steel Alloy
Length	135 cm
Color	Green (referring to the brand's color scheme, the product itself is typically black/grey steel)

Vehicle Service Type	Automobile
Item Dimensions (LxWxH)	37 x 137 x 42 cm (Likely packaging or overall dimensions, not the bar itself)
Maximum Load Capacity	Refer to your vehicle's owner's manual and the specific fitting kit instructions. Do not exceed the lower of the two limits.

8. Warranty and Support

Green Valley products are manufactured to high-quality standards. For information regarding warranty coverage, please refer to the warranty card included with your product or visit the official Green Valley website. Keep your proof of purchase for any warranty claims.

For technical support, spare parts, or further assistance, please contact Green Valley customer service through their official website or the contact information provided in your product packaging.

© 2026 Green Valley. All rights reserved. This manual is subject to change without notice.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question