



[Manuals.plus](#) /

› [TOTO](#) /

› TOTO TS230E Wyeth Wall Spout Instruction Manual

TOTO TS230E

TOTO TS230E Wyeth Wall Spout Instruction Manual

Model: TS230E

INTRODUCTION

This manual provides detailed instructions for the proper installation, operation, and maintenance of your TOTO TS230E Wyeth Wall Spout. Please read all instructions carefully before beginning installation to ensure safe and correct usage. Keep this manual for future reference.

PRODUCT OVERVIEW

The TOTO TS230E Wyeth Wall Spout is designed for wall-mounted applications, featuring a sleek design and durable brass construction. It provides a laminar flow of water, ensuring a smooth and consistent stream.



Image 1: TOTO TS230E Wyeth Wall Spout, Brushed Nickel finish. This image shows the elegant, curved design of the wall-mounted spout.

Key Features:

- **Laminar Flow:** Provides a clear, non-aerated stream of water.
- **Wyeth Family Design:** Styled to complement other products in the TOTO Wyeth collection.
- **Brass Construction:** Ensures durability and longevity.
- **1/2-Inch NPT Connection:** Standard plumbing connection for easy installation.

SAFETY INFORMATION

Always observe the following safety precautions during installation and use:

- Turn off the main water supply before beginning any plumbing work.
- Wear appropriate personal protective equipment, such as safety glasses and gloves.
- If you are unsure about any part of the installation process, consult a qualified plumber.
- Ensure all connections are secure to prevent leaks.
- Do not overtighten connections, as this can damage components.

SETUP AND INSTALLATION

This section outlines the general steps for installing the TOTO TS230E Wyeth Wall Spout. Specific wall conditions and existing plumbing may require additional steps or professional assistance.

1. **Prepare the Wall:** Ensure the wall opening is correctly sized and positioned for a wall-mounted spout. The spout requires a single hole installation.
2. **Connect Water Supply:** Connect the 1/2-inch NPT water supply line to the spout's inlet. Use plumber's tape or thread sealant on all threaded connections to prevent leaks.
3. **Secure the Spout:** Insert the spout into the wall opening and secure it according to the specific mounting hardware provided (not detailed in this general manual, refer to packaging for specific hardware instructions). Ensure the spout is level and firmly attached.
4. **Test for Leaks:** Slowly turn on the main water supply and check all connections for leaks. Tighten any leaking connections as necessary.
5. **Final Inspection:** Verify that the spout is securely mounted and functioning correctly.



Image 2: Underside view of the TOTO TS230E Wyeth Wall Spout, showing the connection point for plumbing. This view highlights the threaded inlet for water supply.

OPERATING INSTRUCTIONS

The TOTO TS230E Wyeth Wall Spout is designed to deliver water with a laminar flow. Operation typically involves a separate faucet handle or valve (not included with the spout) to control water temperature and flow rate. Once the water supply is activated via the control valve, water will flow smoothly from the spout.

MAINTENANCE

Proper care and maintenance will ensure the longevity and appearance of your brushed nickel spout.

- **Regular Cleaning:** Clean the spout regularly with a soft, damp cloth and mild soap.
- **Avoid Abrasives:** Do not use abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the brushed nickel finish.
- **Dry After Use:** Wipe the spout dry after each use to prevent water spots and mineral buildup.
- **Inspect Connections:** Periodically check all plumbing connections for any signs of leaks or corrosion.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Low Water Flow	Partially closed water supply valve; debris in the water line.	Ensure the water supply valve is fully open. Check for and remove any debris from the water line or spout outlet.
Leaks at Connections	Loose connections; insufficient plumber's tape/sealant.	Turn off water supply. Carefully tighten connections. If necessary, disassemble, reapply plumber's tape/sealant, and reassemble.
Water Spots/Stains	Hard water deposits; improper cleaning.	Wipe the spout dry after each use. Clean with a soft cloth and mild soap. For stubborn spots, use a vinegar solution (diluted) and rinse thoroughly.

SPECIFICATIONS

Attribute	Detail
Brand	TOTO
Model Name	TS230E#BN (Wyeth Wall Spout)
Mounting Type	Wall Mount
Finish Type	Brushed Nickel
Material	Brass
Installation Type	Single Hole
Connection Size	1/2-Inch NPT
Item Weight	2.5 Pounds
UPC	739268225428
ASIN	B009IJ34SO

WARRANTY AND SUPPORT

For information regarding the product warranty, please refer to the warranty card included with your purchase or visit the official TOTO website. For technical support or assistance with parts, please contact TOTO customer service directly.

TOTO Customer Service: Please visit www.totousa.com/support for contact information and support resources.

