

PROFLO PFWPLUSA6032

PROFLO PFWPLUSA6032 Lansford 60" x 32" Drop-In 8-Jet Whirlpool Bathtub User Manual

Model: PFWPLUSA6032

1. INTRODUCTION

This manual provides essential instructions for the safe installation, operation, and maintenance of your PROFLO PFWPLUSA6032 Lansford 60" x 32" Drop-In 8-Jet Whirlpool Bathtub. Please read this manual thoroughly before installation and use to ensure proper function and longevity of your product. Retain this manual for future reference.

2. SAFETY INFORMATION

Observe all local plumbing and electrical codes. Improper installation or use can lead to serious injury or property damage. Always consult with qualified professionals for installation.

- **Electrical Safety:** Ensure the electrical supply meets the product's requirements (115 Volts). All electrical connections must be performed by a licensed electrician and comply with local codes. The unit must be connected to a Ground-Fault Circuit Interrupter (GFCI).
- **Water Temperature:** Do not exceed 104°F (40°C) water temperature to avoid hyperthermia.
- **Chemicals:** Use only recommended cleaning agents. Avoid abrasive cleaners or harsh chemicals that can damage the acrylic surface or internal components.
- **Supervision:** Children and individuals with health conditions should be supervised when using the whirlpool tub.
- **Entry/Exit:** Exercise caution when entering and exiting the tub to prevent slips and falls.

3. PRODUCT OVERVIEW

The PROFLO PFWPLUSA6032 Lansford is a 60" x 32" drop-in whirlpool bathtub designed for a relaxing bathing experience. It features durable acrylic construction and 8 hydro-massage jets.

Key Features:

- Durable acrylic construction for heat retention and easy cleaning.
- 8 hydro-massage jets for a therapeutic bathing experience.
- Designed for drop-in installation.
- Reversible drain placement for flexible installation.
- Suitable for both residential and commercial applications.



Figure 1: Top-down view of the PROFLO PFWPLUSA6032 Lansford Whirlpool Bathtub, highlighting the jet placement and overall design.

4. SETUP AND INSTALLATION

Installation of the PROFLO PFWPLUSA6032 whirlpool bathtub should be performed by a qualified plumber and licensed electrician in accordance with all local building and plumbing codes.

Pre-Installation Steps:

1. **Inspect Tub:** Carefully inspect the tub for any shipping damage before installation. Do not install a damaged tub.
2. **Site Preparation:** Ensure the installation area is level, structurally sound, and properly prepared for a drop-in tub. Verify rough-in dimensions match the tub specifications.
3. **Access:** Plan for future access to the pump and plumbing connections for maintenance.
4. **Electrical Requirements:** A dedicated 115 Volt, GFCI-protected circuit is required for the whirlpool pump.
5. **Plumbing Connections:** Prepare hot and cold water supply lines and a drain connection. The tub features reversible drain placement, allowing flexibility.

Drop-In Installation:

1. **Set Tub:** Carefully lower the tub into the prepared opening. Ensure it is level and fully supported around its perimeter.
2. **Connect Plumbing:** Connect the drain assembly and water supply lines. Test for leaks before proceeding.
3. **Connect Electrical:** A licensed electrician should connect the whirlpool pump to the dedicated GFCI circuit.
4. **Final Sealing:** Apply a waterproof sealant around the tub's perimeter where it meets the deck or surround.
5. **Test Operation:** Fill the tub with water and test the whirlpool system to ensure all jets function correctly and there are no leaks.

5. OPERATING INSTRUCTIONS

Follow these steps for safe and effective operation of your whirlpool bathtub.

1. **Fill the Tub:** Ensure the water level is at least 2 inches above the highest jet opening before activating the whirlpool system. Operating the pump without sufficient water can cause damage.
2. **Activate Jets:** Locate the control button (typically pneumatic or electronic) on the tub deck. Press the button to turn the whirlpool jets on.
3. **Adjust Jets:** Some jets may have adjustable nozzles to direct water flow. Rotate or pivot the jet face to customize the massage.
4. **Deactivate Jets:** Press the control button again to turn off the whirlpool system.
5. **Drain Tub:** After use, open the drain to empty the tub.

Important: Do not add bath oils, salts, or other additives that are not specifically designed for whirlpool tubs, as they can clog the jets or damage the pump.

6. MAINTENANCE

Regular maintenance will help preserve the appearance and functionality of your PROFLO whirlpool tub.

- **Surface Cleaning:** Clean the acrylic surface with a soft cloth and a non-abrasive, mild bathroom cleaner. Avoid harsh chemicals, abrasive pads, or solvents, which can scratch or dull the finish.
- **Jet Cleaning:** Periodically fill the tub with warm water and add a small amount of a whirlpool system cleaner (or a few tablespoons of dishwasher detergent). Run the jets for 10-15 minutes, then drain and rinse thoroughly.
- **Drain Cleaning:** Regularly remove and clean the drain cover to prevent hair and debris buildup.
- **General Inspection:** Periodically check all visible plumbing and electrical connections for any signs of wear or leaks.

7. TROUBLESHOOTING

Refer to this section for common issues and their potential solutions. For problems not listed or if solutions do not resolve the issue, contact customer support.

Problem	Possible Cause	Solution
Jets do not activate	No power to pump; GFCI tripped; Insufficient water level.	Check power supply and GFCI. Ensure water level is above jets.
Weak jet pressure	Clogged jets; Air intake blocked; Low water level.	Clean jets. Ensure air intake is clear. Verify adequate water level.
Water leaks	Loose plumbing connections; Damaged seals.	Tighten connections. Inspect and replace damaged seals. Contact a professional.
Unusual noise from pump	Debris in pump; Air in system; Loose mounting.	Turn off power and inspect pump for debris. Bleed air from system if applicable. Ensure pump is securely mounted.

8. SPECIFICATIONS

Model Number	PFWPLUSA6032
Brand	PROFLO
Dimensions (L x W x H)	60" x 17.25" x 19.5"
Installation Type	Drop-In
Material	Acrylic

Color	White
Capacity	50 Gallons
Number of Jets	8
Voltage	115 Volts
Item Weight	83 Pounds
UPC	781889197486

9. WARRANTY INFORMATION

The PROFLO PFWPLUSA6032 Lansford Whirlpool Bathtub is covered by a limited warranty.

- **Residential Warranty:** 5 years from the date of purchase.
- **Commercial Warranty:** 1 year from the date of purchase.

For detailed terms and conditions of the limited warranty, please refer to the official PROFLO warranty documentation or contact PROFLO customer support.



10. CUSTOMER SUPPORT





If you have any questions regarding the installation, operation, maintenance, or warranty of your PROFLO PFWPLUSA6032 Lansford Whirlpool Bathtub, please contact PROFLO customer support for assistance.
For contact information, please visit the official PROFLO website or refer to your purchase documentation.



© 2023 PROFLO. All rights reserved. Information in this manual is subject to change without notice.

Related Documents - PFWPLUSA6032

	<p>PROFLO 72 x 36 Acrylic Whirlpool Tub - Specifications and Installation Guide</p> <p>Detailed specifications, features, model numbers, recommended parts, warranty information, and installation instructions for the PROFLO 72 x 36 inch acrylic whirlpool bathtub. Includes dimensions and electrical requirements.</p>
	<p>PROFLO HET Toilet Bowl and Tank Installation Instructions (1.28 GPF)</p> <p>Comprehensive installation guide for the PROFLO HET Toilet Bowl and Tank, featuring 1.28 gallons per flush. Includes tools needed, removal of old toilet, installation steps, adjustments, troubleshooting, and warranty information.</p>

 <p>PROFLO PF644 PVC CABLE DRAIN & OVERFLOW</p> <p>Model Number: PF644CP, PF644ZBN</p> <p>Material: PVC</p> <p>Finish: White</p> <p>Dimensions: 1/2" x 1/2" x 1/2"</p> <p>Weight: 1.5 lbs</p> <p>Installation: See instructions for details.</p> <p>Warranty: 5 Year Limited</p>	<p>PROFLO PF644 PVC Cable Drain & Overflow - Specifications and Features</p> <p>Detailed specifications, product features, model numbers (PF644CP, PF644ZBN), and warranty information for the PROFLO PF644 PVC Cable Drain & Overflow system. Includes dimensions and installation compatibility for bathtubs.</p>
 <p>PROFLO Enameled Steel Tubs Installation Guide</p> <p>Model Number: PFB14, PFB16, PFB54</p> <p>Material: Enamel Steel</p> <p>Finish: White</p> <p>Dimensions: 1/2" x 1/2" x 1/2"</p> <p>Weight: 1.5 lbs</p> <p>Installation: See instructions for details.</p> <p>Warranty: 5 Year Limited</p>	<p>PROFLO Enameled Steel Tubs Installation Guide PFB14, PFB16, PFB54 Series</p> <p>Comprehensive installation instructions for PROFLO Enameled Steel Tubs, including important warnings, care guidelines, and warranty information for PFB14, PFB16, and PFB54 series.</p>
 <p>PROFLO PFX308 / PFX3085 TWO HANDLE COMMERCIAL DECK FAUCET</p> <p>Model Number: PFX308, PFX3085</p> <p>Material: Brass</p> <p>Finish: Chrome</p> <p>Dimensions: 1/2" x 1/2" x 1/2"</p> <p>Weight: 1.5 lbs</p> <p>Installation: See instructions for details.</p> <p>Warranty: 5 Year Limited</p>	<p>PROFLO PFX308/PFX3085 8-Inch Commercial Deck Faucet Parts and Warranty</p> <p>Detailed parts breakdown and warranty information for the PROFLO PFX308 and PFX3085 8-inch commercial deck faucets, including model numbers, part codes, materials, and compliance standards.</p>
 <p>PROFLO PFXC8027 Faywood Single-Handle Pull-Down Kitchen Faucet</p> <p>Model Number: PFXC8027</p> <p>Material: Brass</p> <p>Finish: Chrome</p> <p>Dimensions: 1/2" x 1/2" x 1/2"</p> <p>Weight: 1.5 lbs</p> <p>Installation: See instructions for details.</p> <p>Warranty: 5 Year Limited</p>	<p>PROFLO PFXC8027 Faywood Single-Handle Pull-Down Kitchen Faucet Specifications</p> <p>Detailed specifications for the PROFLO PFXC8027 Faywood Single-Handle Pull-Down Kitchen Faucet, including product features, model numbers, dimensions, warranty, and certifications.</p>