

[Manuals.plus](#) /

› [Drop Stop](#) /

› Drop Stop - The Original Patented Car Seat Gap Filler Instruction Manual

Drop Stop DR001

Drop Stop - The Original Patented Car Seat Gap Filler Instruction Manual

Brand: Drop Stop

Model: DR001

PRODUCT OVERVIEW

The Drop Stop is an innovative car accessory designed to prevent items from falling into the gap between your car seat and the center console. This patented device provides 100% gap coverage, ensuring that phones, keys, food, and other small items remain accessible and do not get lost in hard-to-reach areas. It attaches securely to the seat belt catch and moves with the seat, eliminating the need for constant readjustment.



Image: Drop Stop installed in a vehicle, demonstrating its function in preventing items from falling into the seat gap.

KEY FEATURES

- **100% Gap Coverage:** Designed to block the entire gap in front of, surrounding, and behind the seat belt catch.
- **Secure Attachment:** Attaches directly to the seat belt catch via a built-in slot, ensuring it moves seamlessly with the seat.
- **Universal Fit:** Engineered to fit most vehicles, adapting to various gap sizes due to its high-grade neoprene casing.
- **Durable Material:** Made from high-grade neoprene, which is squishy, flexible, and designed for long-lasting use without falling apart.
- **Blends Seamlessly:** The black color blends with most car interiors, making it discreet once installed.
- **Bonus Items:** Each package includes two Drop Stops (one for the driver side and one for the passenger side), a Slide Free Pad, and an LED Credit Card Light.



Image: The contents of the Drop Stop package, showing the two gap fillers and included bonus items.

SETUP AND INSTALLATION

Preparation:

- Ensure your car's interior is clean and free of debris in the seat gap area.
- For easier installation, recline the seat back as far as possible to create a wider gap between the seat and the center console.
- It is recommended to install the Drop Stop from the opposite seat (e.g., install the driver's side Drop Stop from the passenger seat) to avoid compressing the seat cushion against the console, which can make installation difficult.

Installation Steps:

1. Locate the patented seat belt slot on the Drop Stop.
2. Slide the seat belt buckle through this slot. The Drop Stop is designed to fit snugly around the buckle.
3. Push the Drop Stop down into the gap between the seat and the center console, ensuring it goes all the way to the bottom of the seat belt.
4. While pushing down, pull the Drop Stop tight from the front to ensure a snug fit. The neoprene material will stretch and conform to the shape of your car's interior.
5. Once installed, adjust your seat back to your preferred driving position. The Drop Stop will move with your seat, remaining securely in place.

Your browser does not support the video tag.

Video: Official Drop Stop Pro Installation Tips. This video demonstrates the recommended steps for installing the Drop Stop in your vehicle, including seat adjustment and proper placement around the seat belt buckle.



Image: An illustration of items, such as french fries, falling into the car seat gap, highlighting the common issue the Drop Stop addresses.



Image: A smartphone caught in the car seat gap, showing how the Drop Stop prevents items from disappearing into the hard-to-reach space.

OPERATING INSTRUCTIONS

Once properly installed, the Drop Stop operates passively. It continuously blocks the gap between your car seat and the center console, preventing items from falling through. No further action is required for its daily operation. It is designed to remain in place even when the seat is moved forward or backward, thanks to its attachment to the seat belt buckle.

MAINTENANCE

To maintain the cleanliness and effectiveness of your Drop Stop, it can be periodically cleaned. The neoprene material is durable and can be hand-washed with mild soap and water. Allow it to air dry completely before reinstalling. Avoid using harsh chemicals or abrasive cleaners, as these may damage the material.

TROUBLESHOOTING

Issue	Solution
Drop Stop shifts or pops out when seat is adjusted.	Ensure the seat is fully reclined during installation to maximize the gap. Re-tuck firmly into the gap. The neoprene material is designed to flex with seat movement, but a very tight initial fit is crucial.
Items are still falling into the gap.	Verify that the Drop Stop is pushed all the way down into the gap and that the seat belt buckle is correctly threaded through its designated slot. Ensure there are no large gaps around the product.
Product appears dirty or stained.	Clean the Drop Stop by hand-washing with mild soap and water. Allow it to air dry completely before reinstallation.

SPECIFICATIONS

Attribute	Detail
Manufacturer	Drop Stop
Model Name	Car Seat Gap Filler
Item Model Number	DR001
Item Weight	11.2 ounces
Product Dimensions	17.95 x 5.04 x 2.6 inches
Country of Origin	China

WARRANTY AND SUPPORT

The Drop Stop product is covered by the manufacturer's standard warranty. For specific warranty details, product support, or to address any issues not covered in this manual, please contact Drop Stop LLC directly through their official website or the retailer where the product was purchased. Keep your proof of purchase for warranty claims. For additional information and resources, visit the official Drop Stop Store: [Drop Stop Store on Amazon](#).

