Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

Flex Seal FSR20

Flex Seal Spray Rubber Sealant Coating User Manual

Model: FSR20 - Black, 14 oz

1. Introduction

Flex Seal Spray is an all-purpose, rubberized sealant coating designed to stop leaks quickly. It seeps into cracks and holes, drying to a watertight, flexible, rubberized coating. This product effectively seals out water, air, and moisture, prevents rust, and can be painted once dry. It remains flexible and pliable, offering long-lasting protection.
Ideal for various applications including gutters, roof repair, RVs, wood, and metal surfaces. It is also suitable for arts, crafts, projects, and hobbies.

2. Safety Information

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. MAY CAUSE FIRE. CONTENTS UNDER PRESSURE. RESPIRATORY TRACT IRRITATION. CONTENTS UNDER PRESSURE.

- Read entire can label carefully before use.
- Wear face and eye protection, protective gloves, and clothing during application.
- Ensure the surface is clean, dry, and free of grease, oil, dirt, and debris.
- Use in a well-ventilated area. Prevent vapor buildup by opening doors and windows. Ensure fresh air entry during application and drying.
- Do not use near heat, sparks, open flames, or other sources of ignition. Do not smoke.
- When spraying indoors, use a respirator. Vapors are heavier than air and can accumulate in low areas.
- Allow adequate ventilation during and after application.
- This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm (Proposition 65 warning).

3. Product Overview

Flex Seal Spray is a versatile rubberized coating that provides a durable, waterproof barrier. Key features include:

- Stops leaks fast and seals out water, air, and moisture.

- Prevents rust and corrosion.
- Dries to a flexible, rubberized coating.
- Paintable once dry.
- Maintains flexibility and pliability for many years.
- Will not sag or drip in summer heat.
- Will not crack or peel in winter cold.



Image: Flex Seal Spray can highlighting its consistent, effective formula.

4. Setup and Preparation

1. **Clean the Surface:** Ensure the surface is clean, dry, and free of grease, oil, dirt, and debris for optimal adhesion.



Image: Illustration depicting the cleaning of a surface before application.

2. **Shake Well:** Shake the can vigorously for at least one minute before use to ensure proper mixing of the contents.

5. Operating Instructions (Application)

1. **Spray Distance:** Hold the can 8 to 12 inches from the surface you intend to coat.




Image: Illustration showing the recommended spray distance for Flex Seal.

2. **Apply Even Coats:** Apply several even coats, ensuring complete coverage. For best results, apply multiple thin coats rather than one thick coat.



Image: Illustration demonstrating the application of multiple coats.

3. **Drying Time:** The product will be dry to the touch in approximately 2 to 6 hours. Full cure time is typically 24 to 48 hours. Drying time is dependent on temperature and humidity.



Image: Illustration indicating the 24 to 48 hour curing time.

4. **Sealing Cracks and Holes:** Make sure all gaps, cracks, and holes are completely filled and the product has fully cured before sealing. If you see an opening or if light passes through, apply additional coats as needed to ensure the area is completely sealed.
5. **Paintable:** Once fully dry, Flex Seal Spray can be painted any color.

Application Examples:



Applying Flex Seal to a leaking gutter.



Sealing a window frame with Flex Seal.



Protecting a wooden chair with Flex Seal.



Repairing a concrete crack with Flex Seal.



Sealing an RV seam for waterproofing.



Protecting a rusty car undercarriage from corrosion.



Waterproofing and protecting a mailbox.

6. Maintenance

Flex Seal Spray is designed for long-lasting durability. Once cured, it forms a robust, flexible barrier that:

- Will not sag or drip in high summer temperatures.
- Will not crack or peel in cold winter conditions.

Regular inspection of the coated area is recommended to ensure the integrity of the seal, especially in areas subject to extreme wear or environmental exposure. Reapply as needed for continued protection.

7. Troubleshooting

Clogged Nozzle:

If the nozzle becomes clogged, invert the can and apply a short burst until the nozzle clears. If clogging persists, the nozzle may need to be cleaned or replaced.

8. Specifications

Feature	Detail
Brand	Flex Seal
Model	FSR20
Color	Black
Item Weight	14 ounces
Unit Count	14 Ounce
Item Dimensions (L x W x H)	9.5 x 2.5 x 2.5 inches
Material	Plastic (can material)
Item Form	Spray
Water Resistance Level	Waterproof
Compatible Material	Rubber, Wood, Metal, etc.
Surface Recommendation	Roof, Windows, Wood, Gutters, RVs
UPC	855647003019

9. Warranty

This product comes with a**1 Year Limited Warranty**. For specific terms and conditions, please refer to the official Flex Seal Products website or contact customer support.

10. Support

For additional information, product inquiries, or support, please visit the official Flex Seal Store:

Visit the Flex Seal Store on Amazon

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B00CD9FGNW

More documents and user manuals: **https://manuals.plus/**