Monroe 172144

Monroe Quick-Strut 172144 Suspension Strut and Coil Spring Assembly

Instruction Manual

For Honda CR-V (2002-2006)

1. Introduction

This manual provides essential information for the proper installation, operation, and maintenance of your Monroe Quick-Strut 172144 Suspension Strut and Coil Spring Assembly. Designed for 2002-2006 Honda CR-V models, this complete assembly offers a comprehensive solution for strut replacement, aiming to restore original equipment (OE) ride height and handling characteristics.

The Monroe Quick-Strut assembly is engineered for durability and ease of installation, eliminating the need for a spring compressor. Please read all instructions carefully before proceeding with installation or maintenance.



Figure 1: Monroe Quick-Strut 172144 Suspension Strut and Coil Spring Assembly.

2. Product Overview and Components

The Monroe Quick-Strut assembly is a fully integrated unit designed to simplify suspension repair. It includes all necessary components pre-assembled for a direct fit replacement.

- **Preassembled Upper Strut Mount:** Helps ensure smooth, precise steering and reduces noise, vibration, and harshness.
- **OE-Style Coil Spring:** Application-specific design engineered to restore ride height and support the vehicle's weight.
- **OE-Quality Strut Technology:** Delivers improved control and handling.
- **Durable Boot Kit:** Protects the strut rod from contaminants.
- **Robust Bearing Plate:** For reliable performance.
- **SAE-Grade Nuts & Bolts:** Ensures secure fastening.



Figure 2: Exploded view illustrating the components of the Monroe Quick-Strut assembly.

3. Setup and Installation

Compatibility: This Monroe Quick-Strut assembly (Model 172144) is compatible with **2002-2006 Honda CR-V** vehicles. Always verify compatibility with your specific vehicle before installation.

Safety First: Suspension work can be complex and requires specialized tools and knowledge. It is highly recommended that installation be performed by a qualified automotive technician. If you choose to perform the installation yourself, ensure you have the correct tools, follow all safety precautions, and properly support the vehicle.

Installation Benefits: The Quick-Strut design simplifies the repair process by providing a fully assembled unit, eliminating the need for a spring compressor, which enhances safety and reduces installation time.

General Installation Steps (Consult a service manual for detailed vehicle-specific instructions):

1. Safely lift and support the vehicle on jack stands. Remove the wheel.
2. Locate and loosen the upper strut mounting nuts under the hood.
3. Disconnect any brake lines, ABS sensor wires, or sway bar links attached to the strut assembly.
4. Remove the lower strut mounting bolts from the steering knuckle.
5. Carefully remove the old strut assembly from the vehicle.
6. Install the new Monroe Quick-Strut assembly, ensuring proper alignment of mounting points.
7. Secure all bolts and nuts to the manufacturer's specified torque settings.
8. Reattach any disconnected lines or links.
9. Reinstall the wheel and lower the vehicle.
10. Perform a wheel alignment after installation to ensure proper vehicle handling and tire wear.



Figure 3: Illustrative image of a Quick-Strut assembly during installation.



Figure 4: The complete Quick-Strut assembly simplifies the repair process.

4. Operating Characteristics and Benefits

Once installed, the Monroe Quick-Strut assembly works to optimize your vehicle's suspension performance:

- **Restores Ride Height:** Each application-specific coil spring is precisely calibrated to meet OE design, restoring the vehicle's original ride height and supporting its weight effectively.
- **Maintains Vehicle Control:** The assembly reduces body sway, vibration, and road harshness, preventing these from reaching the passenger cabin and improving overall vehicle handling.
- **Improves Steering:** The premium upper strut mount contributes to smooth, 'like-new' steering precision, while also reducing noise, vibration, harshness, and memory steer.
- **Rust Protection:** A protective coating is applied to reduce rust, ensuring durability against environmental elements.



Figure 5: The coil spring is designed to restore original ride height.



Figure 6: The upper strut mount enhances steering precision.

5. Maintenance

To ensure the longevity and optimal performance of your Monroe Quick-Strut assembly, consider the following maintenance practices:

- **Regular Inspections:** Periodically inspect the struts, springs, and mounting components for any signs of wear, damage, or leaks. Look for rust, cracks, or unusual noises.
- **Wheel Alignment:** Always perform a wheel alignment after replacing suspension components to ensure correct steering and prevent premature tire wear. Regular alignment checks are also recommended.
- **Tire Rotation and Balance:** Maintain proper tire rotation and balance to reduce stress on suspension components.
- **Professional Check-ups:** Have your vehicle's suspension system inspected by a professional technician during routine service appointments.

6. Troubleshooting

If you experience any issues with your vehicle's suspension after installing the Monroe Quick-Strut assembly, consider the following common troubleshooting points. For complex issues, professional diagnosis is recommended.

- **Uneven Ride Height:** If the vehicle sits higher or lower than expected, verify that the correct part number was installed for your specific vehicle year and model. Ensure all components are seated correctly and mounting bolts are torqued to specification.
- **Unusual Noises (Clunking, Squeaking):** Check all mounting points for proper torque. Inspect for any loose components or interference with other vehicle parts. A professional can help identify the source of the noise.
- **Poor Handling or Steering Issues:** An immediate wheel alignment is crucial after strut replacement. If handling issues persist, re-check installation, and consult a technician for further diagnosis of steering and suspension components.
- **Vibration:** Ensure wheels are balanced and tires are in good condition. Check for any loose suspension components or worn bushings.

7. Specifications

Attribute	Detail
Brand	Monroe
Model Number	172144
Auto Part Position	Front
Vehicle Service Type	Car (Honda CR-V 2002-2006)
Material	Alloy Steel
Item Weight	5 pounds
Product Dimensions	25.4 x 9.8 x 10.6 inches
UPC	048598140548

8. Official Product Videos

For additional visual guidance and information, please refer to the official product videos below:

About Monroe Quick-Strut Complete Strut Assemblies

Your browser does not support the video tag.

Video 1: This video provides an overview of the Monroe Quick-Strut Complete Strut Assemblies, detailing their design and benefits.

Monroe Quick-Strut Assembly: Built for Durability

Your browser does not support the video tag.

Video 2: This video highlights the robust construction and durability features of the Monroe Quick-Strut Assembly.

Monroe Quick Strut Product Overview

Your browser does not support the video tag.

Video 3: A concise product overview of the Monroe Quick-Strut, covering its key features and advantages.

9. Warranty and Support

Monroe offers a 'Feel the Difference Guarantee' which typically includes a trial period. For specific warranty details, terms, and conditions, please refer to the official Monroe website or contact Monroe customer support directly. Keep your purchase receipt for warranty claims.

For technical assistance, installation questions, or to report any issues, please contact Monroe customer service through their official channels.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question