

## Kawasaki 49065-2071

# Kawasaki 49065-2071 Oil Filter Instruction Manual

Genuine OEM Replacement Part

[Introduction](#)   [Compatibility](#)   [Installation](#)   [Maintenance](#)   [Specifications](#)   [Troubleshooting](#)  
[Warranty](#)   [Support](#)

## 1. INTRODUCTION

This manual provides essential information for the proper use and installation of the Kawasaki 49065-2071 Oil Filter. This is a genuine OEM Kawasaki part designed for specific 4-stroke engines in various vehicles. The Kawasaki 49065-2071 Oil Filter is a direct replacement for part numbers 16097-0003, 49065-2087, and 49065-2057.



Image: The Kawasaki 49065-2071 Oil Filter shown alongside its official packaging box.

## 2. COMPATIBILITY

---

This oil filter is compatible with a wide range of Kawasaki 4-stroke engines found in Personal Watercraft, All-Terrain Vehicles (ATVs), and Utility Task Vehicles (UTVs). It is crucial to consult your machine's specific service manual to confirm the correct part number before installation.

Known compatible vehicle types include:

- Jet Ski models: SX-R, STX-12F, STX-15F, Ultra 250X, Ultra 260X, Ultra 260LX, Ultra LX, Ultra 300X, Ultra 300LX, Ultra 310LX, Ultra 310X, Ultra 310X SE, Ultra 310R
- Teryx models: 750 FI 4X4, 750 FI 4X4 SPORT, 750 4x4 NRA Outdoors, 750 FI 4x4 LE, 750 FI 4x4 SGE, 750 FI 4x4 LE SGE, Teryx, Teryx LE, Teryx CAMO, Teryx4, Teryx4 LE, Teryx4 CAMO, Teryx4 750 4x4, Teryx4 750 EPS, Teryx4 750 EPS LE
- MULE PRO-MX models: (EPS) LE, (EPS), CAMO (EPS)
- Prairie models: 360 4x4, 360, 360 4x4 Hardwoods Green HD, 360 4x4 Realtree APG HD
- Brute Force models: 750 4x4i, 650 4x4, 750 4x4i Realtree Hardwoods Green HD, 750 4x4i NRA Outdoors, 750 4x4i EPS

This list is not exhaustive. Always refer to your vehicle's owner's manual for the most accurate compatibility information.

## 3. INSTALLATION INSTRUCTIONS

---

Proper installation of the oil filter is critical for engine performance and longevity. Follow these steps carefully:

1. **Preparation:** Ensure the engine is cool. Place a drain pan beneath the oil filter location to catch any residual oil. Remove the old oil filter.
2. **Gasket Lubrication:** Apply a thin coat of clean engine oil to the rubber gasket of the new Kawasaki 49065-2071 Oil Filter. This ensures a proper seal and prevents the gasket from sticking or tearing during installation.
3. **Hand Tightening:** Thread the new oil filter onto the engine by hand. Turn the filter until the gasket makes contact with the engine's mounting surface.
4. **Final Tightening:** Once the gasket contacts the mounting surface, tighten the filter an additional 3/4 of a turn by hand. Do not overtighten, as this can damage the filter or engine.
5. **Check for Leaks:** After installation, start the engine and let it run for approximately 3 minutes. Carefully inspect the area around the oil filter for any signs of oil leaks. If leaks are detected, turn off the engine and re-check the filter's tightness.



Image: The Kawasaki 49065-2071 Oil Filter with printed installation guidelines for gasket lubrication and tightening.

## 4. MAINTENANCE

Regular oil filter replacement is essential for maintaining engine health and performance. Refer to your vehicle's owner's manual for the recommended oil change and filter replacement intervals. Typically, this is based on operating hours or mileage.

Always use genuine Kawasaki replacement parts to ensure optimal fit and filtration performance.

## 5. SPECIFICATIONS

Feature	Detail
Brand	Kawasaki
Model Number	49065-2071
Manufacturer Part Number	49065-2071
OEM Equivalent Part Numbers	16097-0003, 49065-2087, 49065-2057
Material	Paper

Product Grade	Replacement Part
Vehicle Service Type	Personal Watercraft, All-Terrain Vehicles, Utility Task Vehicles
Item Dimensions (L x W x H)	3.25 x 3 x 3 inches
Outside Diameter	3 Inches
Thread Size	3/4" - 16 UNF
Item Weight	6.4 ounces



Image: Top view of the Kawasaki 49065-2071 Oil Filter, highlighting the internal structure and gasket.

## 6. TROUBLESHOOTING

### Oil Leakage After Installation

- **Cause:** Insufficient tightening, damaged gasket, or debris on the mounting surface.
- **Solution:** Turn off the engine. Carefully re-check the tightness of the oil filter, ensuring it is hand-tightened an additional 3/4 turn after gasket contact. If the leak persists, remove the filter, inspect the gasket for damage, and ensure the engine's mounting surface is clean. Replace the filter if the gasket is damaged.

## Difficulty Removing Old Filter

- **Cause:** Overtightening during previous installation or prolonged use.
- **Solution:** Use an appropriate oil filter wrench. Ensure the wrench is correctly sized and applied to avoid crushing the filter housing.

## 7. WARRANTY INFORMATION

---

The Kawasaki 49065-2071 Oil Filter comes with a Limited Warranty from the manufacturer. For specific details regarding warranty coverage, terms, and conditions, please refer to the documentation provided with your original vehicle or contact Kawasaki customer service.

## 8. CUSTOMER SUPPORT

---

For further assistance, technical inquiries, or to locate authorized service centers, please refer to your vehicle's owner's manual or visit the official Kawasaki website. Always provide the model number (49065-2071) when seeking support for this product.