

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

- › [Duravit](#) /
- › [Duravit 2545090092 Wall-Mounted Washdown Toilet User Manual](#)

## Duravit 2545090092

# Duravit 2545090092 Wall-Mounted Washdown Toilet User Manual

Model: 2545090092 | Brand: Duravit

## 1. INTRODUCTION

This manual provides essential information for the safe and efficient installation, operation, and maintenance of your Duravit 2545090092 Wall-Mounted Washdown Toilet. Please read these instructions carefully before beginning installation or use, and retain them for future reference. This wall-mounted toilet features a washdown model design in White Alpin ceramic, offering a sleek and space-saving solution for modern bathrooms.

## 2. SAFETY INFORMATION

**WARNING:** Improper installation or use can lead to injury or product damage. Always follow local plumbing and building codes.

- Ensure all water supply lines are turned off before installation.
- Wear appropriate personal protective equipment (PPE) during installation, including gloves and eye protection.
- The toilet is heavy (approximately 64.25 lbs). Use proper lifting techniques or seek assistance to prevent injury.
- Verify that the wall structure and mounting frame (not included) are capable of supporting the toilet's weight and user load.
- Do not use abrasive cleaners or harsh chemicals, as these can damage the ceramic finish.

## 3. PACKAGE CONTENTS

Please check that all components are present before beginning installation:

- Duravit 2545090092 Wall-Mounted Washdown Toilet Bowl (White Alpin)

- Durafix mounting hardware
  - *Note: Toilet seat, concealed cistern, and flush plate are sold separately.*
- 

## **4. SETUP AND INSTALLATION**

Installation of a wall-mounted toilet requires professional plumbing knowledge and adherence to local building codes. It is highly recommended to have this product installed by a qualified plumber.

### **4.1 Pre-Installation Checks**

- Ensure the concealed cistern and mounting frame are correctly installed and secured within the wall according to the manufacturer's instructions.
- Verify that the water supply and waste connections are properly positioned and accessible.
- Confirm that the wall surface is prepared for the toilet bowl installation.

### **4.2 Mounting the Toilet Bowl**

1. Attach the Durafix mounting hardware to the toilet bowl as per the included instructions.
2. Carefully align the toilet bowl with the threaded rods extending from the concealed frame.
3. Slide the toilet bowl onto the threaded rods, ensuring a snug fit against the finished wall.
4. Secure the toilet bowl using the provided nuts and washers, tightening them evenly to prevent stress on the ceramic. Do not overtighten.
5. Connect the water supply and waste pipes to the toilet bowl, ensuring all seals are watertight.
6. Install the toilet seat (sold separately) according to its manufacturer's instructions.



*Image 1: Duravit 2545090092 Wall-Mounted Washdown Toilet in a modern bathroom setting.*



*Image 2: Dimensional drawing showing measurements for the Duravit 2545090092 toilet bowl.*

## **5. OPERATING INSTRUCTIONS**

The Duravit 2545090092 is a washdown model toilet designed for efficient flushing. Operation is straightforward:

- **Flushing:** Press the flush plate (not included, typically installed above the toilet) to activate the flushing mechanism. Most flush plates offer dual-flush options for water conservation (a smaller button for liquid waste, a larger button for solid waste).
- **Toilet Seat:** The toilet seat (if soft-close) will lower gently on its own. Avoid forcing it down to prevent damage to the soft-close mechanism.

---

## 6. MAINTENANCE AND CARE

Regular cleaning and proper maintenance will ensure the longevity and hygiene of your Duravit toilet.

### 6.1 Cleaning the Ceramic Surface

- Use a soft cloth or sponge with a mild, non-abrasive bathroom cleaner.
- Wipe down all ceramic surfaces, including the bowl interior and exterior.
- Rinse thoroughly with clean water and dry with a soft cloth to prevent water spots.
- *Avoid using abrasive powders, scouring pads, or cleaners containing strong acids, alkalis, or bleach, as these can damage the ceramic glaze.*

### 6.2 Cleaning the Toilet Seat

- Clean the toilet seat with a mild soap and water solution.
- Do not use harsh chemicals or abrasive cleaners on the seat, as this can cause discoloration or damage.
- Many Duravit seats feature quick-release hinges for easy removal and thorough cleaning. Consult your toilet seat manual for specific instructions.

### 6.3 General Maintenance

- Periodically check all connections for leaks.
- Ensure the flush plate mechanism operates smoothly.
- If the toilet is not in use for an extended period, consider turning off the water supply to the cistern.

---

## 7. TROUBLESHOOTING

This section addresses common issues you might encounter. For complex problems, contact a qualified plumber.

Problem	Possible Cause	Solution
Weak Flush	Low water level in cistern, partially closed stopcock, clogged rim jets.	Adjust water level in cistern, fully open stopcock, clean rim jets.
Toilet Leaks	Loose connections, worn seals, cracked ceramic.	Tighten connections, replace seals, contact a plumber for ceramic damage.
Continuous Water Flow	Faulty flush valve in cistern, flush plate stuck.	Inspect and adjust/replace flush valve, ensure flush plate moves freely.

---

## 8. SPECIFICATIONS

Feature	Detail
Brand	Duravit
Model Number	2545090092
Color	White Alpin
Material	Ceramic
Installation Method	Wall Mounted
Product Dimensions (D x W x H)	13.63"D x 14.38"W x 13.63"H
Item Weight	64.25 Pounds
Bowl Shape	Oblong
Included Components	Toilet bowl, Durafix mounting hardware

---

## 9. WARRANTY AND SUPPORT

For warranty information and customer support, please refer to the official Duravit website or contact your local Duravit dealer. Keep your proof of purchase for any warranty claims.

**Contact Information:**

- **Manufacturer:** Duravit
- **Website:** [www.duravit.com](http://www.duravit.com) (Please check for regional websites)