

[Manuals.plus](#) /

> [NBS](#) /

> NBS Motorcycle Parts Center 316601 Jog ZR Rear Spoiler User Manual

NBS 316601

NBS Motorcycle Parts Center 316601 Jog ZR Rear Spoiler User Manual

Model: 316601

1. PRODUCT OVERVIEW

This manual provides instructions for the installation, maintenance, and care of the NBS Motorcycle Parts Center 316601 Jog ZR Rear Spoiler. This component is designed to enhance the aesthetic appeal and potentially the aerodynamic profile of compatible Yamaha JOG ZR SA36J/39J models.



Figure 1.1: The NBS Motorcycle Parts Center 316601 Jog ZR Rear Spoiler, shown from a top-front angle, highlighting its sleek black finish and mounting points. Three small metal bushings are visible below the spoiler.



Figure 1.2: A top-rear view of the NBS Motorcycle Parts Center 316601 Jog ZR Rear Spoiler, providing a different perspective of its contours and the placement of the mounting holes. The three metal bushings are also visible.



Figure 1.3: A side profile view of the NBS Motorcycle Parts Center 316601 Jog ZR Rear Spoiler, illustrating its depth and how it would sit on the motorcycle. This view emphasizes the curved design.

2. SPECIFICATIONS

Attribute	Value
Brand	NBS
Model Number	316601
Compatible Models	Yamaha JOG (SA36J/39J)
Colour	black (black 19-3911tcx)
Product Dimensions (L x W x H)	32.11 x 30 x 7.59 cm
Item Weight	540 g (approx. 20.0 oz)
Position	Rear
Assembly Required	Yes

3. SETUP AND INSTALLATION

3.1 Unpacking

- Carefully open the packaging and remove the rear spoiler and any accompanying hardware.
- Inspect all components for any signs of damage during transit. If any damage is found, do not proceed with installation and contact your retailer.
- Verify that all parts listed in the product packaging are present. This typically includes the spoiler unit and any necessary mounting bushings or screws.

3.2 Installation

Installation of the rear spoiler requires basic mechanical aptitude and common hand tools (e.g., screwdrivers, wrenches). It is recommended to consult your motorcycle's service manual for specific instructions regarding the removal of existing components and access to mounting points.

- Preparation:** Ensure the motorcycle is stable, preferably on a center stand or paddock stand. Turn off the engine and remove the key.
- Access Mounting Area:** Depending on your specific Yamaha JOG ZR model, you may need to remove existing rear body panels or an old spoiler to access the mounting points. Refer to your vehicle's service manual for precise instructions.
- Position the Spoiler:** Carefully align the new NBS rear spoiler with the designated mounting holes on the motorcycle's frame or existing structure.
- Secure the Spoiler:** Insert the provided mounting hardware (e.g., screws, bushings) through the spoiler's mounting holes and into the corresponding points on the motorcycle. Hand-tighten all fasteners initially.
- Final Tightening:** Once all fasteners are in place and the spoiler is correctly aligned, progressively tighten them using

- appropriate tools. Do not overtighten, as this can strip threads or crack the spoiler material. Ensure the spoiler is securely fastened and does not wobble.
6. **Reassemble:** Reinstall any body panels or components that were removed to facilitate the installation.
7. **Final Check:** Before riding, perform a final visual and physical check to ensure the spoiler is firmly attached and all components are correctly reassembled.

4. OPERATING

The NBS Motorcycle Parts Center 316601 Jog ZR Rear Spoiler is a static, non-moving component. Its primary function is to provide an aesthetic enhancement to your motorcycle. While designed to complement the vehicle's lines, any aerodynamic benefits are typically minor for this type of accessory on a scooter.

No specific operational procedures are required for the spoiler itself once it is correctly installed.

5. MAINTENANCE

- Proper maintenance will help preserve the appearance and integrity of your rear spoiler.
- **Cleaning:** Clean the spoiler regularly with a soft cloth and mild, non-abrasive automotive soap. Rinse thoroughly with water and dry with a clean microfiber towel to prevent water spots. Avoid harsh chemicals or abrasive cleaners that could damage the finish.
 - **Inspection:** Periodically check the mounting fasteners for tightness. Vibrations from riding can sometimes cause fasteners to loosen over time. Tighten any loose fasteners immediately to prevent rattling or detachment.
 - **Damage Check:** Inspect the spoiler for any cracks, chips, or other damage, especially after impacts or falls. Damaged spoilers should be replaced to maintain appearance and structural integrity.

6. TROUBLESHOOTING

Most issues related to the rear spoiler are minor and can be resolved with simple checks.

Problem	Possible Cause	Solution
Spoiler is loose or rattling	Loose mounting fasteners	Tighten all mounting fasteners securely. Do not overtighten.
Spoiler does not fit correctly	Incorrect model application or improper alignment during installation	Verify that the spoiler is the correct model for your Yamaha JOG ZR (SA36J/39J). Re-align and re-install, ensuring all mounting points are correctly engaged.
Scratches or dull finish	Improper cleaning or exposure to harsh elements	Clean with mild automotive soap and soft cloth. For minor scratches, consider using a plastic polish designed for automotive finishes.

7. OFFICIAL PRODUCT VIDEOS

No official product videos from the seller are available for this item at this time.

8. WARRANTY AND SUPPORT

Specific warranty information for the NBS Motorcycle Parts Center 316601 Jog ZR Rear Spoiler is not provided in the product details. Please refer to your purchase receipt or contact the retailer directly for details regarding warranty coverage and support.

For technical assistance or further inquiries, it is recommended to contact the manufacturer or the point of purchase.

© 2024 NBS. All rights reserved.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

<https://manuals.plus/asin/B00FB0HSTK>

More documents and user manuals: <https://manuals.plus/>