

[Manuals.plus](#) /

> [ColorRite](#) /

> ColorRite YSF Metallic Triton Blue Touch-Up Paint Jar Instruction Manual for Suzuki M90

ColorRite TU4400-30-3908

ColorRite YSF Metallic Triton Blue Touch-Up Paint Jar Instruction Manual for Suzuki M90

Model: TU4400-30-3908

1. INTRODUCTION

This manual provides detailed instructions for the proper use and application of the ColorRite YSF Metallic Triton Blue Touch-Up Paint Jar kit, specifically formulated for Suzuki M90 motorcycles. This kit includes two 2-ounce jars: one containing the factory-matched color paint and another containing a high-quality clearcoat for a durable finish.

2. SAFETY INFORMATION

- Use in a well-ventilated area to avoid inhaling fumes.
- Wear appropriate personal protective equipment, including gloves and eye protection.
- Avoid contact with skin and eyes. In case of contact, rinse immediately with plenty of water and seek medical advice.
- Keep out of reach of children and pets.
- Store in a cool, dry place away from direct sunlight and ignition sources.
- This product is flammable. Do not use near open flames or sparks.

3. PRODUCT OVERVIEW

The ColorRite touch-up paint kit consists of two distinct jars, each containing 2 ounces of product. The first jar contains the YSF Metallic Triton Blue color paint, and the second jar contains a clearcoat. Both jars are designed for brush application to address small nicks and scratches.



Image 1: The ColorRite touch-up paint kit, showing the color paint jar and the clearcoat jar.

4. PREPARATION

1. **Clean the Surface:** Thoroughly clean the area to be touched up. Ensure it is free of dirt, grease, wax, and rust. Use a mild cleaner and allow the surface to dry completely.
2. **Shake Jars:** Before each use, shake both the color paint jar and the clearcoat jar vigorously for at least one minute to ensure proper mixing of pigments and components.
3. **Perform a Test Application (Spray-Out):** It is critical to perform a test application on an inconspicuous area or a piece of scrap material that mimics the original surface. This allows you to verify the color

match and practice your application technique before applying to the intended part. Note that it is not possible to correctly match faded or damaged paint.

5. APPLICATION

5.1. Color Paint Application

1. Carefully unscrew the cap of the YSF Metallic Triton Blue color paint jar. The cap includes a brush applicator.
2. Wipe any excess paint from the brush against the inside rim of the jar to prevent drips and ensure a thin application.
3. Apply thin, even coats of the color paint to the damaged area. For small chips or scratches, a light dabbing motion may be effective.
4. Allow each coat to dry for approximately 10-15 minutes before applying the next. Multiple thin coats are preferable to one thick coat, as this helps prevent runs and ensures a smoother finish.
5. Continue applying coats until the damaged area is adequately covered and the color depth matches the surrounding paint.



Image 2: Brush applicator being used with the ColorRite touch-up paint jar.

5.2. Clearcoat Application

1. Once the final coat of color paint is dry to the touch (typically 30-60 minutes, depending on conditions), unscrew the cap of the clearcoat jar.
2. Apply thin, even coats of clearcoat over the touched-up area. The clearcoat provides protection, enhances gloss, and helps blend the repair with the original finish.
3. Allow each clearcoat layer to dry for 10-15 minutes between applications. Apply 2-3 coats for optimal protection and shine.

6. DRYING AND CURING

Drying times can vary based on temperature, humidity, and coat thickness. While paint may be dry to the touch within minutes, full curing can take several hours to days. Avoid washing or waxing the touched-up area for at least 72 hours to allow for complete curing.

7. MAINTENANCE

Once fully cured, the touched-up area can be maintained like the rest of your vehicle's finish. Regular cleaning and waxing will help preserve the appearance and longevity of the repair.

8. TROUBLESHOOTING

- **Color Does Not Match:** Ensure you performed a test application. ColorRite guarantees a match to your original factory color, but cannot match faded or damaged paint. If the color still appears off after a test, contact ColorRite support.
- **Uneven or Bumpy Finish:** This often results from applying coats too thickly or not allowing sufficient drying time between coats. For best results, apply multiple thin layers.
- **Runs or Drips:** Too much paint on the brush or applying too much paint in one area can cause runs. Wipe excess paint from the brush before application.

9. STORAGE

Store both paint jars in a cool, dry, and dark place. Ensure the caps are tightly sealed to prevent the paint from drying out. Proper storage helps maintain the product's shelf life.

10. SPECIFICATIONS

Brand	ColorRite
Color	YSF Metallic Triton Blue
Model Number	TU4400-30-3908
Product Type	Touch-Up Paint Jar (Color + Clearcoat)
Volume	2 oz. per jar (total 4 oz.)
Intended Use	Suzuki M90 Motorcycles

11. WARRANTY AND SUPPORT

ColorRite guarantees that our paint will match your original factory color. This guarantee does not apply to faded or damaged paint, as an accurate match is not possible under such conditions. Performing a test application (spray-out) is crucial to ensure satisfaction.

For further assistance, technical support, or questions regarding your ColorRite product, please refer to the official ColorRite website or contact their customer service department.

