Fujifilm XF10-24MMF4 R OIS

Fujifilm Fujinon XF10-24mmF4 R OIS Lens Instruction Manual

Model: XF10-24MMF4 R OIS

1. Product Overview

The Fujifilm Fujinon XF10-24mmF4 R OIS is a high-performance wide-angle zoom lens designed for Fujifilm X-mount cameras. It offers a versatile focal length range equivalent to 15-36mm in 35mm format, making it suitable for landscapes, architecture, and interior photography. The lens features a constant F4 maximum aperture and Optical Image Stabilization (OIS) for enhanced performance in various lighting conditions.



Figure 1: Front view of the Fujinon XF10-24mmF4 R OIS lens with its lens hood.

Key Features:

- Equivalent to 35mm format 15-36 mm focal length.
- Fixed F4 aperture for consistent exposure across the zoom range.
- Optical Image Stabilization (OIS) to reduce camera shake.
- 14 elements in 10 groups, including 4 aspherical and 3 extra-low dispersion elements for superior image quality.
- Wide-angle lens type.

2. Setup and Installation

Attaching the Lens:

1. Ensure your camera is powered off.

2. Remove the rear lens cap and the camera body cap by twisting them counter-clockwise.
3. Align the white mounting index mark on the lens with the corresponding mark on the camera body.
4. Insert the lens into the camera mount and rotate it clockwise until it clicks into place. Do not force the lens.
5. Remove the front lens cap.



Figure 2: Rear view of the lens, showing the mounting mechanism.

Removing the Lens:

1. Ensure your camera is powered off.
2. Press and hold the lens release button on the camera body.
3. While holding the button, rotate the lens counter-clockwise until it detaches from the camera body.
4. Attach the front and rear lens caps to protect the lens elements.

3. Operating Instructions

Zooming:

Rotate the zoom ring to adjust the focal length between 10mm and 24mm. The lens maintains its F4 aperture throughout the entire zoom range.



Figure 3: The lens with visible zoom ring and focal length indicators (10, 14, 18, 20, 24mm).

Aperture Control:

The lens features an aperture ring for direct control over the F-stop. Rotate the aperture ring to select your desired aperture setting. The constant F4 aperture allows for consistent light gathering capabilities.

Optical Image Stabilization (OIS):

The OIS function helps to reduce blur caused by camera shake, especially useful in lower light conditions or when shooting handheld. Locate the OIS switch on the side of the lens barrel to turn the stabilization on or off as needed.



Figure 4: Side view of the lens, highlighting the OIS (Optical Image Stabilization) switch.

4. Care and Maintenance

- **Cleaning the Lens:** Use a soft, lint-free cloth and a specialized lens cleaning solution to gently wipe the lens elements. Avoid touching the glass with your fingers.
- **Storage:** When not in use, always attach the front and rear lens caps. Store the lens in a dry, cool place, away from direct sunlight and extreme temperatures.
- **Handling:** Avoid dropping or subjecting the lens to strong impacts. This can damage the internal optical elements and mechanical components.
- **Dust and Moisture:** While the lens is robust, it is not weather-sealed. Avoid exposing it to excessive dust, sand, or moisture.

5. Troubleshooting

Image Blur:

- Ensure the OIS switch is set to 'ON' if shooting handheld in low light.
- Check your shutter speed. For sharp images, especially with wider lenses, a general rule is to use a shutter speed faster than 1/focal length (e.g., 1/10s for 10mm).
- Verify that the lens is securely attached to the camera body.

Autofocus Issues:

- Ensure there is sufficient light on your subject for the camera's autofocus system to operate effectively.
- Clean the lens contacts on both the lens and camera body.
- Check your camera's autofocus settings to ensure they are appropriate for your shooting situation.

6. Technical Specifications

Specification	Value
Product Dimensions	3.43 x 3.07 x 3.07 inches
Item Weight	14.5 ounces
Item Model Number	XF10-24MMF4 R OIS
Focal Length Description	10-24 millimeters
Lens Type	Wide Angle
Compatible Mountings	Other (Fujifilm X-mount)
Manufacturer	Fujifilm

Specification	Value
Date First Available	December 19, 2013

7. Warranty and Support Information

Warranty:

This product is covered by a 90-day parts and labor warranty. For specific warranty details and terms, please refer to the documentation provided at the time of purchase or contact Fujifilm customer support.

Support:

For technical assistance, service, or further inquiries regarding your Fujinon XF10-24mmF4 R OIS lens, please visit the official Fujifilm support website or contact their customer service department. Keep your purchase receipt and product serial number (e.g., SERIAL #45A00894) handy when seeking support.

© 2026 Fujifilm. All rights reserved.