

[Manuals.plus](#) /

› [Rust-Oleum](#) /

› Rust-Oleum Industrial Choice S1600 System Inverted Striping Paint Spray Manual

Rust-Oleum 1691838

Rust-Oleum Industrial Choice S1600 System Inverted Striping Paint Spray Manual

Model: 1691838

INTRODUCTION

This manual provides instructions for the safe and effective use of the Rust-Oleum Industrial Choice S1600 System Inverted Striping Paint Spray. This industrial-grade aerosol paint is designed to create crisp, clean, and long-lasting lines on various surfaces. Please read this manual thoroughly before use to ensure proper application and safety.

IMPORTANT SAFETY INFORMATION

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Always use in a well-ventilated area. Wear appropriate personal protective equipment (PPE) including gloves, eye protection, and a respirator.

- Keep out of reach of children.
- Flammable liquid and vapor. Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
- Pressurized container: May burst if heated. Do not pierce or burn, even after use.
- Do not expose to temperatures exceeding 120°F (49°C).
- Avoid contact with skin and eyes. In case of contact, rinse immediately with plenty of water and seek medical advice.
- Do not ingest. If swallowed, call a poison control center or doctor immediately.
- Dispose of contents/container in accordance with local regulations.

PRODUCT OVERVIEW

The Rust-Oleum Industrial Choice S1600 System Inverted Striping Paint is an 18 oz aerosol can designed for creating durable lines. It is suitable for indoor and outdoor use on surfaces such as concrete, gravel, or other types of pavement. Each can can produce approximately 300 linear feet of a 2-inch stripe.



Image: Rust-Oleum Industrial Choice S1600 System Inverted Striping Paint Spray can. This image shows the white aerosol can with the Rust-Oleum branding, designed for inverted spraying.

SETUP

1. **Surface Preparation:** Ensure the surface to be striped is clean, dry, and free of loose debris, oil, or grease.
2. **Shake Can:** Shake the aerosol can vigorously for at least one minute after the mixing ball begins to rattle. Continue to shake occasionally during use.
3. **Insert into Striping Machine (Recommended):** For straight, consistent 2-4 inch lines, insert the inverted striping paint can into a compatible striping machine, such as the Rust-Oleum Striping Machine #2395000. Ensure the can is securely seated.
4. **Test Spray:** Before applying to the desired surface, perform a test spray on a scrap piece of material to ensure proper spray pattern and color.



Image: A bundle of Rust-Oleum Industrial Choice S1600 System Inverted Striping Paint Spray cans. This image illustrates multiple cans, often used for larger projects, highlighting the product's availability in quantities.

OPERATING INSTRUCTIONS

This paint is designed for inverted spraying. If not using a striping machine, ensure the can is held upside down during application.

1. **Positioning:** Position the striping machine (or hold the can inverted) at the desired starting point for your line.
2. **Application:** Depress the spray nozzle or activate the trigger on the striping machine. Move at a steady, consistent pace to ensure an even coat. Overlapping slightly on subsequent passes can help achieve a uniform line.
3. **Line Width:** The paint is designed to create 2-inch wide stripes. The Rust-Oleum Striping Machine #2395000 can adjust for 2-4 inch lines.
4. **Drying Time:** Allow adequate drying time between coats if multiple coats are desired. Refer to the product label for specific recoat times.
5. **Coverage:** Each 18 oz can covers approximately 300 linear feet for a 2-inch stripe.

MAINTENANCE AND STORAGE

- **Clear Nozzle:** After each use, invert the can and spray for 2-3 seconds to clear the nozzle. This prevents clogging for future use.
- **Storage:** Store cans in a cool, dry, well-ventilated area away from direct sunlight, heat sources, and open flames. Do not store at temperatures above 120°F (49°C).
- **Disposal:** Dispose of empty cans and any unused paint in accordance with local waste disposal regulations. Do not puncture or incinerate cans.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Uneven or inconsistent line	Inconsistent speed during application; clogged nozzle; insufficient shaking.	Maintain a steady pace. Clear nozzle by inverting and spraying. Shake can thoroughly before and during use.

Problem	Possible Cause	Solution
No paint sprays	Clogged nozzle; empty can.	Clear nozzle. Replace can if empty.
Paint drips or runs	Applying too much paint; holding can too close to surface.	Apply thinner coats. Maintain recommended distance from surface.

SPECIFICATIONS

Brand: Rust-Oleum

Model Name: Industrial Choice S1600 System Inverted Striping Paint Spray

Model Number: 1691838

Color: White

Finish Type: Gloss

Item Volume: 18 fluid ounces (per can)

Container Type: Aerosol Can

Paint Type: Spray

Special Feature: Inverted Spraying

Specific Uses: Interior/Exterior striping on concrete, gravel, pavement

Item Weight: 1.1 pounds (per can)

UPC: 020066169183

WARRANTY AND SUPPORT

For specific warranty information or technical support, please refer to the product packaging or visit the official Rust-Oleum website. Contact information for customer service can typically be found on the product label or manufacturer's website.

Rust-Oleum Website: www.rustoleum.com

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question