MAHLE MS19385

MAHLE MS19385 Exhaust Manifold Gasket Set Instruction Manual

Introduction Safety Installation Post-Installation Maintenance Troubleshooting Specifications Support

1. Introduction

This manual provides essential instructions for the proper installation and maintenance of the MAHLE MS19385 Exhaust Manifold Gasket Set. This product is designed to provide a reliable seal for your vehicle's exhaust manifold, meeting or exceeding original equipment specifications. Proper installation is crucial for optimal performance and longevity.
The MAHLE MS19385 gasket set contains all necessary gaskets for the exhaust manifold application, ensuring a complete and secure seal.

2. Safety Information

WARNING: Automotive repair can be dangerous. Always follow safety precautions to prevent injury or damage.

- Ensure the vehicle's engine is completely cool before beginning any work on the exhaust system. Hot components can cause severe burns.
- Wear appropriate personal protective equipment (PPE), including safety glasses, gloves, and hearing protection.
- Work in a well-ventilated area to avoid inhaling exhaust fumes.
- Securely lift and support the vehicle using jack stands if working underneath. Never rely solely on a jack.
- Disconnect the vehicle's battery before starting work to prevent electrical shorts.
- Refer to your vehicle's specific service manual for detailed torque specifications and procedures.

3. Package Contents

The MAHLE MS19385 Exhaust Manifold Gasket Set includes:

- Exhaust Manifold Gaskets (quantity as required for application)



Figure 1: MAHLE MS19385 Exhaust Manifold Gasket Set. The image displays two exhaust manifold gaskets alongside their blue and white MAHLE branded packaging.

4. Installation Instructions

These are general installation guidelines. Always consult your vehicle's specific service manual for precise instructions and torque specifications.

4.1. Preparation

1. Park the vehicle on a level surface and engage the parking brake.
2. Allow the engine to cool completely.
3. Disconnect the negative terminal of the battery.
4. Gather necessary tools, including wrenches, sockets, torque wrench, gasket scraper, wire brush, and cleaning solvent.
5. If necessary, lift the vehicle safely using a jack and support it with jack stands.

4.2. Removal of Old Gasket

1. Locate the exhaust manifold. Depending on the vehicle, this may require removing other components for access.
2. Disconnect the exhaust pipe from the manifold.
3. Carefully unbolt and remove the exhaust manifold from the engine cylinder head. Keep track of all fasteners.
4. Remove the old gasket material from both the cylinder head and the exhaust manifold surfaces. Use a gasket scraper and wire brush to ensure all surfaces are clean and free of debris, carbon buildup, or old gasket residue.
5. Inspect the manifold for cracks or warping. Address any issues before proceeding.

4.3. Installation of New Gasket

1. Ensure both the cylinder head and exhaust manifold mating surfaces are perfectly clean and dry.
2. Carefully position the new MAHLE MS19385 gasket onto the cylinder head studs or align it with the bolt holes on the manifold. Ensure correct orientation.
3. Reinstall the exhaust manifold onto the cylinder head, ensuring the gasket remains properly seated.
4. Install the manifold bolts and tighten them finger-tight.
5. Using a torque wrench, tighten the manifold bolts to the manufacturer's specified torque in the recommended sequence (usually a crisscross pattern). Refer to your vehicle's service manual for exact specifications.
6. Reconnect the exhaust pipe to the manifold, tightening fasteners to specification.
7. Reinstall any components removed for access.
8. Reconnect the negative battery terminal.

5. Post-Installation Checks

1. Start the engine and listen for any exhaust leaks. Leaks may sound like a ticking or hissing noise.
2. Visually inspect the manifold area for any signs of leaks or loose connections.
3. Allow the engine to reach operating temperature, then shut it off and allow it to cool.
4. After the first heat cycle, it is recommended to re-check the torque on the exhaust manifold bolts, as some settling may occur.

6. Maintenance

Exhaust manifold gaskets generally do not require routine maintenance after proper installation. However, periodic inspection is recommended:

- During routine vehicle inspections, visually check the exhaust manifold area for any signs of exhaust leaks (e.g., black soot, unusual noises).
- If any signs of leakage are detected, investigate the cause and address it promptly to prevent further damage.

7. Troubleshooting

Problem	Possible Cause	Solution
Exhaust leak after installation	Improper gasket seating, insufficient bolt torque, warped manifold, damaged gasket during installation.	Re-check bolt torque. If leak persists, remove manifold, inspect gasket and mating surfaces for damage or debris, and reinstall with a new gasket if necessary. Ensure manifold is not warped.

Problem	Possible Cause	Solution
Engine noise (ticking/hissing)	Common symptom of an exhaust leak.	Follow steps for "Exhaust leak after installation".

8. Specifications

- **Brand:** MAHLE
- **Model Number:** MS19385
- **Material:** OE Equivalent
- **Part Type:** Exhaust Manifold Gasket Set
- **Manufacturer:** MAHLE Original
- **UPC:** 027067718921

9. Warranty and Support

MAHLE Original gaskets are manufactured to meet or exceed original equipment specifications, ensuring high quality and reliable performance. For specific warranty information or technical support, please refer to the official MAHLE website or contact MAHLE customer service directly.
You can find more information and contact details on theMAHLE Store on Amazon or the official MAHLE website.

© 2023 MAHLE. All rights reserved. This document is for informational purposes only.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question